

*****READ & SAVE THESE INSTRUCTIONS *****
MODEL 52029
INSTALLATION & OPERATION INSTRUCTIONS

1) TOOLS AND MATERIALS REQUIRED

- ❖ Blade Screwdriver
- ❖ Star Screwdriver
- ❖ Wire Cutters
- ❖ Wiring supplies as required by Electrical Code
- ❖ 3 x GU-10 120v 35w Maximum Bulbs

Attention:

Before assembling your lighting fixture, please read the following instructions.

(2) GENERAL

1. To ensure the success of the installation, be sure to read these instructions thoroughly before beginning.
2. All electrical connections must be in accordance with local codes, ordinances, or the National Electrical Code. If you are unfamiliar with methods of installing electrical wiring, secure the services of a qualified licensed electrician.
3. These fixtures are intended for mounting to a standard 4" x 2 1/4" deep metal octagon outlet box. The box must be directly supported by the building structure.
4. Before commencing with the installation, **disconnect the power by turning off the circuit breaker** or by removing the fuse at the fuse box. Turning the power off using the light switch is not sufficient to prevent electrical shock.

NOTE:

The important safeguards and instructions appearing in this manual are not meant to cover all possible conditions and situations that may occur. It must be understood that common sense, caution and care, are factors that cannot be built into any product. The person(s) caring for and operating the fixture must supply these factors.

(3) UNPACKING THE FIXTURE

On checking the contents of the box you will find;

1. Fixture assembly
2. 3 x Bulb Retaining Clips
3. Mounting Hardware Pack

(4) PREPARE THE FIXTURE

1. If you are replacing an existing fixture, disconnect and remove the old fixture. Expose the supply wiring from the outlet box.
2. Lay the un-assembled fixture on a soft surface and carefully remove all the packing material. wire. Attach the ground (copper wire) from the fixture to. The outlet box ground terminal or (the box ground wire)
3. Screw the supplied 1/4" threaded rod approximately 4-5 turns into the hole located in the center of the crossbar and secure at either end with washers and hex nuts provided. Attach the cross bar to the junction box with the supplied screws.
4. Connect the supply wires from the junction box to the fixture wires. The Black supply wire attaches to the Black fixture wire and the White supply wire attaches to the White fixture
5. Attach the fixture over the 1/4" threaded rod and secure with the supplied finial
6. Insert the twist and lock GU-10 Halogen bulb into the sockets and secure with the supplied bulb retaining clips.
7. .

Restore electricity and enjoy your new lighting fixture.

CAUTION:

- **Ensure that the Fitting is Cool and Switched off, Before Changing Bulbs.**
- **Do Not use Bulbs Exceeding Maximum Wattage, As Per Caution Label.**
- **Do Not Touch the fixture whilst it is in operation.**

