

Attention:

PLEASE NOTE : ALL INSTALLATIONS MUST BE PERFORMED BY A QUALIFIED ELECTRICIAN.

All electrical connections must be in accordance with local codes, ordinances, or the National Electrical Code.

1. To ensure the success of the installation, be sure to read these instructions and review the diagrams thoroughly before beginning.
2. These fixtures are intended for mounting to a standard 4" x 2¼" deep metal octagon outlet box. The box must be directly supported by the building structure.
3. Before commencing with the installation, disconnect the power by turning off the circuit breaker or by removing the fuse at the fuse box. Turning the power off using the light switch is not sufficient to prevent electrical shock.

NOTE:

The important safeguards and instructions appearing in this manual are not meant to cover all possible conditions and situations that may occur. It must be understood that common sense, caution and care, are factors that cannot be built into any product. The person(s) caring for and operating the fixture must supply these factors.

CAUTION:

Ensure that the Fitting is Cool and Switched off, Before Changing Bulb.

Do Not use Bulbs Exceeding Maximum Wattage, As Per Caution Label.

4. Carefully unpack your new fixture and lay out all the parts on clear area. Take care not to loose any small parts necessary for installation. Be sure the electricity to the wires you are working on is shut off - either the fuse removed or the circuit breaker set at "Off".
5. Spread the Arms for each tier evenly (See the Arm & Decorative Panel Positions after Assembly).
6. Secure the 3pcs of Decorative Panel to the Upper Housing with Screws.
7. Place Glass Shade over Socket, tighten Glass Shade by threading the Socket Ring onto Socket.
8. Insert Bulb to Socket.
9. Your installation is now complete, you may return power to the Junction Box and test the fixture

