

ASSEMBLY AND INSTALLATION INSTRUCTION

Attention:

1. To ensure the success of the installation, be sure to read these instructions and review the diagrams thoroughly before beginning.
2. All electrical connections must be in accordance with local codes, ordinances, or the National Electrical Code. ALL installations MUST be performed by a qualified electrician.
3. These fixtures are intended for mounting to a standard 4" x 2 1/4" deep metal octagon outlet box. The box must be directly supported by the building structure.
4. Before commencing with the installation, disconnect the power by turning off the circuit breaker or by removing the fuse at the fuse box. Turning the power off using the light switch is not sufficient to prevent electrical shock.

NOTE: The important safeguards and instructions appearing in this manual are not meant to cover all possible conditions and situations that may occur. It must be understood that common sense, caution and care, are factors that cannot be built into any product. The person(s) caring for and operating the fixture must supply these factors.

CAUTION:

Ensure that the Fitting is Cool and Switched off, Before Changing Bulb.

Do Not use Bulbs Exceeding Maximum Wattage, As Per Caution Label.

5. Carefully unpack your new fixture and lay out all the parts on clear area. Take care not to loose any small parts necessary for installation. Be sure the electricity to the wires you are working on is shut off - either the fuse removed or the circuit breaker set at "Off".
6. The Mounting Strap contains several pairs of threaded holes. Find the pair of holes that match the hole spacing in your Canopy, and thread the two Mounting Screws part way into the Mounting Strap and tighten with two Hex Nut.
7. Secure the Mounting Strap to the Outlet Box by threading the two Outlet Box Mounting Screws through the key holes on the Mounting Strap.
8. Attach the power supply wires to the fixture lead wires by connecting **BLACK to BLACK** (or **SMOOTH**) and **WHITE to WHITE** (or **RIBBED**).
9. Attach **GROUND** wire (**GREEN** or **COPPER**) from Outlet Box and the fixture Ground wire to the Green Ground Screw on the Mounting Strap or connect both wires together using the correct size of wire connectors. NOTE: Twist the wire connector onto the wires and twist the wires together in the same direction.
10. Tuck these wire connections neatly into Outlet Box, raise Canopy against ceiling and tighten with two Threaded Studs.
11. Secure Threaded Nipple to Connector and tighten with Hex Nut.
12. Install medium base bulb for your fixture. DO NOT EXCEED 60-WATTS.
13. Slide Glass Shade and Plastic Washer, Steel Washer through Threaded Pipe and tighten with Hex

