

INSTALLATION AND ASSEMBLY INSTRUCTIONS

Attention:

1. To ensure the success of the installation, be sure to read these instructions and review the diagrams thoroughly before beginning.
2. All electrical connections must be in accordance with local codes, ordinances, or the National Electrical Code. If you are unfamiliar with methods of installing electrical wiring, secure the services of a qualified licensed electrician.
3. These fixtures are intended for mounting to a standard 4" x 2¼" deep metal octagon outlet box. The box must be directly supported by the building structure.
4. Before commencing with the installation, disconnect the power by turning off the circuit breaker or by removing the fuse at the fuse box. Turning the power off using the light switch is not sufficient to prevent electrical shock.

NOTE:

The important safeguards and instructions appearing in this manual are not meant to cover all possible conditions and situations that may occur. It must be understood that common sense, caution and care, are factors that cannot be built into any product. The person(s) caring for and operating the fixture must supply these factors.

CAUTION:

Ensure that the Fitting is Cool and Switched off, Before Changing Bulb.

Do Not use Bulbs Exceeding Maximum Wattage, as Per Caution Label.

5. Carefully unpack your new fixture and lay out all the parts on clear area. Take care not to loose any small parts necessary for installation. Be sure the electricity to the wires you are working on is shut off - either the fuse removed or the circuit breaker set at "Off" .
6. Carefully unpack your new fixture and lay out all the parts on clear area. Take care not to loose any small parts necessary for installation.
7. The Universal Crossbar contains several pairs of threaded holes. Find the pair of holes that match the hole spacing in your fixture Wall Plate, and thread two Fixture Mounting Screws part way into the Universal Crossbar.
8. Secure the Universal Crossbar to the Outlet Box by threading two Outlet Box Screws through the Key Holes.
9. Connect the fixture wires to the Outlet Box wires as follows. Connect the White Fixture wire to the White Supply Wire, Connect the Black Fixture Wire to the Black Supply Wire. Make sure all Wire Connectors are secure and do not easily pull off with the slight tug. If there is no Green Ground Wire from the Outlet Box, connect the Fixture Ground Wire to the Universal Crossbar with the Green Grounding Screw provided.
10. Place the fixture Wall Plate over the two Fixture Mounting Screws so they protrude through the holes in the Wall Plate. Thread the Finials onto the Fixture Mounting Screws and continue turning until the Fixture is snug against the wall.
11. Slide the Glass Shade and Spacer through Socket and tighten the Glass Shade by using the Socket Wrench to thread Socket Ring onto Socket.

