

Product Specifications for E53712-AL				
Job Name:	Job Type:			
Quantity:	Comments			



ADA

E53712-AL StarStrand 24" Channel Star 24 5000 K

Lamping		Measurements
Number of Bulb(s)	36	Width
Light Type	LED	Height
Bulb Type	LED	Length
Max Bulb Wattage	0.21	Extension
Max Fixture Wattage	7.4	Back Plate Width
Rated Life	±30,000 Hours	Back Plate Height
Rated Lumens	±488	НСО
Color Temp	±5,000 K	Min Overall Height
Bulb(s) Included	Integrated	Max Overall Height
Light Úp/Down	N/A	Hanging Weight
Beam Spread	N/A	Height Adjustable
CRI	N/A	Slope
Photo Cell Included	N/A	Chain Length
Ballast/Driver/Transformer	r No	Wire Length
Dimmable	Magnetic Low-Voltage	Canopy Width
		Canopy Height

No

weasurements	
Width	0.90"
Height	0.58"
Length	24.00"
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
HCO	N/A
Min Overall Height	N/A
Max Overall Height	N/A
Hanging Weight	0.30 lb(s)
Height Adjustable	N/A
Slope	N/A
Chain Length	N/A
Wire Length	N/A
Canopy Width	N/A
Canopy Height	N/A
Canopy Length	N/A

Shipping	
Carton Weight	0.43 lb(s)
Carton Width	2.10"
Carton Height	1.10"
Carton Length	24.50"
Carton Cubic Feet	N/A
Master Pack	50
Master Pack Weight	23.10 lb(s)
Master Pack Width	11.10"
Master Pack Height	11.90"
Master Pack Length	25.20"
Master Cubic Feet	N/A
UPS Shippable	Yes

Certification		Other		Equivalents	
Safety Rating	Damp	UPC Code	845094036838	Incandescent Watts	44.36
Energy Star	No	Material	N/A	Fluorescent Watts	9.76
CA Title 24	Yes				
CA Title 20	No				

ET2 Contemporary Lighting and all designs, logos and images © 2014 ET2 Contemporary Lighting. All Rights Reserved. ET2 Contemporary Lighting reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes. Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.