



Product Specifications for E59913-SN

Job Name:	Job Type:
Quantity:	Comments



E59913-SN

CounterMax MX-L120DC 13" 3000K 4-LED Under Cabinet

Uses MXInterLink4 accessories. Click [here](#) for a complete list of compatible accessories.

Finish
Satin Nickel

Glass/Shade
Clear

Product Category
Under Cabinet

Lamping

Number of Bulb(s)	4
Light Type	LED
Bulb Type	Cree® LED
Max Bulb Wattage	2.44
Max Fixture Wattage	9.76
Rated Life	±50,000 Hours
Rated Lumens	±471
Color Temp	±3,000 K
Bulb(s) Included	Integrated
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	Yes
Dimmable	Lutron® or Leviton® LED Dimmer

Measurements

Width	4.00"
Height	1.00"
Length	13.00"
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
HCO	N/A
Min Overall Height	N/A
Max Overall Height	N/A
Hanging Weight	2.31 lb(s)
Height Adjustable	N/A
Slope	N/A
Chain Length	N/A
Wire Length	N/A
Canopy Width	N/A
Canopy Height	N/A
Canopy Length	N/A

Shipping

Carton Weight	2.49 lb(s)
Carton Width	6.00"
Carton Height	2.75"
Carton Length	17.25"
Carton Cubic Feet	N/A
Master Pack	6
Master Pack Weight	14.96 lb(s)
Master Pack Width	16.93"
Master Pack Height	6.69"
Master Pack Length	17.32"
Master Cubic Feet	N/A
UPS Shippable	Yes

Certification

Safety Rating	Dry
Energy Star	No
CA Title 24	No
CA Title 20	No
ADA	No

Other

UPC Code	845094049760
Material	N/A

Equivalents

Incandescent Watts	42.82
Fluorescent Watts	9.42

ET2 Contemporary Lighting and all designs, logos and images © 2014 ET2 Contemporary Lighting. All Rights Reserved. ET2 Contemporary Lighting reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes. Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.