

Product Specifications for E59914-SN						
	Job Name:	Job Type:				
		**				
	Quantity:	Comments				



E59914-SN

CounterMax MX-L120DC 21" 3000K 6-LED Under Cabinet

Uses MXInterLink4 accessories. Click here for a complete list of compatible accessories.

Finish Satin Nickel		Glass/Shade Clear		Product Category Under Cabinet	
Lamping		Measurements		Shipping	
Number of Bulb(s)	6	Width	4.00"	Carton Weight	3.59 lb(s)
Light Type	LED	Height	1.00"	Carton Width	6.00"
Bulb Type	Cree® LED	Length	21.00"	Carton Height	2.75"
Max Bulb Wattage	2.49	Extension	N/A	Carton Length	24.50"
Max Fixture Wattage	14.93	Back Plate Width	N/A	Carton Cubic Feet	N/A
Rated Life		Back Plate Height	N/A	Master Pack	6
Rated Lumens	±715	НСО	N/A	Master Pack Weight	21.56 lb(s)
Color Temp	±3,000 K	Min Overall Height	N/A	Master Pack Width	16.93"
Bulb(s) Included	Integrated	Max Overall Height	N/A	Master Pack Height	6.69"
Light Up/Down	N/A	Hanging Weight	3.30 lb(s)	Master Pack Length	24.80"
Beam Spread	N/A	Height Adjustable	N/A	Master Cubic Feet	N/A
CRI	N/A	Slope	N/A	UPS Shippable	Yes
Photo Cell Included	N/A	Chain Length	N/A		
Ballast/Driver/Transformer	Yes Lutron® or	Wire Length	N/A		
Dimmable	Leviton® LED Dimmer	Canopy Width	N/A		
		Canopy Height	N/A		
		Canopy Length	N/A		
Certification		Other		Equivalents	
Safety Rating	Dry	UPC Code	845094049791	Incandescent Watts	65
Energy Star	No	Material	N/A	Fluorescent Watts	14.3
CA Title 24	No				
CA Title 20	No				
ADA	No				

ET2 Contemporary Lighting and all designs, logos and images © 2014 ET2 Contemporary Lighting. All Rights Reserved. ET2 Contemporary Lighting reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes. Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.