

ε (		8	
ı	ı		

Product Specifications for E93153-39	Product S	pecifications	for	E931	53-	39
--------------------------------------	-----------	---------------	-----	------	-----	----

Job Name:	Job Type:
Quantity:	Comments

E93153-39

**Carte 3-Light Pendant** 

FinishGlass/ShadeProduct CategorySatin NickelGrey RippleLinear Pendant

Yes

No

Other

**UPC Code** 

Material

Lamping	
Lamping Number of Bulb(s)	3
Light Type	Fluorescent
Bulb Type	G24q-1 Quad T4 CFL
Max Bulb Wattage	13
Max Fixture Wattage	39
Rated Life	±10,000 Hours
Rated Lumens	±2,340
Color Temp	±2,700 K
Bulb(s) Included	No
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A

Measurements	
Width	5.00"
Height	13.00"
Length	24.50"
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
НСО	N/A
Min Overall Height	N/A
Max Overall Height	60.00"
Hanging Weight	11.10 lb(s)
Height Adjustable	Yes
Slope	120°
Chain Length	N/A
Wire Length	120.00"
Canopy Width	N/A
Canopy Height	N/A
Canopy Length	N/A

Shipping	
Carton Weight	14.43 lb(s)
Carton Width	8.00"
Carton Height	14.50"
Carton Length	30.00"
Carton Cubic Feet	N/A
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes

## Certification

Dimmable

Ballast/Driver/Transformer

Safety Rating	Dry
Energy Star	No
CA Title 24	No
CA Title 20	No
ADA	No

## **Equivalents**

845094025221

N/A

Incandescent Watts	213
Fluorescent Watts	N/A

ET2 Contemporary Lighting and all designs, logos and images © 2014 ET2 Contemporary Lighting. All Rights Reserved. ET2 Contemporary Lighting reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes. Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.