


















PARTS & ASSEMBLY SHEET

Fixture Name: Valencia 2049-M1L FB

This fixture assembled PO: _____ Date: _____

Notice: Please review the parts listing and check for all parts before assembling the fixture. If any parts are missing or damaged, please note on this sheet and contact the place of purchase to arrange for replacement parts.


PARTS LIST			Company Name: _____ Co. Account #: _____
to be filled out by retailer			
Canopy  1 ea 5.2"DIA*1.1"	Hex Nut (A)  1 ea 3/8"*H3mm	Nipple (C)  1 ea 3/8"*H45mm	
Chain  1 ea 6FT*Φ4.2mm	Threaded Ring (H)  1 ea Φ23-16T*H5mm	Spring Washer (B)  1 ea Φ15*H3mm	
Chain Connector  2 ea Φ4*H55mm	Screw Collar Loop (F)  1 ea 3/8"*H42.4mm	Junction Box Screw (E)  2 ea #8-32N*H32mm	
Mounting Strap (D)  1 ea 3/4"*1"	Green Ground Screw  1 ea #8-32N*H10mm	Wire Connectors  3 ea P3	
Top Loop (J)  1 ea W42*H53mm	Crystal (K)  2 ea W21*63Lmm	Glass 4ea W110*H160mm 	
Part Needed _____	Quantity _____		
Part Needed _____	Quantity _____		
Reason why _____	(missing, scratched, broken glass, bent, bad finish)		
Comments _____			

FIXTURE ASSEMBLY INSTRUCTIONS

Read and review installation instruction sheet before assembling the fixture.

1. Slide the Glass panels (L) into the box, then secure with clips.
2. Hang the Crystals (K).
3. Tighten Top loop (J).

NOTE: INSTALL THE GLASS ASSEMBLY BEFORE THE FIXTURE IS HUNG.



For Customer Service, contact the place of purchase to arrange for replacement parts.

PARTS & ASSEMBLY SHEET

Fixture Name: Valencia 2049-M1L FB

ASSEMBLING THE FIXTURE (Fig. 2)

4. By measuring determine correct number of links needed for proper hanging height. Use a pair of pliers to open one link of the Chain then remove the excess Chain and discard it.

5. Use one chain connector to attach one end of the chain to the Top loop (J) and close the chain connector.

6. Feed the fixture wires through the Chain (every three links) and pull the wires until taut.

7. Slip Canopy loop collar over the chain, then do the same with the canopy.

8. When ready to complete the installation Use the other chain connector and attach the other end of the chain to the canopy loop and close the chain connector.


9. Make sure the weight of the fixture is supported by the chain-not the electrical wire.

*You may now hang the fixture

10. Install the light bulb in accordance with the fixture's specifications.

DO NOT EXCEED MAXIMUM WATTAGE RATING!

Fig 2





INSTALLATION INSTRUCTIONS

Fixture Name: Valencia 2049-4P/6/9/M1L FB


For Pendant Light Fixture

WARNING ! SHUT OFF POWER AT FUSE OR CIRCUIT BREAKER.

HANGING THE FIXTURE (Fig. 1)

1. Carefully remove the new fixture from the carton and the yellow bag that holds all parts. Check that all parts are included as shown in the illustration and parts list.
2. Shut off the power at the circuit breaker and remove old fixture from ceiling, including the old mounting strap.
3. Thread Nipple(C) into Canopy Loop (F) until snug.
4. Thread other end of the Nipple (C) with Canopy Loop attached into Mounting Strap (D).
5. Place Lock Washer (B) over end of Nipple (C) protruding through Mounting Strap (D) and thread Hex Nuts (A) onto Nipple until tight.
6. Take this mounting strap assembly and mount to ceiling junction box with Mounting screws (E). Tighten screw securely with screw driver.
7. Unscrew the Canopy loop collar(H) from the Canopy loop. Take the canopy and pass over the Canopy loop. approximately one half of the canopy loop exterior threads should be exposed. Adjust until desired height is reached. *the Canopy loop collar should fit snugly on the Canopy loop after the canopy is installed. Remove Canopy and Canopy lock collar.
8. Assemble the fixture and have an assistant or secure support hold the weight of the fixture while you complete the wiring connections.
9. Thread the fixture wires and ground wire of the assembled fixture through the canopy loop and nipple and into the outlet box.


Fig. 1



CONNECTING THE WIRES (Fig 2)

10. Attach the power supply wires to the fixture lead wires by connecting BLACK to BLACK (or SMOOTH) and WHITE to WHITE (or RIBBED).
 11. Attach the GROUND wire(GREEN or COPPER) from the Junction Box and the fixture Ground wire to the green Ground Screw on the Mounting Bracket (D) or connect both wires together using the correct size of wire connectors.
- NOTE:** Twist the wires together in the same direction you twist the wire connector onto the wires.
12. Tuck these wire connections neatly into the Junction Box.

Fig. 2



FINISHING THE INSTALLATION

13. Raise the Canopy (G) to the ceiling. Secure in place by tightening the Canopy Loop Collar (H) onto the Canopy Loop (F).

**YOUR INSTALLATION IS NOW COMPLETE.
RETURN POWER TO THE JUNCTION BOX AND
TEST THE FIXTURE.**