




Family: Lauren | Item No. 4068



Drawing 1 - Arm Spacing



Drawing 2 - Fixture Assembly



▼ start here

1

1. Find a clear area in which you can work.
2. Unpack fixture and glass from carton.
3. Carefully review instructions prior to assembly.

*** The construction of this fixture will be accomplished by first assembling the main body of the fixture, making all necessary electrical connections, hanging the fixture from the ceiling, and then installing the glass.

SAFETY WARNING: READ WIRING AND GROUNDING INSTRUCTIONS (I.S. 18) AND ANY ADDITIONAL DIRECTIONS. TURN POWER SUPPLY OFF DURING INSTALLATION. IF NEW WIRING IS REQUIRED, CONSULT A QUALIFIED ELECTRICIAN OR LOCAL AUTHORITIES FOR CODE REQUIREMENTS.

2

1. Rotate arms (A) until they are approximately 51.5 degrees apart - see Drawing 1.
2. Slip loop (1) along wire and thread onto tube (B) at top of center column (2).
3. Slip candle sleeve (3) over socket (S).
3. Please refer to hanging instruction sheet (I.S. 19) provided to hang this fixture. Then refer back to this sheet to install glass.

3

1. Fixture can be lamped accordingly prior to installing the glass.
2. To install glass (4) slip glass through ring and make sure base of glass seats properly in glass holder (GH) - see Drawing 2.

01.01.12