

**WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER .**

## ASSEMBLY THE FIXTURE (Fig.2)

1. Attach the loop (B) to the fixture center body (C) by turning it clockwise until tight.
2. Thread the pipe nipple (E) into bottom center of the fixture body (C). Raise the lower frame (F) to bottom center of the fixture body (C), aligning the hole with pipe nipple and screw it with finial (G).
3. Place the socket sleeve (D) onto the socket of the fixture body (C).
4. Install the light bulbs in accordance with the fixture specifications. **NOTE: DO NOT EXCEED THE SPECIFIED WATTAGE.**

## HANG THE FIXTURE (Fig.1)

1. Shut off the power at the circuit breaker and remove old fixture from ceiling, including the old crossbar.
2. Carefully unpack new fixture and lay all the parts on a clear surface.
3. Thread end of nipple (C) into crossbar (D).
4. Place lock washer (B) over end of nipple protruding from crossbar and thread hex nut (A) onto nipple until tight.
5. Take this crossbar assembly and mount to ceiling junction box with junction box screws (E). Tighten screws securely with screwdriver. The side of the crossbar marked "GND" must face out.

## CONNECTING THE WIRES (Fig.3)

1. Take the black wire from the ceiling junction box and the smooth wire leg from the fixture and twist bare ends together. Twist wire connector onto end of wire until snug.
2. Repeat same process with white junction box wire and ribbed wire leg of fixture wire. **NOTE:** Twist wires together in the same direction you twist the wire connector onto wires.
3. If your junction box has a grounding wire (green or bare copper), attach this wire and the bare copper wire from the fixture together as step 1. If junction box has no ground wire, attach the bare copper fixture wire to the green ground screw on the crossbar.
4. Tuck these wire connections neatly into the ceiling outlet box and then raise the fixture canopy all the way to the ceiling.
5. Place the fixture canopy over the nipple (C), and then tighten it with ball nut (A).

Your installation is now complete Return power to the junction box and test the fixture.

Fig.1




Fig.2




Fig.3

