## ASSEMBLING & INSTALLATION INSTRUCTIONS PRODUCT# 8585 For Wall Mount Fixture

## WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER.

MOUNTING THE FIXTURE

## **Installation** (see fig.1)

- 1. Disconnect power at main electrical panel before installation.
- 2. Thread the two mounting screws about 1/4" into the pre-drilled holes in the mounting plate, spaced about the same distance apart as the holes in the fixture back plate. Attach the mounting plate to the junction box using two junction box screws. The side of the mounting plate marked "GND" must face out.
- 3. Guide fixture wires through hole in center of mounting plate. By measuring, determine correct distance of junction box to the plastic anchors. Mount the plastic anchors into the wall attach the angle iron(B) to the wall and lock it with the screw(C).
- 4. Follow wiring instructions carefully (see fig.2)
- 5. Place the fixture body (D) over the mounting plate, aligning the hole with mounting screw and aligning the top nipple with hole of angle iron(B), then screw the ball nuts (G) onto the mounting screws.
- 6. Attach the glass shade (F) onto the lamp holder, then lock it securely with check ring (E).
- 7. Install the light bulbs in accordance with the fixture's specifications. DO NOT EXCEED THE MAXIMUM WATTAGE RATING!

## Wiring (see fig.2)

- 1. Connect the electrical wires as follows. Connect the Black wire from the fixture to the black house (hot) Wire. Connect the white wire from the fixture to the white (neutral) house wire. Make sure all wire nuts are secured. You may wrap the connections with electrical tape. If your outlet box has a ground wire (green or bare copper) connect fixture's ground wire to it. Otherwise attach the bare copper fixture wire to the green ground screw on the mounting plate.
- 2. Tuck the wire connections neatly into the wall junction box.





