

Lighting Your Life Since 1970

Product Specifications - 85530WTSN		
Job Name:	Job Type:	
Quantity:	Comments	



85530WTSN

Linear EE 1-Light Wall Sconce

Finish

Satin Nickel

Lam	ping	7	
Num	hor	Ωf	

umber of Bulbs 1 **Light Type** Fluorescent G24q-3 Quad T4 **Bulb Type** CFL Max Bulb Wattage 26 Max Fixture Wattage 26 ±10,000 Hours Rated Life **Rated Lumens** ±1,800 Color Temp ±3,000 K Bulb(s) Included Light Up/Down N/A **Beam Spread** N/A CRI N/A **Photo Cell Included** N/A Ballast/Driver/Transformer Yes **Dimmable**

Glass/Shade White

Measurements

Width 9.5" Height 10.5" Length N/A Extension 4" **Back Plate Width** 7.1" **Back Plate Height** 10.6" HCO N/A Min Overall Height N/A **Max Overall Height** N/A Hanging Weight 3.9 lbs Height Adjustable N/A Slope N/A **Chain Length** N/A Wire Length N/A **Canopy Width Canopy Height Canopy Length** N/A

Product Category Wall Sconce

Shippina

Jilippilig	
Carton Weight	3.9 lbs
Carton Width	6"
Carton Height	13"
Carton Length	12"
Carton Cubic Feet	0.49
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes

Certification

Safety Rating Dry **Energy Star** No CA Title 24 Yes CA Title 20 No **ADA** Yes Dark Sky N/A

Other	
UPC Code	783209093850
Shades Included	N/A
Crystals Included	N/A
Diffuser Included	N/A
Conversion Kit	N/A
Material	Metal

Equivalents

Incandescent Watts	168
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2013 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.