



Lighting Your Life Since 1970

## Product Specifications - 87453WT

Job Name:	Job Type:
Quantity:	Comments:



**87453WT**

**CounterMax MX-X12-LX 4-Light Xenon Under Cabinet**

### Finish

White

### Glass/Shade

### Product Category

Under Cabinet

### Lamping

Number of Bulbs	4
Light Type	Xenon
Bulb Type	12V Wedge T5 Xelogen
Max Bulb Wattage	18
Max Fixture Wattage	72
Rated Life	±10,000 Hours
Rated Lumens	±1,056
Color Temp	±2,900 K
Bulb(s)	Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	Yes
Dimmable	Low-Voltage

### Measurements

Width	5.0"
Height	1.0"
Length	30.0"
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
HCO	N/A
Min Overall Height	N/A
Max Overall Height	N/A
Hanging Weight	3.2 lbs
Height Adjustable	N/A
Slope	N/A
Chain Length	N/A
Wire Length	N/A
Canopy Width	N/A
Canopy Height	N/A
Canopy Length	N/A

### Shipping

Carton Weight	3.2 lbs
Carton Width	7"
Carton Height	3"
Carton Length	33"
Carton Cubic Feet	0.40
Master Pack	5
Master Pack Weight	23.0 lbs
Master Pack Width	8.1"
Master Pack Height	17.5"
Master Pack Length	33.5"
Master Cubic Feet	2.76
UPS Shippable	Yes

### Certification

Safety Rating	Dry
Energy Star	No
CA Title 24	No
CA Title 20	No
ADA	No
Dark Sky	N/A

### Other

UPC Code	783209077010
Shades Included	N/A
Crystals Included	N/A
Diffuser Included	N/A
Conversion Kit	N/A
Material	Aluminum

### Equivalents

Incandescent Watts	N/A
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2013 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.