

Lighting Your Life Since 1970

Product Specifica	tions - 90350CLCS
Job Name:	Job Type:
Quantity:	Comments



90350CLCS

Bound Glass 3-Light Entry Foyer Pendant

Finish Country Stone

Lamping Number of Bulbs

Dimmable

Nulliber of Duibs	3
Light Type	Incandescent
Bulb Type	CA
Max Bulb Wattage	40
Max Fixture Wattage	120
Rated Life	±1,500 Hours
Rated Lumens	±1,152
Color Temp	±2,700 K
Bulb(s)	Not Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	No

Glass/Shac	le
Clear	

Measurements	
Width	

Med3di ellielli	
Width	13.0"
Height	20.5"
Length	N/A
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
HCO	N/A
Min Overall Height	N/A
Max Overall Height	N/A
Hanging Weight	10.1 lbs
Height Adjustable	N/A
Slope	N/A
Chain Length	36"
Wire Length	180"
Canopy Width	N/A
Canopy Height	N/A
Canopy Length	N/A

Product Category

Entry Foyer Pendant

Shipping	
Carton Weight	10.1 lbs
Carton Width	15"
Carton Height	21"
Carton Length	17"
Carton Cubic Feet	2.98
Master Pack	1
Master Pack Weigh	t N/A
Master Pack Width	N/A
Master Pack Height	t N/A
Master Pack Lengtl	h N/A
Master Cubic Feet	N/A
UPS Shippable	Yes

Certification

Certification		Other	
Safety Rating	Dry	UPC Code	783209000568
Energy Star	No	Shades Included	N/A
CA Title 24	No	Crystals Included	N/A
CA Title 20	No	Diffuser Included	N/A
ADA	No	Conversion Kit	N/A
Dark Sky	N/A	Material	Copper

Other

Standard Dimmer

Equivalents

Incandescent Watts N/A
Fluorescent Watts N/A

Maxim Lighting International and all designs, logos and images © 2013 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.