



**IMPORTANT:
TURN OFF POWER AT MAIN FUSE OR
CIRCUIT BREAKER BOX BEFORE
STARTING INSTALLATION**

Carefully unpack and identify all parts before assembly. Bulbs are not included.

1. Take fixture wires and ground wire located above coupler and thread through center pipe. Then sit center pipe inside of coupler.
2. Install arms:
 - A. Hook bottom section of an arm onto curl.
 - B. Then install upper section of arm onto fixture place by fastening with small flat washer, small lock washer, and small hex nut.
 - C. Repeat other arms.
3. Screw threaded pipe into bottom of socket assembly. Note correct position of threaded pipe at illustration.
4. Follow enclosed **“Multiple Standard Installation Instructions”** for electrical and fixture installation onto ceiling outlet box.
5. Install light bulb (not included). See relamping label located at socket area for type and maximum allowed wattage.
6. Slip glass shade up till it checks into bottom of pan. Then lock into position by fastening with flat washer and hex nut. Do not over tighten.
7. Slip lower font through same threaded pipe and lock into place by fastening finial.
8. Make certain pin, which is located at bottom of each loops, locks into hole located at bottom side of each curls. If pins can not reach hole in curls, then adjust finial and hex nut in order to raise glass shade and crown location.