




ASSEMBLY INSTRUCTIONS

ITEM NO.:1-3411-8-56



B → C → A → D → E → F → G → H → I → J → K → L →
M → N → O → P → Q → R → S → T

1. Carefully unpack and identify all parts referring to the illustration for parts identification.
2. Turn power to the installation point **OFF**.
3. Thread fixture loop (B) into the nipple inside the big cover of fixture body (A), then finial (C) into the nipple at bottom of big cover of fixture body (A) as shown in the diagram.
4. Attach the end of chain of fixture body (A) to the hook of big cover as shown in the diagram.
5. Thread stem (D) into the coupling at center of fixture body (A), then glass (E), cap (F), cover (G), big cover (H), cap (I) and pipe (J) through the stem (D), and secure finial (K)..
6. Thread stem (L) into the coupling at center of fixture body (A).
7. Install proper bulbs (not provided) to sockets referring to the markings and/or labels on the fixture for maximum wattage.
8. Raise glass (M) and steel washer (N) over the stem (L), and secure with hex nut (O).
9. Slip steel bowl (P) and big steel washer (Q) over the stem (L), secure with hex nut (O).
10. Place font (R) and cap (S) over the stem (L), and secure with finial (K).
11. Place glass plate (T) over each socket.
12. Restore power to the installation point **ON**. Retain this sheet for future reference.