



B → A → C → D → E → F → G → H → I → J → K → L →  
M → N → O → P → Q → R → S → T → U → V → W → X → Y → Z

1. Carefully unpack and identify all parts referring to the illustration for parts identification.
2. Turn power to the installation point **OFF**.
3. Thread stem (B) into the coupling at center of fixture body (A).
4. Set big cap (C), small cap (D), pipe (E), small trim (F), box (G), cover (H) and big cover (I) over the stem (B) and secure with knurled nut (J) and fixture loop (K).
5. Align the holes of arm (L) with small nipple at arm of fixture body (A) and hole of box (G), and secure with ball stud (M) and ball nut (N).
6. Screw stem (O) into the bottom of fixture body (A).
7. Install proper bulbs (not provided) to sockets referring to the markings and/or labels on the fixture for maximum wattage.
8. Raise glass (P), rubber washer (Q) and steel washer (R) up over the stem (O) and secure with hex nut (S).
9. Place font (T) over the stem (O) and secure with finial (U).
10. Align the holes of the glass (V), rubber washer (W) with highlighted small nipple of fixture body (A), and secure with small ball nut (X).
11. Attach crystal (Y), (Z) to the holes of arm of fixture body (A) and arm (L).
12. Restore power to the installation point **ON**. Retain this sheet for future reference.