

*****READ & SAVE THESE INSTRUCTIONS *****
ACCESS LIGHTING
MODEL 20355
INSTALLATION & OPERATION INSTRUCTIONS

(1) TOOLS AND MATERIALS REQUIRED

- ❖ BLADE SCREW DRIVER
- ❖ WIRE CUTTERS
- ❖ WIRING SUPPLIES AS REQUIRED BY ELECTRICAL CODE
- ❖ 1 x 60W or 2 x 60W E-26/medium base bulb
(Model dependent)

Attention:

Before assembling your lighting fixture, please read the following instructions. If you feel you do not have sufficient electrical experience, refer to a do-it-yourself wiring handbook or have your fixture installed by a qualified licensed electrician.

(2) GENERAL

1. To ensure the success of the installation, be sure to read these instructions and review the diagrams thoroughly before beginning.
2. All electrical connections must be in accordance with local codes, ordinances, or the National Electrical Code. If you are unfamiliar with methods of installing electrical wiring, secure the services of a qualified licensed electrician.
3. These fixtures are intended for mounting to a standard 4" x 2 1/4" deep metal octagon outlet box. The box must be directly supported by the building structure and U.L. Recognized.
4. Before commencing with the installation, **disconnect the power by turning off the circuit breaker** or by removing the fuse at the fuse box. Turning the power off using the light switch is not sufficient to prevent electrical shock.

NOTE:

The important safeguards and instructions appearing in this manual are not meant to cover all possible conditions and situations that may occur. It must be understood that common sense, caution and care, are factors that cannot be built into any product. These factors must be supplied by the person(s) caring for and operating the fixture.

(3) UNPACKING THE FIXTURE

On checking the contents of the box you will find;

- ❖ Mounting Hardware and Universal Crossbar
- ❖ Fixture Canopy with socket
- ❖ 1 x Glass Shade
- ❖ 1 x Metal ring

(4) PREPARE THE FIXTURE

Refer to attached illustration of fixture parts and assembly.

1. If you are replacing an existing fixture disconnect and remove the old fixture. Expose the supply wiring from the outlet box .
2. Secure the **Crossbar** to the junction box with the supplied **Mounting screws** (1). Ensure that the two screws attached to the **Universal Crossbar** face downwards away from the mounting surface.
3. Gently pull the **Supply wires** through the center hole in the **crossbar**.
4. Connect the **BLACK supply wire** to the **Black wire** of the fixture and the **WHITE supply wire** to the **White fixture wire**, fasten securely with supplied **wire nuts** (2).And secure **wire nuts** with **UL listed electrical tape** (not supplied).
5. Attach the **ground (GREEN) wire** from the fixture to the **outlet box ground terminal** (or to the box ground wire).
6. Secure the **Fixture Canopy** to the **crossbar** by inserting the screws attached to the **Crossbar** through the designated holes in the **Fixture canopy** and secure with supplied **Nuts** (3)
7. Insert **E-26/ medium base bulb/s** (4) (DO NOT EXCEED WATTAGE SPECIFIED ON WARNING LABEL
8. Put the **Glass shade** (5) into the **Metal ring** (6), and flush up against the **Fixture canopy** by aligning the holes on the **Metal ring** with the holes on the **Canopy**. Then insert the supplied **Screws** (7) into the holes and fasten tightly.
9. Outdoor Wall fixtures must be caulked with suitable PTV or silicone compound around the top and sides of the cover plate to reduce the chance of water entering into the splicing area. Do not caulk the bottom of the fixture; leave it clear, so that if moisture does get into the fixture, it has a means to escape.
10. Restore electricity and check the operation of your new lighting fixture.

CAUTION:

- **Ensure that the Fitting is Cool and Switched off, Before Changing the Bulb.**
- **Do Not use Bulbs Exceeding Maximum Wattage, As per Caution Label.**



MODEL 20355/6

