

ASSEMBLY AND INSTALLATION INSTRUCTIONS

AC1063

WARNING: TO AVOID RISK OF ELECTRICAL SHOCK, BE SURE TO SHUT OFF POWER WHILE INSTALLING OR SERVICING THIS FIXTURE.

Installation Steps

NOTE: Do not install on ceilings with a Radiant Ceiling Heating System.

1. The Circular Strap contains several pairs of threaded holes, Find the pair of holes that match the hole spacing in your Fixture Canopy and thread the two Stud part Way into the Circular Strap, adjust the length as you measured, and then tighten with the small Nut.

2. Attach the Circular Strap to the Outlet Box using the two Screws from the Outlet Box. The side of the Circular Strap marked “GND” must face out.

Connect the Wires. Make sure all wire connectors are secure and do not easily pull off. If there is no Green Ground Wire from the Outlet Box, connect the Fixture Ground Wire to the Circular Strap with the Green Screw provided.

3. Place the fixture Canopy over the two Studs so they protrude through the holes in the Canopy, Thread the Ball nut onto the Stud and continue turning until the Fixture is snug against the ceiling. (See) “Completing the Installation”.

4. Thread the Nipple-1 into the Coupling, attach the canopy over the ironwork and then screw with Hex Nuts.

5. Thread the poles onto the body and screw with ball nuts.

6. Thread the ironwork onto the body .

7. Thread the Nipple-2 into the Coupling, and then screw with a Hex Nut

8. Install the lighting bulbs in accordance with the fixture’s specifications.

9. Attach the Glass Shade over the Nipple-2, place the washer, hex nut, cap in order then screw with finial.

10. Attached the crystal drops as per the drawing.

11. Turn on the power at fuse or Circuit Box.

DO NOT EXCEED THE MAXIMUM WATTAGE RATING!

NOTE: All parts must be used as indicated, and the physical integrity must be maintained to insure ETL/CETL. listing of this fixture.

