## ASSEMBLY AND INSTALLATION

## **INSTRUCTIONS**

## **AC1064**

WARNING: TO AVOID RISK OF ELECTRICAL SHOCK, BE SURE TO SHUT OFF POWER WHILE INSTALLING OR SERVICING THIS FIXTURE.

## **Installation Steps**

NOTE: Do not install on ceilings with a Radiant Ceiling Heating System.

- 1. Carefully unpack your new fixture and lay out all the parts on a clear surface.
- 2. Attach the Nipple-1 to the Circular Strap, and then screw with a Washer and a Hex Nut.
- 3. Attach the Circular Strap to the Outlet Box by using 2 screws.
- 4. Weave the Fixture Wire and the Ground Wire through the Chain links. Spread one end of the chain link to clamp securely to the Loop.
- 5. Thread the Fixture Wire and ground wire through the Collar, Top loop, Canopy, Nipple-1 and Circular Strap in order.
- 6. Screw the Top Loop to the Nipple-1, and clamp the other end of the Chain link to the Top Loop.
- 7. Make Wire connections with Wire Connector:
  - ---The smooth wire (w/ marking) from fixture to Black Wire from power source.
  - ---The ribbed wire (w/o marking) from Fixture to White Wire from power source.
  - ---Attach the Ground Wire and house ground wire to the Circular Strap with a green Ground Screw. Carefully tuck wires back into the Outlet Box.
- 8. Attach the Canopy to the Circular strap by inserting the Top loop, and then screw with the Collar.
- 9. Attached the Crystal strings onto the body according to the diagram.
- 10. Install the lighting bulbs in accordance with the fixture's specifications. DO NOT EXCEED THE MAXIMUM WATTAGE RATING!
- 11. Turn on the power at fuse or Circuit Box.

**NOTE**: All parts must be used as indicated, and the physical integrity must be maintained to insure ETL/CETL listing of this fixture.

