

ASSEMBLY AND INSTALLATION

INSTRUCTIONS

AC1172

WARNING: TO AVOID RISK OF ELECTRICAL SHOCK, BE SURE TO SHUT OFF POWER WHILE INSTALLING OR SERVICING THIS FIXTURE.

Installation Steps

NOTE: Do not install on ceilings with a Radiant Ceiling Heating System.

1. Attach the Nipple-1 to the Circular Strap, and then screw with a Washer and a Hex Nut..
2. Attach the Circular Strap to the Outlet Box by using 2 screws.
4. Weave the Fixture Wire and the Ground Wire through the Chain links. Spread one end of the chain link to clamp securely to the Loop.
5. Thread the Fixture Wire and ground wire through the Collar, Top loop, Canopy, Nipple-1 and Circular Strap in order .
6. Screw the Top Loop to the Nipple-1, and clamp the other end of the Chain link to the Top Loop.
7. Make Wire connections with Wire Connector:
 - The smooth wire (w/ marking) from fixture to Black Wire from power source.
 - The ribbed wire (w/o marking) from Fixture to White Wire from power source.
 - Attach the Ground Wire and house ground wire to the Circular Strap with a green Ground Screw. Carefully tuck wires back into the Outlet Box.
8. Attach the Canopy to the Circular strap by inserting the Top loop, and then screw with the Collar.
9. Screw the Loop over the Nipple-2 until tight.
10. Place the Glass Shades over the Lamp Holder, and screw with the Socket Ring until tight.
11. Install the lighting bulbs in accordance with the fixture's specifications. **DO NOT EXCEED THE MAXIMUM WATTAGE RATING!**
12. Turn on the power at fuse or Circuit Box.

NOTE: All parts must be used as indicated, and the physical integrity must be maintained to insure ETL/CETL listing of this fixture.

