

Attention:

**PLEASE NOTE : ALL INSTALLATIONS MUST BE PERFORMED BY A QUALIFIED ELECTRICIAN.**

All electrical connections must be in accordance with local codes, ordinances, or the National Electrical Code.

1. To ensure the success of the installation, be sure to read these instructions and review the diagrams thoroughly before beginning.
2. These fixtures are intended for mounting to a standard 4" x 2¼" deep metal octagon outlet box. The box must be directly supported by the building structure.
3. Before commencing with the installation, disconnect the power by turning off the circuit breaker or by removing the fuse at the fuse box. Turning the power off using the light switch is not sufficient to prevent electrical shock.

NOTE:

The important safeguards and instructions appearing in this manual are not meant to cover all possible conditions and situations that may occur. It must be understood that common sense, caution and care, are factors that cannot be built into any product. The person(s) caring for and operating the fixture must supply these factors.

CAUTION:

Ensure that the Fitting is Cool and Switched off, Before Changing Bulb.

Do Not use Bulbs Exceeding Maximum Wattage, as Per Caution Label.

4. Carefully unpack your new fixture and lay out all the parts on clear area. Take care not to loose any small parts necessary for installation. Be sure the electricity to the wires you are working on is shut off - either the fuse removed or the circuit breaker set at "Off".
5. This fixture provide 6" Pipe x 2pcs and 12" Pipe x 2pcs to be connected into various height. Measure and determine correct number of Pipes required. Put the fixture wire from Fitter through Pipe and thread Threaded Nipple to inside of Pipe. Thread the Threaded Nipple to Universal Joint on Canopy and tighten with Screw on Canopy Joint.
6. The Mounting Strap contains several pairs of threaded holes. Find the pair of holes that match the hole spacing in your fixture Canopy, and thread the two Mounting Screws part way into the Mounting Strap and tighten with two Hex Nut.
7. Secure the Mounting Strap to the Outlet Box by threading the two Outlet Box Screws through the key holes on the Mounting Strap.
8. Attach the power supply wires to the fixture lead wires by connecting BLACK to BLACK (or SMOOTH) and WHITE to WHITE ( or RIBBED) . Attach GROUND wire (GREEN or COPPER) from Outlet Box and

the fixture Ground wire to the Green Ground Screw on the Mounting Strap or connect both wires together using the correct size of wire connectors.

NOTE: Twist the wire connector onto the wires and twist the wires together in the same direction

9. Tuck these wire connections neatly into Outlet Box, raise Canopy against ceiling and tighten with two Finials.
10. Slide Glass Shade through Socket and tighten the Glass Shade by threading Socket Ring onto Socket
11. Insert Bulb to Socket.
12. Your installation is now complete, you may return power to the Outlet Box and test the fixture.

