

# ASSEMBLY AND INSTALLATION INSTRUCTIONS

CL1366

**WARNING:** TO AVOID RISK OF ELECTRICAL SHOCK, BE SURE TO SHUT OFF POWER WHILE INSTALLING OR SERVICING THIS FIXTURE.

## Installation Steps

**NOTE:** Do not install on ceilings with a Radiant Ceiling Heating System.

1. Carefully unpack your new fixture and lay out all the parts on a clear surface. Take care not to lose any small parts necessary for installation.
2. Attach the Circular Strap to the Outlet Box by using 2 Screws.
3. Weave the Fixture Wire and the Ground Wire through the Chain links. Spread one end of the chain link to clamp securely to the Loop.
4. Thread the Fixture Wire and ground wire through the Collar, Top loop, Canopy, Nipple-1 and Circular Strap in order.
5. Thread the Nipple-2 into the Coupling, then attach the cannula, ironwork-a, and then screw with the coupling.
6. Thread the Nipple-3 into the Coupling, then attach the cap ironwork-b, and then screw with the loop.
7. Thread pole onto the body until tight.
8. Thread the Nipple-4 into the pole then attach the cannula, ironwork-c, cannula, ironwork-d and then screw with the finial.
9. Screw the Top Loop to the Nipple-1, and Clamp the other end of the Chain link to the Top Loop.
10. Make wire connections as follows securing with appropriate UL wire connectors.
  - The smooth wire (w/ marking) from fixture to Black Wire from power source.
  - The ribbed wire (w/o marking) from Fixture to White Wire from power source.
  - Attach the Ground Wire and house ground wire to the Circular Strap with a green Ground Screw.Carefully tuck wires back into the Outlet Box.
11. Attach the Canopy to the Circular strap by inserting the Top loop, and then screw with the Collar.
12. Attach the Crystal strings onto the body according to the diagram.
13. Install the lighting bulbs in accordance with the fixture's specifications.

**DO NOT EXCEED THE MAXIMUM WATTAGE RATING!**

14. Turn on the power at fuse or Circuit Box.

**NOTE:** All parts must be used as indicated, and the physical integrity must be maintained to insure ETL/CETL listing of this fixture.

