



145 West Commercial Ave.
Moonachie, NJ 07074



Dimmer Compatibility Guide

PLEASE NOTE: Compatibility list is based upon testing conducted by the manufacturer in a lab simulated environment. Actual results may vary.

Product Family Name:	4" LED All-in-One Downlight		
Item Number:	773105	773106	773107
Ordering Code:	LED8JBOXDL/4/827/WHRD/D	LED8JBOXDL/4/830/WHRD/D	LED8JBOXDL/4/830/WHRD/D

Lamps per Dimmer							
	Manufacturer	Product	Model Number	Overall Rating	Recommended Minimum	Maximum Tested*	Notes
Incandescent/Halogen (Triac/Phase Cut/Leading Edge Dimmers)	Leviton	IllumaTech	IP106	Best	1	6	Dims down to 10% with 1-6
		SureSlide	6633-P	Best	1	6	Dims down to 7% with 1-6
		Vizia	VPI06-1LZ	Bad	4+	6	dims down to 8% with 5-6
	Lutron	Toggler	TG-600	Best	1	6	Dims down to 3% with 1-6
		Diva	DV-600	Best	1	6	Dims down to 3% with 1-6
		Skylark	S-600	Best	1	6	Dims down to 3% with 1-6
		Maestro	MAW-600	Bad	4	6	Dims down to 4% with 4-6
		Titan	CD703-PW	Best	1	6	Dims down to 16% with 1-6
	Legrand	Harmony	D703-PTC	Best	1	6	Dims down to 3% with 1-6
		Harmony	H703-PTC	Best	1	6	Dims down to 7% with 1-6
CFL/LED	Leviton	IllumaTech	IPLO6	Best	1	6	Dims down to 2% with 1 & 0.5% with 2-6
		Sureslide	6674	Best	1	6	Dims down to 11% with 1-6
		Decora	6672	Best	1	6	Dims down to 11% with 1-6
	Lutron	Skylark	CTCL-153	Best	1	6	Dims down to 0.3% with 1-6
		Diva	DVCL-153PL	Best	1	6	Dims down to 0.3% with 1-6
		Maestro	MACL-153MLH	Best	1	6	Dims down to 8% with 1-6
		Skylark	SCL-153P	Best	1	6	Dims down to 0.3% with 1-6
		Toggler	TGCL-153PH	Best	1	6	Dims down to 0.3% with 1-6
		Radio RA	RA2RR-6CL-PD	Best	1	6	Dims down to 7% with 1-6
	Legrand	Harmony	DCL453-PTC	Best	1	6	Dims down to 9% with 1-6
		Harmony	HCL453PTC	Best	1	6	Dims down to 10% with 1-6
		Adorne Paddle	ADPD453LM2	Good	1	6	Dims down to 25% with 1-6
Electronic Low Voltage	Leviton	Vizia	VPE04	Best	1	6	Dims down to 15% with 1-6
		IllumaTech	IPED4	Good	1	6	Dims down to 12% with 1-6, flicker at HE with 1
		Decora	6615-P	Bad	1	6	Dims down to 40% with 1-6, flicker at HE with 1
	Lutron	Skylark Countour	CTELV-303P	Good	1	6	Dims down to 14% with 1-6, flicker at HE with 1
		Diva	DVELV-300P	Good	1	6	Dims down to 14% with 1-6, flicker at HE with 1
		Maestro	MAELV-600	Best	1	6	Dims down to 13% with 1-6
		Skylark	SELVB-300P	Good	1	6	Dims down to 14% with 1-6, flicker at HE with 1
		VIERTI	VTEL-600M-W	Best	1	6	Dims down to 14% with 1-6
	Legrand	Scene Director	SCELV	Bad	4	6	Dims down to 30% with 4-6
Magnetic Low Voltage	Leviton	Vizia	VPM-06	Bad	5	6	Dims down to 8% with 1-6
		Decora	6613-P	Best	1	6	Dims down to 8% with 1-6
	Lutron	Maestro	MALV-600	Bad	5	6	Dims down to 8% with 1-6
		Harmony	DLV703-PW	Best	1	6	Dims down to 5% with 1-6
	Legrand	Titan	CDLV703-PW	Best	1	6	Dims down to 15% with 1-6
Universal	Legrand	Adorne Softap	ADTP703TU	Good	2	6	Dims down to 20% with 2-6
		Miro Decorator	DRD4-W	Bad	3	6	Dims down to 5% with 3-6, flicker at LE with 3-6
		Harmony	H703PTUTC	Good	2	6	Dims down to 20% with 2-6
		Adorne Whisper	ADWR700MMTUM2	Good	3	6	Dims down to 1% with 3-6
		Adorne Touch	ADTH700MMTUM2	Good	3	6	Dims down to 1% with 3-6
	Cooper	Decorator	DAL06P-C2-K-L	Good	1	6	Dims down to 15% with 1-6, shimmer at LE with 1-6
		Skye	SAL06P-W-K-L	Good	1	6	Dims down to 3% with 1-6, shimmer at LE with 1-6

*Maximum Tested (Lamps per Dimmer) - Additional lamps may work with your dimmer system. For maximum capacity please consult dimmer manufacturer.

*May experience "pop-on", lights cannot be turned on immediately to their minimum level. The slider needs to be raised above the minimum light level for the lights to first turn on if they were initially off. Then, the slider can be lowered to get to a lower light level; the dimmer cannot be turned on to just the minimum level.

Overall Rating	
Not Compatible	One or more of the following observed: Major flickering at various points, significant audible noise, no dimming range, does not turn off.
Bad	One or more of the following observed: Some flickering observed at various points, audible noise may be present, dimming not smooth.
Good	One or more of the following observed: Minor flickering at some point may exist. Dead travel may exist, which means there may be periods of time when the slider (or other form of control button) is moved without affecting the light level. These periods of dead travel are minor and most of the time not visible. Minor audible noise.
Best	Most of the following observed: No flickering, minimal audible noise (typically less than 25 dBA), wide dimming range - can dim down to 20% or less of light output.
High End (H.E.) Dead Travel	Determines how much, if any, dead travel exists at the top and bottom of the dimmer's range. Dead travel is when the slider can be moved without affecting the light level.
Low End (L.E.) Dead Travel	

Contact Information:
Bulbrite Industries Inc.
145 West Commercial Avenue
Moonachie, New Jersey 07074
PHONE: 1-800-528-5555
FAX: 1-800-441-7708
Email: ProductSupport@bulbrite.com
©2017 Bulbrite Industries Inc.
All Rights Reserved.