

# FX-3538-6 INSTALLATION SHEET

## IMPORTANT SAFETY INSTRUCTIONS:

\* These instructions are provided for your safety. It is very important that they are read completely before beginning the installation of your fixture.

\* DIRECT WIRE FIXTURES: WE STRONGLY RECOMMEND INSTALLATION BY A LICENSED ELECTRICIAN.

To avoid risk of fire, do not exceed the recommended wattage.

TO ASSEMBLE: Shut off the main electrical supply at fuse box/circuit breaker.

Remove all parts from carton. Do not throw away any parts as shown.

1. Screw the pole to the fixture (1).
2. Uninstall the washer and ring from the socket, Install the glass shade (2), secure it with washer (3) and ring (4).
3. Install the bulbs as introduced (5).
4. Put the wire through thread of the canopy and the I bar, connect the ground wire "⌐" to the supply wire, Cathode wires "N" in white to the supply wire, Anode wires "L" in black to the supply wire in the junction box as illustrated with wire nuts (6).
3. Affix the I bar (7) to the junction box by screws.
4. Affix the canopy to the plate (8) by cap (9).

Turn on power and enjoy!!!

**Use 60 Watt x 6 Max type A BULB (Bulb not included)**

**WARNINGS:** Turn off power (unplug from the wall outlet) before replacing the bulb(s), making sure the bulb(s) have sufficient time to cool down.

Do not subject the lighting fixture to any shock while lit as shattering of bulbs may result .

**CARE INSTRUCTIONS:** To clean, use a soft cloth only. DO NOT use any chemical or abrasive cleaners.

★ Keep this instruction for future reference

