

FX-3584-3 INSTALLATION SHEET

* These instructions are provided for your safety. It is important that they are read completely before beginning the installation of your fixture.

TO ASSEMBLE:

Shut off the main electrical supply at fuse box/circuit breaker.

Remove all parts from carton. Do not throw away any parts as shown.

1. Put the wire through the canopy and I bar, leave the desired length and fix it with "8" Shaped plastic clip (1).
2. connect the ground wires "⏏" to the supply wire, Cathode wire "N" in white to the supply wire, Anode wire "L" in black to the supply wire in the junction box as illustrated with wire nuts (2).
3. Affix the mounting plate (3) to the junction box by screws.
4. Affix the canopy (4) to the mounting plate by knob (5).
5. Unscrew ring (8), remove plastic ring (6), take down the glass (7) and remove plastic ring(6).
6. Reinstall glass (7) to socket (10) and secure it with ring (8).
7. Install the bulb (9).

Turn on power and enjoy!!!

To avoid risk of fire, do not exceed the recommended wattage.

**Use 60 Watt x 3 Max type A
BULB (Bulb not included)**


WARNINGS:

Turn off power (unplug from the wall outlet) before replacing the bulb(s), making sure the bulb(s) have sufficient time to cool down.

Do not subject the lighting fixture to any shock while lit as shattering of bulbs may result .

CARE INSTRUCTIONS:

To clean, use a soft cloth only. DO NOT use any chemical or abrasive cleaners.



★ Keep this instruction for future reference