

STEP2W3K-WH

Mini Die-Cast LED Step Lights.




The faceplate is much smaller to accommodate tighter spaces

No housing required

Color rendering index: 80

Performance

- Integrated LED board and driver
- Input voltage: AC 120V 50/60Hz
- Housing: Single gang receptacle box (not included)
- I.C. rated for direct contact with insulation
- Type IC for direct contact with insulation
- Lifetime rated for greater than 50,000 hours
- Directional Beam - Great for Sloped Ceilings and Highlighting Artwork



Construction

- Aluminum trim ring with durable powder coat finish
- Beam angle: 45°
- Wet location rated

Installation

- Lamp bracket is secured to standard single gang receptacle box by 2 screws

Galvanized stamped steel housing




Specifications

| | | | |
|--|--------------|--------------------------------------|----------|
| Category | Indoor light | Inner Package Length (Inch) | 2.95 |
| Bulb Base Type | LED | Inner Package Width (Inch) | 2.34 |
| Bulb Base Finish | NO | Inner Package Height (Inch) | 4.92 |
| Color Temperature | 3000K | Inner Package Weight Per Unit (Lbs) | 0.52 |
| Beam Angle | 45° | Carton Package Length (Inch) | |
| Finish | White | Carton Package Width (Inch) | |
| CRI | 80 | Carton Package Height (Inch) | |
| Average Life (Hours) | 50000 | Carton Package Weight Per Unit (Lbs) | |
| Estimated Yearly Energy Cost (11 ¢ /Kwh) | 0.30 | Carton Quantity | |
| Life Based On 3Hrs/Day (Years) | 45.66 | Lamp Type | LED |
| Product Length (Inch) | Φ4 1/2" | Bulb Shape | N/A |
| Product Width (Inch) | Φ2 3/4" | Dry/Wet/Damp | Wet |
| Product Height (Inch) | 2" | Energy Star | NO |
| Product Extension (Inch) | N/A | Power Factor | 0.95 |
| Product Weight Per Unit (Lbs) | 0.49 | Current | 0.12 |
| Dimmable | NO | Lumen/Watt | 10 |
| Watts | 2.5 | Warranty (Year) | 5 |
| Watt Equivalent | / | DLC (Yes/No) | NO |
| Lumens | 25 | Input Voltage | 120 |
| Certification (UL/ETL/FCC) | ETL/CETL | Housing Material | Aluminum |
| | | Lens | Acrylic |
| | | Led Type | |

STEP2W3K-WH

Mini Die-Cast LED Step Lights.



DIMMER COMPATIBILITY

| Brand | Series | Model | Load | Dimmability |
|---------|------------------|------------|-------|-------------|
| Lutron | Ariadni | MYCL-153P | 150W | OK |
| | Diva | DV-600PR | 600W | OK |
| | Diva | DV-153P | 150W | OK |
| | Maestro | DCCL-153MH | 600W | OK |
| | Maestro Wireless | MRF2-6CL | 150W | OK |
| | Rotary | D-600P | 600W | OK |
| | Electronic(ELV) | NTELV-300P | 600W | OK |
| | Skylark | S-600P | 600W | OK |
| | Skylark Contour | CT-600P | 600W | OK |
| | Skylark Contour | CTCL-153P | 150W | OK |
| | Toggler | TG-600P | 600W | OK |
| | Toggler | TGCL-153P | 150W | OK |
| Leviton | Sureslide | 6633 | 600W | OK |
| | Sureslide Decora | 6674 | 600W | 20-100% |
| | Trimatron | 6602 | 600W | OK |
| | ILLVATECH | IPL06 | 600W | 20-100% |
| Legrand | Adorne | ADTP703TU | 700W | 20-100% |
| | Harmony | H703PTW | 700W | OK |
| Cooper | Aspire | 9540 | 1000W | OK |
| | Devine | DAL06P | 300W | OK |