

1	•	

Product Specifications for E24388-91PC

Job Name:	Job Type:
Quantity:	Comments

E24388-91PC

Illusion 8-Light Pendant

Finish Polished Chrome

Lamping

Number of Bulb(s)	8
Light Type	Xenon
Bulb Type	G9
Max Bulb Wattage	40
Max Fixture Wattage	320
Rated Life	±2,000 Hours
Rated Lumens	±4,000
Color Temp	±2,900 K
Bulb(s) Included	Yes
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	Standard Dimmer

Glass/Shade Bubble

Measurements

measurements	
Width	13.00"
Height	15.00"
Length	32.00"
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
HCO	N/A
Min Overall Height	N/A
Max Overall Height	58.00"
Hanging Weight	15.19 lb(s)
Height Adjustable	Yes
Slope	120°
Chain Length	N/A
Wire Length	N/A

Product Category Linear Pendant

Shipping	
Carton Weight	24.76 lb(s)
Carton Width	15.50"
Carton Height	14.00"
Carton Length	15.50"
Carton Cubic Feet	N/A
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes
	Carton Weight Carton Width Carton Height Carton Length Carton Cubic Feet Master Pack Master Pack Weight Master Pack Width Master Pack Height Master Pack Length Master Cubic Feet

Certification

Safety Rating	Dry
Energy Star	No
CA Title 24	No
CA Title 20	No
ADA	No

Other

Canopy Width

Canopy Height

Canopy Length

UPC Code 845094055471 Material Steel

Equivalents

N/A

N/A

Incandescent Watts N/A **Fluorescent Watts** N/A

ET2 Contemporary Lighting and all designs, logos and images © 2014 ET2 Contemporary Lighting. All Rights Reserved. ET2 Contemporary Lighting reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes. Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.