


assembly instructions

Family: Pueblo | Item No. 1190 SN




Drawing 1 - Strap Detail



Vstart here

- 1. Find a clear area in which you can work.
- 2. Unpack fixture and glass from carton.
- 3. Carefully review instructions prior to assembly.


Drawing 2 - Fixture Mounting



*** The construction of this fixture will be accomplished by first mounting the mounting strap to the junction box, making all necessary electrical connections, mounting the fixture to the wall and then installing the glass.

- 1. Prepare mounting strap (A) by threading the two 1 1/4" long mounting screws (B) into the back of the gull wing bracket - see Drawing 1.
- Be sure the holes into which the screws are threaded match the spacing of holes (D) in the back plate (E) - see Drawings 1 and 2.
- 2. Attach mounting strap (A) to junction box (J) using two 1" screws (C) provided see Drawing 2.

Drawing 3 - Fixture Assembly



SAFETY WARNING: READ WIRING AND GROUNDING INSTRUCTIONS (I.S. 18) AND ANY ADDITIONAL DIRECTIONS. TURN POWER SUPPLY OFF DURING INSTALLATION. IF NEW WIRING IS REQUIRED, CONSULT A QUALIFIED **ELECTRICIAN OR LOCAL AUTHORITIES FOR CODE REQUIREMENTS.**

Make electrical connections from supply wire to fixture lead wires. Refer to instruction sheet (I.S. 18) and follow all instructions to make all necessary wiring connections. Then refer back to this sheet to continue installation of this fixture.

- 1. Slide backplate (E) over screws (B) and secure with ball knobs (F) see Drawing 2.
- 1. To install glass, slip glass panel (1) through bottom of cage assembly (2) see Drawing 3.
- 2. Slip top of glass panel (1) under top glass clips (3).
- 3. Slip bottom of glass panel (1) into the bottom of the cage assembly (2).
- 4. Bend lower glass clips (4) up to retain glass panels (1).
- 5. Repeat steps 1-4 for remaining panels.
- 6. Fixture can now be lamped accordingly.

Note: Maximum wattage for 1190 fixture is 75 watts per bulb.

9.12.08