

design • illuminate • enjoy

assembly instructions


1460 1464 1465

Family: CANYON | Item No. 1460/1464/1465




Ystart here

Drawing 1 - Fixture Assembly



- 1
- 1. Find a clear area in which you can work.
- 2. Unpack fixture and glass from carton.
- 3. Carefully review instructions prior to assembly.
- *** The construction of this fixture will be accomplished by assembling main body of fixture, mounting the mounting strap to the junction box, making all necessary electrical connections and then mounting the fixture to the wall.
- 2
- 1. To install glass (2) in cage assembly (1), slip bottom of glass panel into channel (3) in the bottom of the cage see **Drawing 1**.
- 2. Slip top of glass panel (2) under glass clip (4). Note: cut gasket material supplied to size and place between glass and clip.
- 3. Fold over glass clip (4) to secure glass in cage (1).


Drawing 2 - Strap Detail



- 3
- 1. Prepare gem strap (A) for mounting, by threading the two screws (B) provided into the back of the gull wing bracket on gem strap (A) see **Drawing 2**.
- Be sure that holes into which the screws are threaded match the spacing of the mounting holes (**D**) in the back plate (**E**) see **Drawings 2 and 3.**
- 2. Mount gem strap (A) to junction box (J) using two 1" long screws (C) provided.

SAFETY WARNING: READ WIRING AND GROUNDING INSTRUCTIONS (I.S. 18) AND ANY ADDITIONAL DIRECTIONS. TURN POWER SUPPLY OFF DURING INSTALLATION. IF NEW WIRING IS REQUIRED, CONSULT A QUALIFIED ELECTRICIAN OR LOCAL AUTHORITIES FOR CODE REQUIREMENTS.

Drawing 3 - Fixture Mounting



4

Make electrical connections from supply wire to fixture lead wires. Refer to instruction sheet 18 (I.S. 18) and follow instructions to make all necessary wiring connections.

5

- 1. Mount the fixture by slipping the holes (D) in the back plate (E) over the screws (B) in the mounting strap (A) see **Drawing 3**.
- 2. Hold fixture against wall and thread ball knobs (F) onto end of screw (B) showing through the back plate.

Note: Maximum wattage for 1460 fixture is 60 watts per bulb. Maximum wattage for 1464 fixture is 75 watts per bulb. Maximum wattage for 1465 fixture is 100 watts per bulb. 6.01.11