




Item No. 4225



Drawing 1 - Assembly



Drawing 2 - Glass Installation



▼ start here

1

1. Find a clear area in which you can work.
2. Unpack fixture and glass from carton.
3. Carefully review instructions prior to assembly.

***** The construction of this fixture will be accomplished by first assembling the main body of the fixture, making all necessary electrical connections, hanging the fixture from the ceiling, and then installing the glass.**

SAFETY WARNING: READ WIRING AND GROUNDING INSTRUCTIONS (I.S. 18) AND ANY ADDITIONAL DIRECTIONS. TURN POWER SUPPLY OFF DURING INSTALLATION. IF NEW WIRING IS REQUIRED, CONSULT A QUALIFIED ELECTRICIAN OR LOCAL AUTHORITIES FOR CODE REQUIREMENTS.

2

1. To assemble main body, spread arms (A) located on the main body assembly (1), until they are equally spaced **72 degrees** apart - see **Drawings 1 & 2**.
2. It may be necessary to adjust scroll (S) after arms are moved into position, so they are centered on the arm.
3. Please refer to the hanging instruction sheet (I.S. 19-92) provided to hang fixture. Then refer back to this sheet to install glass.

3

1. To install glass first remove socket ring (4) and socket spacer (3) from socket (B) - see **Drawing 2**.
2. Slip glass (2) over socket (B).
3. Slip socket spacer (3) over socket (B).
4. Thread socket ring (4) onto socket (B) using socket tool provided.

01.01.13