



Drawing 1 - Glass Installation

▼ start here

1

1. Find a clear area in which you can work.
2. Unpack fixture and glass from carton.
3. Carefully review instructions prior to assembly.

***** The construction of this fixture will be accomplished by first assembling the main body of the fixture, making all necessary electrical connections, hanging the fixture from the ceiling, and then installing the glass.**

SAFETY WARNING: READ WIRING AND GROUNDING INSTRUCTIONS (I.S. 18) AND ANY ADDITIONAL DIRECTIONS. TURN POWER SUPPLY OFF DURING INSTALLATION. IF NEW WIRING IS REQUIRED, CONSULT A QUALIFIED ELECTRICIAN OR LOCAL AUTHORITIES FOR CODE REQUIREMENTS.

2

1. To assemble main body, slip center column (2) along wire and thread onto nipple (A) and tighten. Making sure the three holes in the top body (B) align with the three arms on the main body assembly (1).
2. Attach the top of scroll (3) to the canopy (B) using the ball knob screws (4).
3. Attach the bottom of the scroll (3) using the ball knob screws (5).
4. Repeat steps 2-3 for remaining scrolls.
5. Thread center stem (6) into coupler (C) approximately 3/8".
6. Thread hex nut (D) onto stem (6) until it is 1 5/8" from the bottom of the stem.
7. Please refer to the hanging instruction sheet (I.S. 19) provided to hang fixture. Then refer back to this sheet to install glass.

3

1. Prior to installing glass, fixture can now be lamped.
2. To install glass, slip positioning ring (7) into center hole of glass (8).
3. Slip glass (8) and ring (7) onto stem (6) and up against hex nut (D) and hold in position.
4. Slip rubber washer (9) and metal washer (10) onto stem (6) and hold in position.
5. Thread hex nut (11) onto center stem (6) and tighten to secure glass (8).
6. Slip decorative cap (12) onto stem (6) and hold in position.
7. Thread bottom knob (13) onto the end of center stem (6).

Note: Maximum wattage for 4532 fixture is 75 watts per bulb.

2.7.08

