

LIGHTING SOLUTIONS

ARCHITECTURAL LIGHTING FIXTURES FOR RETAIL,
COMMERCIAL AND RESIDENTIAL APPLICATIONS



INDOOR & OUTDOOR LIGHTING
Rigid Linear • Recessed Mount
Surface Mount • Specialty Lighting

FOURTH EDITION


JESCO
LIGHTING GROUP

JESCO Lighting Group, one of the first lighting companies to embrace LED technology, has once again broadened its lighting line of fixtures to offer diverse solutions for a myriad of Retail and Commercial applications.

Our newest lighting collection is comprised of energy efficient products, using the most advanced technology for contemporary indoor settings. This catalog features our custom configurable Specialty lighting, our Recessed, Surface, and Rigid Linear lighting and, most recently, our RADIANT Remote Power System. JESCO is proud to provide a comprehensive range of alternatives to meet any design requirement.

In this catalog, you will discover the latest in Lighting Solutions for Retail Displays, In-store Visual Merchandising, Showcases, Exhibits or Museum Case Lighting, in addition to the finest alternatives for illuminating Shelves, Cabinets, Coves, Toe Kicks and Backlighting. Options are also included for Outdoor Lighting.

JESCO's steadfast commitment remains to provide customized lighting solutions, backed by reliability, at a fraction of the cost.



Cove: SG-LED
Shelves: S601
Ceiling: DL-FLEX-HD in
CH-RI-T2 channel
Backlighting: DL-FLEX-UP

TABLE OF CONTENTS

CUSTOM CONFIGURABLE SPECIALTY LIGHTING



CBF BESPOKE FIXTURE
p. 9



RADIANZ STEM-MOUNTED HORIZONTAL p. 10-12



RADIANZ HORIZONTAL SERIES
p. 13



RADIANZ VERTICAL SERIES
p. 14-19



RADIANZ LINKS SERIES
p. 20



CARBON FIBER FINISH
p. 22



RADIANZ EXHIBIT SERIES
p. 23

RECESSED / SURFACE MOUNTED



PK820 LED SLIM DISKS
p. 26



PK811 LED SLIM DISKS
p. 27



PK921, PK923 LED SLIM DISKS
p. 28



RADIANZ MICRO SERIES
p. 29



RADIANZ SURFACE SERIES
p. 30



LOW VOLTAGE MINI RECESSED SERIES p. 31

RIGID LINEAR



CBF BESPOKE FIXTURE
p. 9



RADIANZ LINKS SERIES
p. 20



LED SLIM STIX S602P
p. 35



LED SLIM STIX S601, S601P
p. 37




S650 SERIES
p. 38



S902 SERIES
p. 39



DL-RS SERIES
p. 41



RADIANZ TRACK
p. 42



LED SLEEK ULTRA
p. 45



FLUORESCENT SLEEK PLUS
p. 46-48

POWER ACCESSORIES



SMART TRACK Adjustable Power System p. 50



RADIANZ Remote Power System p. 52



LED Power Supplies & Transformers p. 53-59



Dimming, RGB & DMX Controllers p. 60-62



	RETAIL DISPLAY	SHOWCASE	SHELF	CABINET - UNDER	CABINET - OVER	COVE	TOE KICK	BACKLIGHTING	EXHIBIT	OUTDOOR
--	----------------	----------	-------	-----------------	----------------	------	----------	--------------	---------	---------

SPECIALTY LIGHTING

CBF	page 9	•	•	•	•	•	•	•	•	
RADIANZ Horizontal	page 10	•	•	•					•	
RADIANZ Vertical	page 14	•	•						•	
RADIANZ Link	page 20	•	•	•	•				•	
RADIANZ Exhibit	page 23	•							•	


RECESSED/SURFACE MOUNT















PK800, PK900 Series	page 26	•	•	•	•				•	
RADIANZ Micro	page 29	•	•	•	•				•	
RADIANZ Surface	page 30	•	•	•	•				•	
Mini Recessed	page 31	•	•	•	•				•	

RIGID LINEAR

S602P	page 35	•	•	•	•	•		•	•	
S601, S601P	page 37	•	•	•	•	•		•	•	
S650	page 38	•	•	•	•					
S902	page 39	•	•	•	•	•	•	•	•	
DL-RS	page 41	•	•	•	•	•	•	•	•	•
RADIANZ Track	page 43	•		•	•					
SLEEK ULTRA SG-LED	page 45	•	•	•	•	•	•	•	•	
SLEEK PLUS Fluorescent	page 46	•	•	•	•	•	•	•	•	

SPECIALTY LIGHTING FEATURE MATRIX



														
	CBF page 9	SD383 page 10	SD283 page 11	SD183 page 12	SD100 page 13	SD105 page 14	SD304 page 15	SD107 page 16	SD109 page 16	SD300 page 17	SD106 page 18	SD302 page 19	SDL page 20	ARC201 page 23
Input	24V DC	24V DC	24V DC	12V DC	12V DC	12V DC	350 mA	350 mA	12V DC	350 mA	350 mA	700 mA	24V DC	12V DC
Height (Max)	5/16" to 17/32"	18"	20"	24"	3/4" Ø	20"	11 1/4"	20"	20"	20"	11 3/4"	11 3/4"	9/16"	2 1/2" / 2"
Length / Width (Max)	1" to 96"	60"	96"	120"	120"	3/4" Ø	4 3/8"	1"	1"	1"	15/16"	3/4"	72"	24"
Watts, Max	6.0 or 4.0/ft	4.0/ft	4.0 or 6.0/ft	6.5 or 8.0/ft	6.5 or 8.0/ft	6.5 or 8.0/ft	3.0	3.0	4.0	4.0	3.0	1.5	1.0/2.0	3.8/7.85
Lm, Max	536/332	320	320 /480	525/650	525/650	525/650	240	418	412	300	360	120	120/240	434/800
Lm/Watts, Max	89/83	80	80	81	81	81	80	140	103	75	120	80	120	114/102
Beam Angle	120° or 60°	90°	90°	90°	90°	90°	100°	120°	120°	20° to 60°	30°	20°, 40°, 60°	30°	20°, 30°, 45°
CCT	3000K 4000K 6000K	2700K 3000K 3500K 4000K 5000K	2700K 3000K 3500K 4000K 5000K	2700K 3000K 4000K 5000K	2700K 3000K 4000K 5000K	2700K 3000K 4000K 5000K	2700K 3000K 4000K 5000K	2700K 3000K 4000K 5000K	2700K 3000K 4000K 5000K	3000K 4000K 5000K	2700K 3000K 4000K 5000K	2700K 3000K 4000K 5000K	2700K 3000K 4000K 5000K	2700K 3000K 3500K 4000K 5000K
Dimmable	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Adjustable After Mounting	★	•	•	•	•	•	•	•	•	•	•	•	•	•
Surface Mountable	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Customizable (Height, Length, Finish)	•	•	•	•	•	•	•	•	•	•	•	•	•	•

★ = Adjustable with Mounting Hardware



Shelves: S601
Backlighting: SG-LED
Hartmann Flagship Store, New York, NY
Millwork: Daniel DeMarco & Associates

CBF BESPOKE SLIM LED

Project: The Frye Company
Roosevelt Field Mall
Garden City, NY
Millwork: JPMA, Montreal



FORM + FUNCTION

- Custom Lighting Without the Custom Cost
- A bespoke, high output, low profile LED fixture that allows for complete customization to meet any design need
- Bespoke features 72 LEDs per foot, providing a uniform appearance with no hot spots
- Choice of a flat lens in clear, frosted or opal finish or a rounded 60° beam focusing lens
- Choice of standard lengths - 12", 24", 36", 48", 60" or 72" - or custom lengths up to 8 feet¹. Custom cut lengths in precise 1" increments
- Choice of input and output, plug and play or hardwire connections in standard lengths of 18", 36", 48" or 96" or a custom length in between
- Quickly made to order and shipped ready for installation - saving time and money as well as eliminating on-site assembly

APPLICATIONS

- Showcase Lighting
- Exhibit Lighting
- Retail Displays
- Under Cabinet & Soffit Lighting
- Shelf Lighting
- Cove Lighting
- Toe Kick Lighting
- Backlighting
- Showcase Lighting
- Picture Window Lighting



CBF

COMMERCIAL BESPOKE SLIM 6W LED FIXTURE

LED	24V DC	6.0 W/Ft	536 Lm/Ft	89 Lm/W	80+ CRI
14' MAX	DIM	DRY	UL LISTED		


CBF - LOW WATT

COMMERCIAL BESPOKE SLIM 4W LED FIXTURE

LED	24V DC	4.0 W/Ft	332 Lm/Ft	83 Lm/W	80+ CRI
20' MAX	DIM	DRY	UL LISTED		

Dims: 1 1/16" W x 5/16" H (CL, OP & FR)
1 1/16" W x 17/32" H (FR60)

Beam Angle: 120° (CL, OP & FR)
60° (FR60)



ACCESSORIES



CH-SM-31-CLIP
Clear Mounting Clip
Recommended: 1 every 2'



CH-SM-31-CLIP-A
Adjustable Mounting Clip
Recommended: 1 every 2'

COMPONENTS Pages 50-62

POWER SUPPLIES

24V PP	24V HW	24V JB
-----------	-----------	-----------

CONTROLS

DIM

BATTERY

BAT

TO ORDER

MODEL	CHANNEL	LENS	LENGTH**	LED TYPE	CCT	INPUT	OUTPUT
CBF	SM31						
		CL - Clear	12 - 12 1/4"	HD72 - 6.0W	27 - 2700K	Plug & Play:	Plug & Play:
		OP - Opal Matte	24 - 24 1/4"	HD724 - 4.0W	30 - 3000K	118 - 18"	DEC - Dead End
		FR - Frosted	36 - 36 1/4"		35 - 3500K	136 - 36"	O18 - 18"
		FR60 - 60° Frosted	48 - 48 1/4"		40 - 4000K	148 - 48"	O36 - 36"
			60 - 60 1/4"		60 - 6000K	196 - 96"	O48 - 48"
			72 - 71 1/4"			Hardwire:	Hardwire:
			84 - 84 1/4"†			IHW18 - 18"	DEC - Dead End
			96 - 95 1/4"†			IHW36 - 36"	OHW18 - 18"
			xx - Custom			IHW48 - 48"	OHW36 - 36"
			96" Max*			IHW96 - 96"	OHW48 - 48"


Lumen data based on 4000K, with Clear Lens Cover.

* Custom lengths are available up to 8ft. in increments of 1".

** For overall length: Add 1/4" if requiring both input and output cables. See spec sheet.

† Only available with FR60 lens. (Other lenses only available in 6' length.)

Please note we can mix and match a CBF fixture with any of our DL-FLEX LED strips and any of our channels. Contact factory for all your options. Specifications subject to change without notice. See spec sheet or jescolighting.com for more details.




FORM + FUNCTION

- An micro slim 1/4" diameter fixture
- Wide beam angle (90°) for even illumination
- Customizable height (up to 18") and length (up to 60" with center support)
- Light can be aimed 350°
- Frosted lens cover eliminates glare
- Finish, wattage, and CCT are customizable

APPLICATIONS

- Showcase Lighting
- Exhibit Lighting
- Retail Displays



SD383CV

RADIANTZ 4W ULTRA SLIM LINEAR
STEM MOUNTED

LED	24V DC	4.0 W/Ft	320 Lm/Ft	80 Lm/W	90+ CRI
DIM	90°	350°	DRY	UL LISTED	

Dims: 1/4" Ø

COMPONENTS Pages 52-62

POWER SUPPLIES	24V PP 24V HW 24V JB
ACCESSORIES	LED
CONTROLS	DIM
BATTERY	BAT

TO ORDER

MODEL	WATTS	LENGTH	HEIGHT	CCT/CRI	FINISH
SD 383CV	4W 4W - 4W/Ft	12L - 12" 24L - 24" xxL - Custom 96" Max*	08H - 8" 12H - 12" xxH - Custom 18" Max*	2790 - 2700K 90CRI 3090 - 3000K 90CRI 3590 - 3500K 90CRI 4090 - 4000K 90CRI 5090 - 5000K 90CRI	SV - Silver BK - Black* PS - Polished Aluminum* XX - Custom*

* Custom finishes available. Contact factory more information.

Lumen data based on 4000K



Specifications subject to change without notice. See spec sheet or jescolighting.com for more details.

FORM + FUNCTION

- An ultra slim $\frac{3}{8}$ " diameter fixture
- Wide beam angle (90°) for even illumination
- Customizable height (up to 20") and length (up to 96" with center support)
- Light can be aimed 350°
- Frosted lens cover eliminates glare
- Finish, wattage, and CCT are customizable

APPLICATIONS

- Showcase Lighting
- Exhibit Lighting
- Retail Displays



SD283CV-4W

RADIANT 4W MINI LINEAR
STEM MOUNTED

LED	24V DC	4.0 W/Ft	320 Lm/Ft	90+ CRI
DIM	90°	350°	DRY	UL LISTED

Dims: $\frac{3}{8}$ " Ø

SD283CV-6W

RADIANT 6W MINI LINEAR
STEM MOUNTED

LED	24V DC	6.0 W/Ft	480 Lm/Ft	90+ CRI
DIM	90°	350°	DRY	UL LISTED

Dims: $\frac{3}{8}$ " Ø

COMPONENTS Pages 52-62

POWER SUPPLIES	24V PP	24V HW	24V JB
ACCESSORIES	LED		
CONTROLS	DIM		
BATTERY	BAT		

TO ORDER

MODEL	WATTS	LENGTH	HEIGHT	CCT/CRI	FINISH
SD 283CV	4W - 4W/Ft 6W - 6W/Ft	12L - 12" 24L - 24" 36L - 36" xxL - Custom 96" Max*	08H - 8" 12H - 12" xxH - Custom 20" Max*	2790 - 2700K 90CRI 3090 - 3000K 90CRI 3590 - 3500K 90CRI 4090 - 4000K 90CRI 5090 - 5000K 90CRI	SV - Silver BK - Black* PS - Polished Aluminum* XX - Custom*

* Custom Options. Consult factory for more information.
Lumen data based on 4W, 4000K
Specifications subject to change without notice. See spec sheet or jescolighting.com for more details.




FORM + FUNCTION

- SD183 is a stem-mounted horizontal, high output LED fixture
- Wide beam angle (90°) for even illumination
- Available in standard nominal lengths of 12", 24", 36" and 48" and standard stem heights of 8", 12" and 20"
- The SD183 fixture length and stem height may be custom ordered. Additional power supply may be required – consult factory.
- Standard in Silver and Black finishes. Custom finishes available.
- Frosted lens cover reduces glare

APPLICATIONS

- Showcase Lighting
- Exhibit Lighting
- Retail Displays



SD183CV-6W

RADIANT 6.5W LINEAR STEM MOUNTED

LED	12V DC	6.5 W/Ft	525 Lm/Ft	81 Lm/W	80+ CRI
DIM	90°	350°	DRY	UL LISTED	

Dims: 3/4" Ø

SD183CV-8W

RADIANT 8W LINEAR STEM MOUNTED

LED	12V DC	8.0 W/Ft	650 Lm/Ft	81 Lm/W	80+ CRI
DIM	90°	350°	DRY	UL LISTED	

Dims: 3/4" Ø

COMPONENTS Pages 52-62

POWER SUPPLIES	12V PP	12V HW	12V JB
ACCESSORIES	LED		
CONTROLS	DIM		
BATTERY	BAT		

TO ORDER

MODEL	WATTS	LENGTH	HEIGHT	CCT/CRI	FINISH**
SD183CV	-	-	-	-	-
	6W - 6.5W/Ft 8W - 8.0W/Ft	12L - 12" 24L - 24" 36L - 36" 48L - 48" xxL - Custom 120" Max*	08H - 8" 12H - 12" 20H - 20" xxH - Custom 24" Max*	2780 - 2700K 80CRI 3080 - 3000K 80CRI 4080 - 4000K 80CRI 5080 - 5000K 80CRI	SV - Silver BK - Black* PS - Polished Silver* BR - Brass* BZ - Bronze* WH - White* CB - Carbon Fiber*

* Contact factory more information.

** Consult factory for custom finish options.

Lumen data based on 6.5W, 4000K


Custom lengths over 60 inches long will require two power supplies. There will be a power feed on both ends of the fixture.

Specifications subject to change without notice. See spec sheet or jescolighting.com for more details.

Shown at actual size

FORM + FUNCTION

- SD100 is a high-output LED fixture designed for use in display showcases
- Wide beam angle (90°) for even illumination
- Available in standard lengths of 12", 24", 36" and 48". The fixture may be custom-ordered in any length and finish. Additional power supply may be required for longer lengths – consult factory.
- The SD100 mounts inside cabinets or display cases with clips or mounting brackets
- Frosted lens cover reduces glare



APPLICATIONS

- Showcase Lighting
- Exhibit Lighting
- Retail Displays
- Under Cabinet Lighting



Shown in Carbon finish details on page 22

ACCESSORIES



SD100CC-R-MC
(2) 0° Mounting Clips
for SD100CC-R
Snap in



SD100CC-R-MB1
(2) 0-90° Mounting Brackets
for SD100CC-R
Attached to the end of each fixture. Set screw holds fixture in place. Matched to finish of fixture.

SD100CV-6W

RADIANT 6W LINEAR

LED	12V DC	6.5 W/Ft	525 Lm/Ft	81 Lm/W	80+ CRI
DIM	90°	350°	DRY	UL LISTED	

Dims: 3/4" Ø

SD100CV-8W

RADIANT 8W LINEAR

LED	12V DC	8.0 W/Ft	650 Lm/Ft	81 Lm/W	80+ CRI
DIM	90°	350°	DRY	UL LISTED	

Dims: 3/4" Ø

COMPONENTS Pages 52-62

POWER SUPPLIES	12V PP	12V HW	12V JB
ACCESSORIES	LED		
CONTROLS	DIM		
BATTERY	BAT		

TO ORDER

MODEL	WATTS	LENGTH*	CCT/CRI	FINISH*
SD100CV	-	-	-	-
	6W - 6.5W/Ft 8W - 8.0W/Ft	12L - 12" 24L - 24" 36L - 36" 48L - 48" xxL - Custom 120" Max*	2780 - 2700K 80CRI 3080 - 3000K 80CRI 4080 - 4000K 80CRI 5080 - 5000K 80CRI	SV - Silver BK - Black* PS - Polished Silver* BR - Brass* BZ - Bronze* WH - White* CB - Carbon Fiber*

* Contact factory for more information.


Lumen data based on 6.5W, 4000K

Custom lengths over 60 inches long will require two power supplies. There will be a power feed on both ends of the fixture. Specifications subject to change without notice. See spec sheet or jescolighting.com for more details.



FORM + FUNCTION

- SD105 is a vertical, high output LED fixture designed for use in display showcases
- Wide beam angle (90°) for even illumination
- Available in heights of 8", 12" and 20"
- The fixture is customizable to any height (24" Max) and finish – consult factory
- Frosted lens cover reduces glare



APPLICATIONS

- Showcase Lighting
- Exhibit Lighting
- Retail Displays

SD105CV-6W

RADIANT 6W VERTICAL

LED	12V DC	6.0 W/Ft	525 Lm/W	81 Lm/W	80 CRI
DIM	90°	350°	DRY	UL LISTED	

Dims: 3/4" Ø

SD105CV-8W

RADIANT 8W VERTICAL

LED	12V DC	8.0 W/Ft	650 Lm/W	81 Lm/W	80 CRI
DIM	90°	350°	DRY	UL LISTED	

Dims: 3/4" Ø

COMPONENTS Pages 52-62

POWER SUPPLIES	12V PP, 12V HW, 12V JB
ACCESSORIES	LED
CONTROLS	DIM
BATTERY	BAT

TO ORDER

MODEL	WATTS	HEIGHT	CCT/CRI	FINISH*
SD105CV	- <input type="text"/>	- <input type="text"/>	- <input type="text"/>	- <input type="text"/>
	6W - 6.5W/Ft 8W - 8.0W/Ft	08H - 8" 12H - 12" 20H - 20" xxH - Custom 24" Max*	2780 - 2700K 80CRI 3080 - 3000K 80CRI 4080 - 4000K 80CRI 5080 - 5000K 80CRI	SV - Silver BK - Black* PS - Polished Silver* BR - Brass* BZ - Bronze* WH - White* CB - Carbon Fiber*


* Contact factory for special height and finish options.
Lumen data based on 4000K
Specifications subject to change without notice. See spec sheet or jescolighting.com for more details.

FORM + FUNCTION

- Clean, minimalist design
- Ultra-slim $\frac{1}{4}$ " diameter
- Wide beam angle of 100° for optimum illumination
- Custom heights and finishes available
- High output of 240 lumens using only 3W

APPLICATIONS

- Showcase Lighting
- Exhibit Lighting
- Retail Displays



SD304CC

RADIANZ 3W ULTRA SLIM VERTICAL

LED	350 mA	3.0W	240 Lm	80 Lm/W	90+ CRI
DIM	100°	350°	DRY	UL LISTED	

Dims: 11 $\frac{1}{4}$ " H x 4 $\frac{3}{8}$ " W x $\frac{1}{4}$ " \varnothing

COMPONENTS Pages 52-62

POWER SUPPLIES	CC PP CC HW
ACCESSORIES	CC
CONTROLS	Consult factory
BATTERY	BAT

TO ORDER

MODEL	WATTS	HEIGHT	CCT/CRI	FINISH
SD304CC	3W	11H		
	3W - 3.0W	11H - 11 $\frac{1}{4}$ " xxH - Custom 11 $\frac{1}{4}$ " Max*	2790 - 2700K 90CRI 3090 - 3000K 90CRI 4090 - 4000K 90CRI 5090 - 5000K 90CRI	SV - Silver BK - Black* CH - Chrome*

* Custom heights and finishes available. Consult factory for availability.

Lumen data based on 3000K

Specifications subject to change without notice. See spec sheet or jescolighting.com for more details.

SPECIALTY LIGHTING • LED RADIANT VERTICAL





FORM + FUNCTION

- High output LED fixture with an adjustable light head that allows aiming of light within an 90° arc
- Available in heights of 8", 12", 20"
- The fixture may be custom ordered in any height and finish - consult factory

APPLICATIONS

- Showcase Lighting
- Exhibit Lighting
- Retail Displays



SD107 COMPONENTS Pages 52-62

POWER SUPPLIES	CC PP	CC HW
ACCESSORIES	CC	
CONTROLS	Consult factory	
BATTERY	BAT	

SD109 COMPONENTS Pages 52-62

POWER SUPPLIES	12V PP	12V HW	12V JB
ACCESSORIES	LED		
CONTROLS	DIM		
BATTERY	BAT		

SD107CC

RADIANT VERTICAL

LED	350 mA	3.0W	418 Lm	140 Lm/W	90 CRI
DIM	120°	90°	350°	DRY	UL LISTED

Head : 2 5/8"
Base : 1" Ø

TO ORDER SD107

MODEL	WATTS	HEIGHT	CCT/CRI	FINISH*
SD107CC	3W			
		08H - 8"	2790 - 2700K 90CRI	SV - Silver
		12H - 12"	3090 - 3000K 90CRI	BK - Black*
		20H - 20"	4090 - 4000K 90CRI	BZ - Bronze*
		xxH - Custom	5090 - 5000K 90CRI	WH - White*
		20" Max*		PS - Polished Silver*
				CB - Carbon Fiber*

SD109CV

RADIANT VERTICAL

LED	12V DC	4.0W	412 Lm	103 Lm/W	90 CRI
DIM	60°	90°	350°	DRY	UL LISTED

Head : 2 5/8"
Base : 1" Ø



TO ORDER SD109

MODEL	WATTS	HEIGHT	CCT/CRI	FINISH*
SD109CV	4W			
		08H - 8"	3090 - 3000K 90CRI	SV - Silver
		12H - 12"	4090 - 4000K 90CRI	BK - Black*
		20H - 20"	5090 - 5000K 90CRI	BZ - Bronze*
		xxH - Custom		CH - Chrome*
		20" Max*		PS - Polished Silver*
				CC - Custom*

* Consult factory for more information.
Lumen data based on 4000K
Specifications subject to change without notice. See spec sheet or jescolighting.com for more details.



Shade easily extends to adjust from wide 60° to spot 20° beam



FORM + FUNCTION

- Unique adjustable shade head allows for 20° to 60° beam selection
- The head also pivots 90° for easy positioning
- Available in heights of 8", 12", 20"
- The fixture may be custom ordered in any height (up to 20") and finish – consult factory

APPLICATIONS

- Showcase Lighting
- Exhibit Lighting
- Retail Displays

SD300CC

RADIANT ADJUSTABLE BEAM VERTICAL

LED	350 mA	3.68W	300 Lm	75 Lm/W	90 CRI	DIM	90°	350°	DRY	UL LISTED
-----	--------	-------	--------	---------	--------	-----	-----	------	-----	-----------

Beam: Variable Zoom 20° to 60°

Head: 1 3/4" L x 1" Ø

Base: 1" Ø

COMPONENTS Pages 52-62

POWER SUPPLIES	CC PP CC HW
ACCESSORIES	CC
CONTROLS	Consult factory
BATTERY	BAT

TO ORDER

MODEL	WATTS	HEIGHT	CCT/CRI	FINISH*
SD300CC	4W			
	4W - 3.68W	08H - 8" 12H - 12" 20H - 20" xxH - Custom 20" Max*	2790 - 2700K 90CRI 3090 - 3000K 90CRI 4090 - 4000K 90CRI 5090 - 5000K 90CRI	SV - Silver BK - Black* BR - Brass* BZ - Bronze* PS - Polished Aluminum* WH - White*

* Custom option. Contact factory for availability.

Lumen data based on 4000K



Specifications subject to change without notice. See spec sheet or jescolighting.com for more details.

FORM + FUNCTION

- Three adjustable heads rotate independently up to 90 degrees for showcasing multiple items using a single fixture
- Remote 350 mA driver delivers 1W to each head for a total of 3W per fixture
- Fixture can rotate 350° for aiming after being mounted
- Hooded light output eliminates glare

APPLICATIONS

- Showcase Lighting
- Exhibit Lighting
- Retail Displays



SD106CC

RADIANT FOCUSING ADJUSTABLE VERTICAL



Dims: 11 3/4" H x 1 5/16" Ø

TO ORDER

MODEL	WATT	HEIGHT	CCT/CRI	FINISH*
SD106CC	3W	12H		
	3W - 3.0W	12H - 11 3/4"	2790 - 2700K 90CRI 3090 - 3000K 90CRI 4090 - 4000K 90CRI 5090 - 5000K 90CRI	SV - Silver CH - Chrome* BK - Black*

* Custom height and finishes available. Consult factory for availability.
Lumen data based on 4000K
Specifications subject to change without notice. See spec sheet or jescolighting.com for more details.

COMPONENTS Pages 52-62


POWER SUPPLIES	CC PP CC HW
ACCESSORIES	CC
CONTROLS	Consult factory
BATTERY	BAT

FORM + FUNCTION

- Clean, minimalist design
- Multiple pre-selected beam angles available for precise focusing
- Aimable – Fixture rotates 350°, head tilts down up to 40°
- The fixture may be custom ordered in any finish – consult factory
- Height adjustable from 3 15/16" to 11 3/4" after mounting
- High output of 120 lumens using only 1.5W

APPLICATIONS

- Showcase Lighting
- Exhibit Lighting
- Retail Displays



SD302CC

RADIANT HEIGHT-ADJUSTABLE VERTICAL

LED	700 mA	1.5W	120 Lm	80 Lm/W	90 CRI	DIM	40°	350°	DRY	UL LISTED
-----	--------	------	--------	---------	--------	-----	-----	------	-----	-----------

Height: 3 15/16" - 11 3/4" Adjustable
Head: 1 5/16" L x 3/4" Ø

COMPONENTS Pages 52-62

POWER SUPPLIES	CC PP CC HW
ACCESSORIES	CC
CONTROLS	Consult factory
BATTERY	BAT

TO ORDER

MODEL	WATT	BEAM	CCT/CRI	FINISH*
SD302CC	2W			
	2W - 1.5W	20D - 20° 40D - 40° 60D - 60°	2790 - 2700K 90CRI 3090 - 3000K 90CRI 4090 - 4000K 90CRI 5090 - 5000K 90CRI	SV - Silver CH - Chrome* BK - Black*

* Custom heights and finishes available. Consult factory for availability.
Lumen data based on 3000K
Specifications subject to change without notice. See spec sheet or jescolighting.com for more details.

RADIANZ CONFIGURABLE LINKS & CHANNEL



SDL

RADIANZ CONFIGURABLE LINEAR LINKS AND CHANNEL



Link Dims: 5 15/16" L x 9/16" W

Channel Dims: 3/4" H x 3/4" W (V-Profile Channel)
9/16" H x 1 1/16" W (U-Profile Channel)

Max Channel Length: 72"

Mounting: Surface-mounted

* for Adjustable Links

† per LED head @ 3000K

TO ORDER LINEAR CHANNEL

TRACK	TYPE	LENGTH	FINISH
SDLC	-	-	-
	U - U-Profile Channel	12 - 12"	BK - Black
	V - V-Profile Channel	24 - 24"	SV - Silver*
		36 - 36"	CC - Custom*
		48 - 48"	
		60 - 60"	
		72 - 72"	
		xx - Custom 72" Max	

TO ORDER LINEAR MODULE

TRACK	MODULE	CCT/CRI	FINISH
SDLL CV	-	-	-
	1F - 1-Light Fixed	2790 - 2700K 90CRI	BK - Black
	1A - 1-Light Adjustable	3090 - 3000K 90CRI	SV - Silver*
	2F - 2-Light Fixed	3590 - 3500K 90CRI	CC - Custom*
	2A - 2-Light Adjustable	4090 - 4000K 90CRI	
	BF - Blank Flat Module	5080 - 5000K 90CRI	

* Custom finishes available - consult factory.

† For dimming applications consult factory.

Note: Blank modules are available to snap onto the track for a more integrated look and to hide the wiring. Blanks are 6" long, but the lengths can be customized. Exact spacing information required for the modules when ordering custom blanks. Specifications subject to change without notice. See spec sheet or jescolighting.com for more details.

FORM + FUNCTION

- Build your perfect display fixture combining multiple module types
- Select channel type, U or V profile, up to 72" in length
- Specify 6" modules with single or double LED heads that are either fixed or aimable
- Can be repositioned by sliding inside channel after mounting
- Narrow focused beam angle
- Blanks available for covering wireway
- Modules come with snap-in quick-connects for easy substitution and repositioning

APPLICATIONS

- Showcase Lighting
- Exhibit Lighting
- Retail Displays



SDLC-U
Flat Linear Channel



SDLC-V
45° Corner Linear Channel



SDLLCV-1A
1 Light Aimable Module



SDLLCV-2A
2 Light Aimable Module



SDLLCV-1F
1 Light Fixed Module



SDLLCV-2F
2 Light Fixed Module

ACCESSORIES



SDL-CC2
2" Interconnector



SDL-PC
SDL Power Supply Lead

COMPONENTS Pages 52-60

POWER SUPPLIES



ACCESSORIES



CONTROLS



BATTERY



SDLLCV-BF
6" Blank Flat Module



SDLC-U-EC
Flat Linear Channel
End Cap





SDLC-V-EC
45° Corner Linear
Channel End Cap

CARBON FIBER FINISH

JESCO is proud to introduce our newest material - Carbon Fiber in Black, Gold, Silver, Blue and Red. Our machined aluminum fixtures are wrapped in true carbon fiber to add style and pizzazz to any display. The endcaps and joiners can be specified in Polished Aluminum, Chrome, Black and Gold finishes.

Most of our fixtures are customizable in terms of finish and dimensions. Finishes can also be matched to your requirements based on samples you provide.

Contact us for any finish or option you would like to incorporate into your project.




CK - "Black" Carbon Fiber




CG - "Gold" Carbon Fiber



CV - "Silver" Carbon Fiber



CL - "Blue" Carbon Fiber



CD - "Red" Carbon Fiber



PS - Polished Aluminum



CH - Chrome



BK - Black




GD - Gold



CC - Custom





FORM + FUNCTION

- The ARC201 is a high-output LED fixture designed for trade show and retail lighting
- Provided with both a Slotted Wall Bracket and a Clamp
- Two wattage options for two light output levels
- Features an aimable head allowing the optimum positioning of the light

APPLICATIONS

- Showcase Lighting
- Exhibit Lighting
- Display Window Lighting
- Retail Displays
- Tradeshow Booths

ARC201CV-4W

4W HIGH OUTPUT AIMABLE EXHIBIT

LED	12V DC	3.80W	434 Lm	114 Lm/W	90 CRI	DIM	90°	DRY	UL LISTED
-----	--------	-------	--------	----------	--------	-----	-----	-----	-----------

Dims: 1 15/16" Ø x 24" L x 2" H

Mounting: Slotted Wall Bracket & Clamp included

ARC201CV-8W

8W HIGH OUTPUT AIMABLE EXHIBIT

LED	12V DC	7.85W	800 Lm	102 Lm/W	90 CRI	DIM	90°	DRY	UL LISTED
-----	--------	-------	--------	----------	--------	-----	-----	-----	-----------

Dims: 1 15/16" Ø x 24" L x 2 1/2" H

Mounting: Slotted Wall Bracket & Clamp included



ARC201-4W



ARC201-8W



Slotted Wall Bracket Mounting included with fixture



Clamp Mounting included with fixture

TO ORDER

MODEL	WATT	BEAM	CCT/CRI	FINISH
ARC201CV	-	-	-	-
	4W - 3.8W	20D - 20°	2790 - 2700K 90CRI	PS - Polished Aluminum
	8W - 7.85W	30D - 30°	3090 - 3000K 90CRI	SV - Silver*
		45D - 45°	3590 - 3500K 90CRI	BK - Black*
			4090 - 4000K 90CRI	
			5090 - 5000K 90CRI	

* Custom option. Contact factory for availability.

Lumen data based on 4000K

Specifications subject to change without notice. See spec sheet or jescolighting.com for more details.


COMPONENTS Pages 52-62

POWER SUPPLIES	12V PP, 12V HW, 12V JB
ACCESSORIES	LED
CONTROLS	DIM
BATTERY	BAT

RECESSED/SURFACE MOUNT



RECESSED/SURFACE MOUNT FEATURE MATRIX

	 PK820 page 26	 PK811 page 27	 PK900 Series page 28	 SD100 Series page 29	 RZ-SM Series page 30	 RH Series page 31
Input	12V DC	12V DC	24V DC	350mA	24V DC	12V DC
Depth	1 5/8" / 2"	1 1/2" / 2 3/16"	3/4"	1/2" to 1 1/4"	5/16"	various
Width	2 3/4" Ø	3" Ø	3 1/4" Ø	1 1/16" Ø	3"	2 3/4" to 4"
Watts per fixture	4.0 / 8.0	3.80 / 7.85	2.7 / 4.5	1.2	2.0	35 / 50
Lm	408 / 800	434 / 800	310 / 450	120	210	see lamp specs
Lm/Watts	102 / 100	114/102	115 / 100	100	105	see lamp specs
Beam Angle	Adjustable 8° to 60°	20°, 30°, 45°	38°	25°, 35°, 45°	110°	see lamp specs
CCT	2700K 3000K 3500K 4000K 5000K	2700K 3000K 3500K 4000K 5000K	3000K 97CRI 4000K 80CRI 3000K 80CRI* 5000K 80CRI*	3000K 4000K 5000K	2700K* 3000K 4000K	see lamp specs
Adjustable After Mounting	•	•	•	•		•
Surface Mountable			•		•	
Customizable (Dimensions, Finish)	•	•		•		

* Custom options. Consult factory



RADIANZ SLIM DISKS PK820



Focusable beam spread
from 8° to 60°



Shown 4W, Silver



Shown 8W, Black

FORM + FUNCTION

- The PK820 Series Focusing LED Slim Disk is the perfect Single Point Source lighting for showcase and display applications, designed with the lighting consultant in mind
- Hand-adjustable, focusable beam spread, from 8° to 60°, for precise highlighting of merchandise on display
- Produces up to 800 lumens and has the ability to light objects from the top of a 8' display all the way to the floor
- The low profile ultra high-output COB LED fixture with two wattage options allow for two levels of light output
- Fixture may be ordered in custom finishes - contact factory

APPLICATIONS

- Retail Lighting
- Exhibit Lighting
- Under Cabinet Lighting
- Lighting for Shelves
- Showcase Lighting
- Cabinet Lighting
- Ceiling Display to Floor Coverage

PK820CV-4W

COB LED SLIM DISK
8° TO 60° FOCUSING BEAM ANGLE - 4W

LED	12V DC	4.0W	408 Lm	102 Lm/W	90+ CRI
DIM	20°	DRY	UL LISTED		

Beam: Variable Zoom 8° to 60°

Dims: 2 3/4" Ø

Mounting Depth: 1 5/8"

PK820CV-8W

COB LED SLIM DISK
8° TO 60° FOCUSING BEAM ANGLE - 8W

LED	12V DC	8.0W	800 Lm	100 Lm/W	90+ CRI
DIM	20°	DRY	UL LISTED		

Beam: Variable Zoom 8° to 60°

Dims: 2 3/4" Ø

Mounting Depth: 2"

TO ORDER

MODEL	WATTS	CCT	FINISH*
PK820CV	4W - 4.0W 8W - 8.0W	2790 - 2700K 90CRI 3090 - 3000K 90CRI 3590 - 3500K 90CRI 4090 - 4000K 90CRI 5090 - 5000K 90CRI	SV - Silver BK - Black* PS - Polished Silver* CC - Custom Finish*

COMPONENTS Pages 52-62

POWER SUPPLIES	12V PP 12V HW 12V JB
ACCESSORIES	12V PP
CONTROLS	DIM
BATTERY	BAT

* Customizable finishes and color temperatures - consult factory for availability.
Lumen data based on 4000K
Specifications subject to change without notice. See spec sheet or jescolighting.com for more details.



Retail window display



FORM + FUNCTION

- The low profile ultra high-output COB LED fixture provides a 20° adjustment for precise highlighting of merchandise on display
- The 8W PK811 version produces an impressive 800 lumens, has the ability to light objects from the top of a 8' display all the way to the floor
- The standard 4W PK811 fixture produces up to 434 lumen
- Fixture may be ordered in custom finishes - contact factory

APPLICATIONS

- Retail Lighting
- Exhibit Lighting
- Under Cabinet Lighting
- Shelf Lighting
- Showcase Lighting
- Cabinet Lighting
- Ceiling Display to Floor Coverage

PK811CV-4W

ADJUSTABLE COB LED SLIM DISK - 4W

LED	12V DC	3.8W	434 Lm	114 Lm/W	90+ CRI
DIM	20°	DRY	UL LISTED		

Dims: 3" Ø × 1 1/16" H
Trim: 1/8" H

PK811CV-8W

ADJUSTABLE COB LED SLIM DISK - 8W

LED	12V DC	7.85W	800 Lm	102 Lm/W	90+ CRI
DIM	20°	DRY	UL LISTED		

Dims: 3" Ø × 2" H
Trim: 1/8" H

COMPONENTS Pages 52-62

POWER SUPPLIES	12V PP 12V HW 12V JB
ACCESSORIES	12V PP
CONTROLS	DIM
BATTERY	BAT

TO ORDER

MODEL	WATTS	BEAM	CCT	FINISH*
PK811CV	-	-	-	-
	4W - 3.80W 8W - 7.85W	20D - 20° 30D - 30° 45D - 45°	2790 - 2700K 90CRI 3090 - 3000K 90CRI 3590 - 3500K 90CRI 4090 - 4000K 90CRI 5090 - 5000K 90CRI	SV - Silver BK - Black*

* Customizable finishes - consult factory for availability.

Lumen data based on 4000K

Specifications subject to change without notice. See spec sheet or jescolighting.com for more details.

RECESSED/SURFACE MOUNT • RADIANTZ PK900



PK921LED
Shown with PK H900A Housing
for Surface Mounting



PK923LED
Shown with Clips for
Recessed Mounting



Shown Recessed Mounted



Shown Recessed Mounted

FORM + FUNCTION

- The PK900 LED Slim Disk Series is designed for showcase and display lighting applications
- Available in Fixed and Adjustable versions, the high-output COB Single Point Source LED fixtures may be Recessed or Surface mounted. PK-H900A Surface Mounting aluminum housing sold separately.
- The 3000K CCT option is standard with a 97CRI

APPLICATIONS

- Retail Lighting
- Exhibit Lighting
- Under Cabinet Lighting
- Showcase Lighting
- Cabinet Lighting
- Shelf Lighting

PK921

ADJUSTABLE COB LED SLIM DISK
FOR RECESSED AND SURFACE MOUNT

LED	24V DC	38°	20°	DRY	UL LISTED
2.7W	310Lm	115 Lm/W	80/97 CRI		
4.5W	450Lm	100 Lm/W	80/97 CRI		

Dims: 3 1/4" Ø x 3/4" H
Trim: 1/16" H

PK923

FIXED COB LED SLIM DISK
FOR RECESSED AND SURFACE MOUNT

LED	24V DC	38°	DRY	UL LISTED	
2.7W	310Lm	115 Lm/W	80/97 CRI		
4.5W	450Lm	100 Lm/W	80/97 CRI		

Dims: 3 1/4" Ø x 3/4" H
Trim: 1/16" H

PK900 SERIES HOUSING



Surface Mount
Aluminum Housing
PKH900A
Dims: 3 1/4" Ø x 7/8" H
Compatible: PK921, PK923
Finish: SV

TO ORDER

MODEL	WATTS	BEAM	CCT	FINISH
PK921 LED - Adj. PK923 LED - Fixed	2 - 2.7W 4 - 4.5W	38 - 38°	309 - 3000K 97CRI 408 - 4000K 80CRI 308 - 3000K 80CRI* 508 - 5000K 80CRI*	SV - Silver BK - Black* WH - White*

* Custom Option - consult factory
Lumen data based on 4000K
Specifications subject to change without notice. See spec sheet or jescolighting.com for more details.

COMPONENTS Pages 52-62

POWER SUPPLIES	24V PP 24V HW 24V JB
ACCESSORIES	LED
CONTROLS	Consult factory
BATTERY	BAT

FORM + FUNCTION

- Measuring just 1 1/16" in diameter, the miniature LED Radianz Micro Spot Series provides high impact accent lighting for showcase applications
- The SD110 Snoot and SD120 shallow Snoot are ideal for glare elimination; the SD111 is an Adjustable Eyeball; the SD112 is an Adjustable Regressed Eyeball – all constructed of cast aluminum in an anodized silver finish
- High output and efficient LEDs
- Custom finishes available
- Multiple units, each merely 1.2W, may be wired to a single driver with the use of a Distribution Block
- Positive lock on all connectors
- Mixed use of color temperatures increase visual clarity, interest and drama of the objects on display



SD111CC
RADIANZ MICRO EYEBALL

LED	350 mA	1.2W	120 Lm	100 Lm/W	90 CRI
DIM	30°	DRY	UL LISTED		

Dims: 1 1/16" Ø × 5/16" Ext
Mounting Depth: 13/16" D



SD112CC
RADIANZ REGRESSED MICRO EYEBALL

LED	350 mA	1.2W	120 Lm	100 Lm/W	90 CRI
DIM	30°	DRY	UL LISTED		

Dims: 1 1/16" Ø
Mounting Depth: 1" D

APPLICATIONS

- Retail Lighting
- Exhibit Lighting
- Under Cabinet Lighting
- Showcase Lighting
- Cabinet Lighting
- Shelf Lighting



SD110CC
RADIANZ MICRO SNOOT

LED	350 mA	1.2W	120 Lm	100 Lm/W	90 CRI
DIM	30°	25°	DRY	UL LISTED	

Dims: 1 1/16" Ø × 5/8" Ext
Mounting Depth: 13/16" D



SD120CC
RADIANZ MICRO SNOOT
FOR SHALLOW APPLICATIONS

LED	350 mA	1.2W	120 Lm	100 Lm/W	90 CRI
DIM	30°	25°	DRY	UL LISTED	

Dims: 1 1/16" Ø × 5/8" Ext
Mounting Depth: 1/2" D

TO ORDER

COMPONENTS Pages 52-62

POWER SUPPLIES	CC PP CC HW
ACCESSORIES	CC
CONTROLS	Consult factory
BATTERY	BAT

MODEL	WATTS	BEAM	CCT	FINISH**
SD110CC	1W - 1.0W	25D - 25°	3090 - 3000K 90CRI	SV - Silver
SD111CC		35D - 35° ¹	4090 - 4000K 90CRI	BK - Black*
SD112CC		45D - 45° ¹	5090 - 5000K 90CRI	BR - Brass*
SD120CC*				BZ - Bronze*
				PS - Polished Silver*
				WH - White*

* Custom options. Consult factory for availability and pricing.

** Customizable finishes - consult factory for availability.

¹ Custom options. Available only with SD111 and SD112 - consult factory.

Lumen data based on 4000K

Specifications subject to change without notice. See spec sheet or jescolighting.com for more details.

RECESSED/SURFACE MOUNT • RADIANT RZ-SM



FORM + FUNCTION

- Radianz Surface Mount modules are high lumen output fixtures with an ultra-shallow depth, measuring only 5/16"
- Offered in Round and Square in three color temperatures and provided with interchangeable bezel finishes of white, silver and bronze
- The 3000K Radianz Surface Mounts are available in a DIY 3-Module Kit that includes a Power Supply and a Distribution Block. Also available is a 3-Module Extension Kit for longer installations.
- Can be mounted in an face up position for dramatic uplighting through glass art objects and bottles
- Complementing Radianz Track fixture is available for design continuity - see page 42

RZ-SM-SQ

SURFACE MOUNT - SQUARE MODULE

LED	24V DC	2.0W†	210† Lm	105 Lm/W	80+ CRI
110°	DRY	UL LISTED			

Dims: 3" L x 3" W x 5/16" D

Finish: Interchangeable White, Silver or Bronze Bezels provided

RZ-SM-RD

SURFACE MOUNT - ROUND MODULE

LED	24V DC	2.0W†	210† Lm	105 Lm/W	80+ CRI
110°	DRY	UL LISTED			

Dims: 3" Ø x 1/4" D

Finish: Interchangeable White, Silver or Bronze Bezels provided

TO ORDER

MODEL

CCT

	-	
--	---	--

RZ-SM-RD
RZ-SM-SQ

30 - 3000K
40 - 4000K
27 - 2700K*

* Consult Factory
† Per Module

Note: Power supply selection is based on wattage of total system (2W/module)
Lumen data based on 3000K
Specifications subject to change without notice.
See spec sheet or jescolighting.com for more details.

ACCESSORIES



RZ-SM-DB4
4-Port Distribution Block for Radianz Surface Mounts

RZ-SM-DB12
12-Port Distribution Block for Radianz Surface Mounts
Finish: White

POWER SUPPLY



RZ-SM-PS-24/24SW
Plug-In Power Supply with On/Off Switch and 4-Port Distribution Block
Output: 24W/24V
Finish: White


COMPONENTS Pages 52

BATTERY

BAT

3-LIGHT RADIANT SURFACE MOUNT KITS

KIT-RZ-SM-SQ3	Set of 3 Square Surface Mount LED Modules with interchangeable bezels. Includes Power Supply with On/Off switch, and 4-port Distribution block. CCT - 3000K
KIT-RZ-SM-RD3	Set of 3 Round Surface Mount LED Modules with interchangeable bezels. Includes Power Supply with On/Off switch, and 4-port Distribution block. CCT - 3000K
KIT-RZ-EXT-SM-SQ3	Extension Kit of 3 Square Surface Mount LED Modules with interchangeable bezels. Includes 4-port distribution block. CCT - 3000K
KIT-RZ-EXT-SM-RD3	Extension Kit of 3 Round Surface Mount LED Modules with interchangeable bezels. Includes 4-port distribution block. CCT - 3000K



Companion RADIANT track found on p. 42

FORM + FUNCTION

- The Mini Recessed Series is perfect for clients seeking a true halogen solution
- Adjustable Mini Recessed Trims mount easily with tension clips
- Low Voltage fixtures require a Class II Electronic Transformer
- Not suitable for drywall installations



RH42

ADJUSTABLE GIMBAL



Lamp: MR16G
 Dims: 3 3/4" Ø
 Cut-Out: 3 3/8" Ø
 Housing: RH27



RH49

ADJUSTABLE MINI GIMBAL



Lamp: MR11
 Dims: 2 3/4" Ø
 Cut-Out: 2 1/2" Ø
 Housing: not available



RH46

ADJUSTABLE SQUARE TELESCOPE



Lamp: MR16G
 Dims: 4" L x 4" W x 1 1/4" Ext
 Cut-Out: 3 1/2" L x 3 1/2" W
 Housing: RH29



RH30

ADJUSTABLE MINI GIMBAL



Lamp: MR16G
 Dims: 3 1/2" Ø x 3/4" Ext
 Cut-Out: 2 7/8" Ø
 Housing: RH25

LED MR16 RETROFIT LAMPS



LL-MR16-6W-38-2780
LL-MR16-6W-38-3080
LL-MR16-6W-38-4080
LED 12V GU5.3 MR16 LAMP
 LED: COB LED
 Input: 12V AC/DC
 Watt: 6W (40W equivalent)
 Base: GU5.3
 Beam: 35°
 CCT: 2700K, 3000K, 4000K
 Lumen: 450 Lm @3000K
 Dimming: ELV



LL-MR16-7HW-40-2780
LL-MR16-7HW-40-3080
LL-MR16-7HW-40-4080
LED 12V GU5.3 MR16 LAMP
 Input: 12V AC/DC
 Watt: 7.5W (50W equivalent)
 Base: GU5.3
 Beam: 35°
 CCT/CRI: 2700K, 3000K, 4000K
 Lumen: 650 Lm @3000K
 Dimming: ELV

OPTIONAL HOUSINGS



RH25
Self Flanged 1/4" Housing
 Dims: 2 3/4" Ø x 4" H
 Compatible Trims: RH30
 Finish: Black



RH27
Self Flanged 1/4" Housing
 Dims: 3 7/8" Ø x 4 1/8" H
 Compatible Trims: RH42
 Flange Trim Ring available: RH27TF
 Finish: Black



RH29
Self Flanged 1/4" Housing
 Dims: 3 3/4" L x 3 3/4" W x 4 1/8" H
 Compatible Trims: RH46
 Finish: Black

TO ORDER

MODEL	FINISH
<input type="text"/>	<input type="text"/>
RH42	ST - Satin Chrome
RH46	WH - White
RH49	
RH30	CH - Chrome
	PB - Polished Brass
	ST - Satin Chrome
	WH - White









Specifications subject to change without notice.
 See spec sheet or jescolighting.com for more details.

COMPONENTS Page 58

POWER SUPPLIES



For more information see our LED Lamps brochure or JESCOLIGHTING.COM

								
	CBF page 9, 34	S602P page 35	S601P page 37	S601 page 37	S650 page 38	S902 page 39	DL-RS page 41	RZ-TR page 43
Lamp Source	LED	LED	LED	LED	LED	LED	LED	LED
Low Voltage 24V	•	•	•	•	•	•	•	•
Line Voltage 120V								
Max Run	20/14 ft	20 ft	20 ft	20 ft	17 ft	20 ft	24 ft	22W
Height	1 ⁷ / ₃₂ " ¹ / 5 ¹ / ₁₆ "	0.49"	3 ⁸ / ₁₆ "	3 ⁸ / ₁₆ "	5 ⁸ / ₁₆ "	5 ⁸ / ₁₆ "	5 ⁸ / ₁₆ "	3 ⁴ / ₁₆ "
Width	1 ¹ / ₁₆ "	0.48"	1 ³ / ₃₂ "	1 ³ / ₃₂ "	1"	1 ³ / ₁₆ "	5 ⁸ / ₁₆ "	2 3 ⁸ / ₁₆ "
Length (inches)	12, 24, 36, 48, 60, 72, 84 ¹ , 96 ¹	8, 12, 24, 36, 48	8, 12, 24, 36, 48	8, 12, 24, 36, 48	17, 34	8, 12, 24, 36, 48	12, 24, 36, 48	12, 18, 24
Wet Location							•	
Watts/Ft, Max	6.0/4.0 ²	4.97	3.6	2.9	2.47	6.3	3.2	2**
Lm/Ft @4000K	536 /332	266.1	167.9	246	265	438	325	210**
Lm/Watts, Max	89 /83	53.5	46.6	84	108	70	102	105**
Beam Angle	120° / 60°	130°	130°	90°	asymmetrical	120°	120°	110°
CCT	2700K 3000K 3500K 4000K 6000K	3000K 4000K	3000K 4000K 6000K	3000K 4000K 6000K	4000K* 5000K	2700K* 3000K 4000K 5000K* 6000K	2700K 3000K 4000K 6000K RGB Blue Green Red Yellow	2700K* 3000K 4000K
RGB Color Changing							•	
Dimmable - Triac	•	•	•	•	•	•	•	on board
Dimmable - 0-10V	•	•	•	•	•	•	•	
On-Board Switch Available		•	•	•				•
Adjustability After Mounting	•	•	•	•		•	•	•
Smart Track System Compatible	•	•	•	•	•			
Direct End-to-End Connectable		•	•	•		•		•
IC Chip Controlled	•*			•		•		
Finishes	Aluminum	Aluminum	Aluminum	Aluminum	White	Aluminum	Aluminum	Silver White

• = Adjustable with Mounting Hardware











* Consult factory

** Per Module

¹ With FR60 lens only

² With CL lens

[†] Customizable in 1" increments up to 72"

									
SG-LED page 45	SGA-LED page 45	SG4 page 46	SG4A page 47	SG5 page 46	SG5A page 47	SG5HO page 46	SG5HO page 47	SG5AT page 48	SG5ATHO page 48
LED	LED	Fluorescent	Fluorescent	Fluorescent	Fluorescent	Fluorescent	Fluorescent	Fluorescent	Fluorescent
•	•	•	•	•	•	•	•	•	•
80 ft	80 ft	360W	360W	360W	360W	360W	360W	360W	360W
1 3/8"	1 5/8"	1 1/4"	1 5/8"	1 1/2"	1 5/8"	1 3/4"	1 7/8"	2 7/8"	2 7/8"
3/4"	3/4"	3/4"	7/8"	3/4"	7/8"	7/8"	7/8"	7/8"	7/8"
12, 24, 36, 48	12, 24, 36, 48	10, 14, 18, 20, 22, 30, 35, 41, 47	10, 14, 18, 20, 22, 30, 35, 41, 47	10, 13, 23, 35, 47, 58	10, 13, 23, 35, 47, 58	23, 35, 47	23, 35, 47	23, 35, 47, 59	23, 35, 47
4.5	4.5	12	12	8	8	12	12	14	26
475	475	800	800	600	600	1100	1100	1400	2300
106	106	67	67	75	75	92	92	100	88
130°	130°	180°	180°	180°	180°	180°	180°	180°	180°
3000K 4000K 6000K	3000K 4000K 6000K	3000K 4100K 6400K Blue Green Red	3000K 4100K 6400K Blue Green Red	3000K 3500K 4100K 5000K 6400K Blue Green Red Black	3000K 3500K 4100K 5000K 6400K Blue Green Red Black	3000K 3500K 4100K 5000K 6400K Blue Green Red	3000K 3500K 4100K 5000K 6400K Blue Green Red	3000K 3500K 4100K 5000K 6400K Blue Green Red	3000K 3500K 4100K 5000K 6400K Blue Green Red
•	•	•	•	•	•	•	•	•	•
•	•	•	•	•	•	•	•	•	•
•	•	•	•	•	•	•	•	•	•
White	White	White	Silver White	White	Silver White	White	Silver White	Silver White	Silver White

CBF BESPOKE SLIM LED



FORM + FUNCTION

- Custom Lighting Without the Custom Cost
- A bespoke, high output, low profile LED fixture that allows for complete customization to meet any design need
- Bespoke features 72 LEDs per foot, providing a uniform appearance with no hot spots
- Choice of a straight lens in clear, frosted or opal finish or a rounded 60° beam focusing lens
- Choice of standard lengths - 12", 24", 36", 48", 60" or 72" - or custom lengths up to 8 feet†. Custom cut lengths in precise 1" increments.
- Choice of input and output, plug and play or hardwire connections in standard lengths of 18", 36", 48" or 96" or a custom length in between
- Quickly made to order and shipped ready for installation - saving time and money as well as eliminating on-site assembly

APPLICATIONS

- Showcase Lighting
- Exhibit Lighting
- Retail Displays
- Under Cabinet & Soffit Lighting
- Shelf Lighting
- Cove Lighting
- Toe Kick Lighting
- Backlighting
- Showcase Lighting
- Picture Window Lighting

CBF

COMMERCIAL BESPOKE SLIM 6W LED FIXTURE

LED	24V DC	6.0 W/Ft	536 Lm/Ft	89 Lm/W	80+ CRI
14' MAX	DIM	DRY	UL LISTED		

Dims: 1 1/8" W x 5/16" H (CL, OP & FR)
1 1/8" W x 17/32" H (FR60)

Beam Angle: 120° (CL, OP & FR)
60° (FR60)

CBF - LOW WATT

COMMERCIAL BESPOKE SLIM 4W LED FIXTURE

LED	24V DC	4.0 W/Ft	332 Lm/Ft	83 Lm/W	80+ CRI
20' MAX	DIM	DRY	UL LISTED		

Dims: 1 1/8" W x 5/16" H (CL, OP & FR)
1 1/8" W x 17/32" H (FR60)

Beam Angle: 120° (CL, OP & FR)
60° (FR60)

ACCESSORIES



CH-SM-31-CLIP
Clear Mounting Clip
Recommended: 1 every 2'



CH-SM-31-CLIP-A
Adjustable Mounting Clip
Recommended: 1 every 2'

COMPONENTS Pages 50-62

POWER SUPPLIES	24V PP	24V HW	24V JB
CONTROLS	DIM		
BATTERY	BAT		

TO ORDER

MODEL	CHANNEL	LENS	LENGTH**	LED TYPE	CCT	INPUT	OUTPUT
CBF	SM31						
		CL - Clear	12 - 12 1/4"	HD72 - 6.0W	27 - 2700K	Plug & Play:	Plug & Play:
		OP - Opal Matte	24 - 24 1/4"	HD724 - 4.0W	30 - 3000K	I18 - 18"	DEC - Dead End
		FR - Frosted	36 - 36 1/4"		35 - 3500K	I36 - 36"	O18 - 18"
		FR60 - 60° Frosted	48 - 48 1/4"		40 - 4000K	I48 - 48"	O36 - 36"
			60 - 60 1/4"		60 - 6000K	I96 - 96"	O48 - 48"
			72 - 71 1/4"			Hardwire:	Hardwire:
			84 - 84 1/4"†			IHW18 - 18"	DEC - Dead End
			96 - 95 1/4"†			IHW36 - 36"	OHW18 - 18"
			xx - Custom			IHW48 - 48"	OHW36 - 36"
			96" Max*			IHW96 - 96"	OHW48 - 48"

Lumen data based on 4000K, with Clear Lens Cover.

* Custom lengths are available up to 8ft. in increments of 1".

** For overall length: Add 1/4" if requiring both input and output cables. See spec sheet.

† Only available with FR60 lens. (Other lenses only available in 6' length.)

Please note we can mix and match a CBF fixture with any of our DL-FLEX LED strips and any of our channels. Contact factory for all your options.

Specifications subject to change without notice. See spec sheet or jescocolighting.com for more details.



Shown at actual size.

S602P ACCESSORIES



S601-PC

18" Plug and Play Power Connector - Black

S601-PCWH

18" Plug and Play Power Connector - White



S601-PC-HW

12" Hard Wire Power Connector - Black



S601-CC3

S601-CC6

S601-CC12

S601-CC15 - available in White only

S601-CC24

S601-CC48

Connecting Cable

Length: 3", 6", 12", 15", 24", 48"

Finish: BK - Black, WH - White



S601-SW

Switch Box with On/Off switch

Dims: 1 5/8" L x 1 1/4" W x 1" H



S601-FLEX-CON

0 - 180° Flexible Connector



S601-L-CONN

90° Left Connector

S601-R-CONN

90° Right Connector



S602-EC

End Cap

(1) Included with each fixture



S602-MC

Mounting Clip

(2) Included with each fixture



ACC-MT-MAG-02

3/8" Magnet

May be applied to S601-MC or S601 fixture

Recommended 1 magnet per foot

COMPONENTS Pages 50-62

POWER SUPPLIES

24V
PP

24V
HW

24V
JB

CONTROLS

DIM

BATTERY

BAT



S602P shown
with cover open

FORM + FUNCTION

- The new S602P features 84 LEDs/foot that provide for even illumination and no visual hot spots
- Ultra-slim low-profile design provides a lighting solution to a variety of applications
- Extruded aluminum housing and lens assures even light output while protecting LEDs
- Units are inter-connectable end-to-end and may be linked using connecting cables
- Customizable lengths in 1" (nominal) increments. Consult factory
- Smart Track compatible

APPLICATIONS

- Cove and Soffit Lighting
- Path and Contour Marking
- Display Lighting
- Under-shelf and Under-cabinet Lighting
- Accent and Edge Lighting
- Backlighting
- Signage

S602P

LINKABLE SLIM STIX

LED	24V DC	4.97 W/Ft	266 Lm/Ft [†]	53.5 Lm/W [†]	90+ CRI	84 LED/Ft
16' MAX	DIM	130°	DRY	UL LISTED		

Dims: 1 5/32" W x 1/2" H

Includes: (1) S602-EC, (2) S602-MC

[†]Product Lumen data based on 4000K color temperature.
Contact factory for higher Lumen/Wattage output options.

TO ORDER

MODEL	LENGTH	CCT
S602P	- [] / []	
	08 - 7"	30 - 3000K 90CRI
	12 - 10 7/8"	40 - 4000K 90CRI
	24 - 23 3/8"	
	36 - 35 1/4"	
	48 - 46 3/4"	

Custom sizes are available for larger projects. Consult factory.
Specifications subject to change without notice.
See spec sheet or jescolighting.com for more details.




Shelves: S601P
Hartmann Flagship Store
New York, NY
Millwork: Daniel DeMarco & Associates

FORM + FUNCTION


- A miniature linear light fixture designed for narrow spaces and easily concealed
- The S601P measures a mere 3/8" in height and employs high 90+ CRI LEDs
- S601P features 84 LEDs per foot, providing even illumination and no visual hot spots
- The S601 Series has a 90° beam angle and provides a focused light beam
- Multiple units may be direct linked for continuous light output with no dark spots
- Flexible Connector joins two lengths of fixtures at variable angles of 0° - 180°
- Connecting Cables ranging from 3" to 48" available for every type of installation
- Smart Track compatible
- Single and Twin Channel may be mounted directly or at a 45° angle, allows maximum light output
- Included with the fixture are two S601-MC mounting clips that allow a 30° rotation
- Super lightweight fixture that also installs easily with magnets or Velcro in any direction - horizontally or vertically
- S601-SW Switch Box connects directly to the fixture and enables on/off control at the source

APPLICATIONS

- Retail Displays
- Shelf Lighting
- Under Cabinet & Soffit Lighting
- Exhibit Lighting
- Showcase Lighting
- Toe Kick Lighting
- Backlighting



Multiple units can be connected directly together forming a continuous, unbroken line



S601P works with the ST Smart Track Power System. See p. 51 for detail



Shown at actual size.

S601 ACCESSORIES



S601-PC
18" Plug and Play Power Connector - Black

S601-PCWH
18" Plug and Play Power Connector - White



S601-PC-HW
12" Hard Wire Power Connector - Black



S601-CC3
S601-CC6
S601-CC12
S601-CC15 - available in White only
S601-CC24
S601-CC48
Connecting Cable
Length: 3", 6", 12", 15", 24", 48"
Finish: BK - Black, WH - White



S601-SW
Switch Box with On/Off switch
Dims: 1 3/8" L x 1 1/4" W x 1" H



S601-FLEX-CON
0 - 180° Flexible Connector



S601-L-CONN
90° Left Connector

S601-R-CONN
90° Right Connector



S601-EC
End Cap
(1) Included with each fixture



S601-MC
Mounting Clip
Allows 30° rotation
(2) Included with each fixture



ACC-MT-MAG-02
3/4" Magnet
May be applied to S601-MC or S601 fixture
Recommended 1 magnet per foot



S601-CH6
6' Single Channel
Field cuttable
May be mounted at a 0° or 45° angle



S601-CH6T
6' Twin Channel
For side by side parallel installations
Field cuttable
May be mounted at a 0° or 45° angle

COMPONENTS Pages 50-62

POWER SUPPLIES



CONTROLS



BATTERY



S601P shown
with cover open

S601P

LINKABLE SLIM STIX

LED	24V DC	3.6 W/Ft	168 Lm/Ft†	46.6 Lm/W†	90+ CRI	84 LED/Ft
20' MAX	DIM	130°	DRY	UL LISTED		

Dims: 13/32" W x 3/8" H

Includes: (1) S601-EC, (2) S601-MC

TO ORDER

MODEL	LENGTH	CCT
S601P	- [] / []	[]
	08 - 8"	30 - 3000K
	12 - 11 1/2"	40 - 4000K
	24 - 23"	
	36 - 34 3/8"	
	48 - 45 7/8"	

S601

LINKABLE SLIM STIX

LED	24V DC	2.9 W/Ft	246 Lm/Ft†	84 Lm/W†	84 CRI	18 LED/Ft
20' MAX	DIM	90°	DRY	UL LISTED	ETL US	

Dims: 13/32" W x 3/8" H

Includes: (1) S601-EC, (2) S601-MC

†Product Lumen data based on 4000K color temperature.
Contact factory for higher Lumen/Wattage output options.


TO ORDER

MODEL	LENGTH	CCT
S601	- [] / []	[]
	08 - 8"	30 - 3000K
	12 - 11 1/2"	40 - 4000K
	24 - 23"	60 - 6000K
	36 - 34 3/8"	
	48 - 45 7/8"	

Custom sizes are available for larger projects. Consult factory.
Specifications subject to change without notice.
See spec sheet or jescolighting.com for more details.

RIGID LINEAR • LED S650 SERIES

Shelves: S650



Asymmetric light output provides sharp light cutoff for optimally focused lighting of shelves and displays



S650 works with the ST Smart Track Power System. See p. 51 for details

S650

LED SHELF/UNDER CABINET FIXTURE WITH ASYMMETRICAL BEAM ANGLE

LED	24V DC	80+ CRI	108 [†] Lm/W	DIM	17" MAX	DAMP DRY	UL LISTED
34"	7.0W	750 [†] Lm					
17"*	3.5W	375 [†] Lm					

Dims: 17", 34" L x 1" W x 5/8" H

Mounting: Imbedded Magnets

TO ORDER

MODEL	SIZE & WATTAGE	CCT	FINISH
S650	-	-	-
	3407 - 34", 7.0W	50 - 5000K	WH - White
	1703* - 17", 3.5W	40* - 4000K	

* Consult factory

[†] Product Lumen Output and Lumens/Watts are based on 5000K color temperature. Specifications subject to change without notice. See spec sheet or jescolighting.com for more details.

FORM + FUNCTION

- Low glare optical system provides an efficient and uniform, high-output, asymmetrical light with a sharp cutoff to optimally illuminate products displayed on shelves
- Designed in standard 34" and custom 17" lengths and color temperatures of 4000K and 5000K to meet the needs of retail shelf lighting
- Non-polarized circuit design allows complete flexibility of driver location
- Mounts easily and quickly onto metal shelves with built-in magnetic backing. Optional S650-MC Mounting Clips available for non-magnetic surfaces.
- Once mounted the LED diodes are out of sight as the lamp source is placed at an angle
- Smart Track compatible
- Available in CRI of 90+, consult

APPLICATIONS

- Retail Displays
- Shelf Lighting
- Under Cabinet Lighting
- Showcase Lighting

S650 ACCESSORIES



S650-PC
24" P&P Power Connector
Finish: White



S650-PC-HW
80" Hardwire Power Connector
Finish: White



S650-PC-CC6
S650-PC-CC12
S650-PC-CC24
P&P Connecting Cable
Finish: White
Length: 6", 12", 24"



ST-S650-PC24
24" Smart Track Input Power Connector Cable
Finish: White



S650-MC
Mounting Clip
(optional - for non-metallic surfaces)

Note: fixture mounts with use of imbedded magnets

COMPONENTS Pages 50-62

POWER SUPPLIES	24V PP	24V HW	24V JB
CONTROLS	DIM		
BATTERY	BAT		

FORM + FUNCTION

- High output S902 is available in 8", 12", 24", 36" and 48" nominal lengths in a variety of color temperatures ranging from 2700K to 5000K
- Frosted lens encloses 36 LEDs per foot to perfectly diffuse light and reduce hot spots and glare
- Active temperature compensation circuitry protects the fixture from overheating
- Ease of installation – fixtures can be plug-and-play or hardwired and mount quickly with straight or angled mounting clip sets
- Fixtures easily connect and lock end-to-end or with connecting cables available in 3", 6", 12", 24" and 48"

APPLICATIONS

- Retail Displays
- Shelf Lighting
- Under Cabinet & Soffit Lighting
- Cove Lighting
- Exhibit Lighting
- Showcase Lighting
- Toe Kick Lighting
- Backlighting



Shelves: S902
Track: HV238



Direct
connectivity of
fixtures

S902 ACCESSORIES



S902-PC
Plug and Play Power
Connector
Connects to power supply
S902-PC-HW
Hard-Wire Power Connector
Connects to power supply



S902-CC3
S902-CC6
S902-CC12
S902-CC24
S902-CC48
S902 Connecting Cable
Length: 3", 6", 12", 24", 48"



DL-RS-MC-1
Mounting Clip Kit
(Included with each fixture)
(2) 0° clips, (2) 45° clips

S902

LED SHELF/UNDER CABINET FIXTURE

LED	24V DC	6.3 W/Ft	438† Lm/Ft	70† Lm/W	85 CRI
20' MAX	DIM	120°	DRY	UL LISTED	

Dims: 5/8" H x 13/16" W
Includes: S902-CLIP-1

TO ORDER

MODEL	LENGTH	CCT
S902	-	/
	08 - 7 3/4"	30 - 3000K
	12 - 11 3/4"	40 - 4000K
	24 - 23 7/16"	60 - 6000K
	36 - 35 3/8"	27* - 2700K
	48 - 47 3/16"	50* - 5000K

* Consult Factory
† Product Lumen Output and Lumens/Watts are based on 4000K color temperature.
Specifications subject to change without notice.
See spec sheet or jescolighting.com for more details.

COMPONENTS Pages 50-62

POWER SUPPLIES	24V PP	24V HW	24V JB
CONTROLS	DIM		
BATTERY	BAT		



JESCO LED Back-Lit Mirror BLML 203 30
& DL-RS on top and bottom

FORM + FUNCTION

- Wide variety of color temperatures from warm to cool white, static colors and RGB color changing options
- Optional snap-on Opal Cover reduces pixilation and provides a similar appearance to a neon edge lighting application
- Waterproof Plug-and-Play Connectors located at the side of the fixture with a 2" wire allow connections of runs of up to 24'
- Designed for Indoor/Outdoor dry/damp/wet location use
- Specially keyed RGB fixture connections simplify installation
- Compatible with UL Listed, Outdoor Rated Power Supplies

APPLICATIONS

- Outdoor Illumination
- Exhibit Lighting
- Retail Displays
- Showcase Lighting
- Shelf Lighting
- Under Cabinet & Soffit Lighting
- Cove Lighting
- Toe Kick Lighting
- Backlighting



DL-RS Underlighting of
Outdoor Glass Panels
University of Rhode Island
School of Pharmacy



- Opal Cover
- Cover easily slides onto the fixture
 - Includes two clip-on cover end caps
 - 80-85% light transmittance



- Waterproof
plug and play
connectors



DL-RS ACCESSORIES

	DL-RS-C-12
	DL-RS-C-24
	DL-RS-C-36
	DL-RS-C-48
	DL-RS-C-72
	Length: 12", 24", 36", 48", 72"
	DL-RS-MC-1
	Mounting Clip Kit (included with each fixture) (2) 0° clips, (2) 45° clips
	ACC-MT-MAG-01-SET
	Magnetic Mounting Clip (Set of 2)

DL-RS OUTDOOR ACCESSORIES

	DL-PS-OD-PT-F
	Outdoor DC Output Power Connector
	DL-PS-OD-RGB-PT-F
	RGB Outdoor DC Output Power Connector Length: 8"
	DL-PS-OD-EXT18
	DL-PS-OD-EXT48
	DL-PS-OD-EXT96
	Outdoor DC Power Extension Cable
	DL-PS-OD-RGB-EXT18
	DL-PS-OD-RGB-EXT48
	DL-PS-OD-RGB-EXT96
	RGB Outdoor DC Power Extension Cable Length: 18", 48", 96"
	DL-PS-OD-EC
	End Cap for Outdoor DC Output Power Connector
	DL-PS-OD-RGB-EC
	RGB End Cap for Outdoor DC Output Power Connector Must cap the end of each run for wet & damp applications
	DL-PS-OD-2Y
	Outdoor DC 2-Way Power Splitter
	DL-PS-OD-RGB-2Y
	RGB Outdoor DC 2-Way Power Splitter Length: 13". Length of Split Lead: 6"
	DL-PS-OD-3Y
	Outdoor DC 3-Way Power Splitter
	DL-PS-OD-RGB-3Y
	RGB Outdoor DC 3-Way Power Splitter Length: 13". Length of Split Lead: 6"
	DL-PS-OD-PT-M
	Outdoor DC Bare Wire to Male Input Power Connector
	DL-PS-OD-RGB-PT-M
	RGB Outdoor DC Bare Wire to Male Input Power Connector Length: 8"

COMPONENTS Pages 52-62

POWER SUPPLIES	24V PP 24V HW 24V JB
CONTROLS	DIM RGB DMX
BATTERY	BAT

DL-RS

LED RIGID STRIP

LED	24V DC	3.2 W/Ft†	325 Lm/Ft†	102 Lm/W†	80+ CRI
24' MAX	DIM	120°	UL LISTED		

Dims: 5/8" W x 5/8" H (1 5/16" H with Opal Cover)

Housing: Aluminum extrusion

Environment: Wet*, Damp, Dry

Includes: (1) DL-RS-MC-1, (1) DL-PS-OD-EC

DL-RS-RGB

LED RGB RIGID STRIP

LED	24V DC	3.8 W/Ft†	148 Lm/Ft†	39 Lm/W†	
24' MAX		120°	UL LISTED		

Dims: 5/8" W x 5/8" H (1 5/16" H with Opal Cover)

Housing: Aluminum extrusion

Environment: Wet*, Damp, Dry

Includes: (1) DL-RS-MC-1, (1) DL-PS-OD-RGB-EC

TO ORDER

MODEL	LENGTH	CCT	OPTION
DL-RS	-	-	-
	12 - 12"	27 - 2700K	C - Opal Cover
	24 - 23 7/8"	30 - 3000K	
	36 - 35 5/8"	40 - 4000K	
	48 - 47 1/2"	60 - 6000K	
		R - Red	
		G - Green	
		B - Blue	
		Y - Yellow	

MODEL	LENGTH	CCT	OPTION
DL-RS	-	-	-
	12 - 12"	RGB	C - Opal Cover
	24 - 23 7/8"		
	36 - 35 5/8"		
	48 - 47 1/2"		

* This product cannot be submersed in water.


The outdoor DC end cap is required at the end of each open run for wet and damp applications.

† Product Lumen Output and Lumens/Watts are based on 4000K color temperature. Specifications subject to change without notice. See spec sheet or jescolighting.com for more details.



FORM + FUNCTION

- The Radianz Track is a dimmable slim track system with high output snap-on LED modules that slide along the track for easy repositioning and aiming
- Customize the amount of light desired by adding as many Round or Square LED Modules to the track as needed, up to a max of 11 units per power feed
- Tracks offered in 12", 18" and 24" may be inter-connected with Direct Connectors for a straight line configuration or Connecting Cables to negotiate corners
- System available a-la-carte or in DIY Kits, offered in 12" 2-Light kit or 18" 3-Light kit. Kits include all necessary power supplies and dimmers. For longer runs, a 12" 2-Light Extension Kit that includes a Direct Connector is available
- A complementing Radianz Surface Mount version is available for design continuity - see page 30



APPLICATIONS

- Bookcase, Cabinet Shelves & Under Cabinet Lighting
- Retail & Merchandise Showroom Displays, Case Lighting, Store Counters & Display Shelves
- Integrate into Furniture & Bedroom Headboards and Decorate Trim Lighting for Home, Office and Hotels



Complementing surface-mounted RADIANTZ found on p. 30



Winner of the DIY Network
"New Product World - Fills Consumer Need"
 Award at the 2014 National Hardware Show

RADIANT TRACK COMPONENTS



RZ-T12
RZ-T18
RZ-T24
RADIANT Track
Finish: Silver
Length: 12", 18", 24"



RZ-TR-DMEC
Dimmable End Cap for RADIANT Track
Input: 24V DC
Full range dimmer and on/off switch.
Memorizes last setting.
Offers master/slave control of any connected tracks.



RZ-TR-PFEC
End Cap for RADIANT Track
Input: 24V DC
Required End Cap with power feed for connections
or used in place of RZ-TR-DMEC when dimming/on-off
control is not required



RZ-TR-CONN
Direct Connector for RADIANT Track
Allows for end-to-end connection of two tracks.
Note: Can only be used between two RZ-TR-PFEC
track end caps



RZ-TR-CC06
6" Connecting Cable



RZ-TR-CC12
12" Connecting Cable
For use between two tracks



RZ-TR-SM-CC60
59" Power Connector
Provides connection between RADIANT Track System and
the Radiant Surface Mount power distribution blocks



RZ-TR-PS-24/24
Power Supply for RADIANT Track
Output: 24W/24V

Note: can power up to 11 modules per run

COMPONENTS Pages 52

BATTERY

BAT

RADIANT TRACK MOUNT KITS

KIT-RZ-T12-RD2	2 Round Modules with 12" Radiant Track, Power Supply and Onboard Dimmer. CCT - 3000K. Finish - Silver, White
KIT-RZ-T12-SQ2	2 Square Modules with 12" Radiant Track, Power Supply and Onboard Dimmer. CCT - 3000K. Finish - Silver, White
KIT-RZ-T18-RD3	3 Round Modules with 18" Radiant Track, Power Supply and Onboard Dimmer. CCT - 3000K. Finish - Silver, White
KIT-RZ-T18-SQ3	3 Square Modules with 18" Radiant Track, Power Supply and Onboard Dimmer. CCT - 3000K. Finish - Silver, White
KIT-RZ-EXT-T12-RD2	Round Extension Kit with 12" Radiant Track, 2 Round Modules and Direct Connector. CCT - 3000K. Finish - Silver, White
KIT-RZ-EXT-T12-SQ2	Square Extension Kit with 12" Radiant Track, 2 Square Modules and Direct Connector. CCT - 3000K. Finish - Silver, White



RZ-TR-SQ

LED TRACK MOUNT SQUARE MODULE

LED	24V DC	2.0W†	210† Lm	105 Lm/W	80+ CRI
DIM	110°	DRY	UL LISTED		

Module Dims: 2 1/4" x 2 1/4" x 3/4"



RZ-TR-RD

LED TRACK MOUNT ROUND MODULE

LED	24V DC	2.0W†	210† Lm	105 Lm/W	80+ CRI
DIM	110°	DRY	UL LISTED		

Module Dims: 2 3/8" Ø x 5/8"

TO ORDER RADIANT TRACK

1. Choose Track Length. 2. Choose Input End Cap.
3. Choose Output End Cap. 4. Choose Style and Quantity of Modules

Power Supply, Connectors & Cables sold separately

TO ORDER MODULES

MODEL	CCT	FINISH
RZ-TR-SQ	30 - 3000K	S - Silver
RZ-TR-RD	40 - 4000K	W - White
	27* - 2700K	

* Consult Factory

† Per Module

Lumen data based on 4000K

Note: Power supply selection is based on wattage of total system (2W/module)

Specifications subject to change without notice.

See spec sheet or jescolighting.com for more details.



Shelf & Backlighting: SG-LED

FORM + FUNCTION

- The Line Voltage SG-LED and SGA-LED use the same power cord and inter-connectors and accessories as the Mini Fluorescent Sleek Plus fixtures enabling a quick retrofit or upgrade
- Low profile design with a minimal footprint
- Patented adjustable light-barrel allows light to be aimed 360° where needed
- Opal acrylic diffuser distributes light evenly and eliminates glare
- Multiple fixtures can be connected end-to-end with Direct Connectors or Connecting Cables of various lengths, up to a max run of 80'
- Fixture may be hardwired by using a Hardwire Box (SG-B or SG-BM) or plugged directly into standard wall outlet with a cord and 3 prong plug (sold separately)
- Each fixture provided with (1) Direct Connector (SG-DC), (2) Vertical Mounting Clips (SG-MC-V). The SG-LED is also provided with (2) 45° Angled Mounting Clips (SG-MC-45)

APPLICATIONS

- Under Cabinet & Soffit Lighting
- Underlighting of Counters in Bars, Restaurants, Stores, Hotels, Reception Desks, Hospitals, Offices and Home Workstations
- Retail & Merchandise Showroom Displays, Exhibit Lighting, Case Lighting, Store Counters and Display Shelves
- Lighting for Bookcases, Shelves, Cabinet Shelves & Toe Kicks
- Integrate into Furniture & Bedroom Headboards and Decorate Trim Lighting for Home, Office and Hotels
- Cove Lighting
- Backlighting of Signage or Decorative Tiles and Panels in Stores, Restaurants, Hotels and Offices
- Cabinets/Closets "Close to Clothing" environments



Shown lit

Non-glare opal acrylic diffuser distributes light with the highest efficiency and quality.



Cutout view

All accessories also function with JESCO's SG4 & SG5 fluorescent fixtures for easy retrofitting or interconnecting.



With Switch

May be interconnected end-to-end with Direct Connection (SG-DC) or with various connecting cables (SG-CCx) for a max run of 80 feet.



SG-LED

LED SLEEK ULTRA - FIXED

LED	120V AC	4.5 W/Ft	475 Lm/Ft†	106 Lm/W†	80 CRI
80' MAX	130°	DRY	UL LISTED		

Dims: ¾" W x 1 ⅝" H

Housing: Aluminum

Dimming: No

Includes: (1) SG-DC, (2) SG-MC-V, (2) SG-MC-45

For environments requiring a special listing for Damp locations or for Cabinets/Closets
"Close to Clothing" contact factory

SGA-LED

LED SLEEK ULTRA - ADJUSTABLE

LED	120V AC	4.5 W/Ft	475 Lm/Ft†	106 Lm/W†	80 CRI
80' MAX	130°	360°	DRY	UL LISTED	

Dims: ¾" W x 1 ⅝" H

Housing: Aluminum

Dimming: No

Includes: (1) SG-DC, (2) SG-MC-V

TO ORDER

MODEL	LENGTH	CCT	FINISH	OPTION
<input type="text"/>	- <input type="text"/>	- <input type="text"/>	- <input type="text"/>	- <input type="text"/>
SG-LED	12 - 12 ¾"	30 - 3000K	W - White	SW* - On/Off Switch
SGA-LED	24 - 22 ¾"	40 - 4000K		
	36 - 34 ½"	60 - 6000K		
	48 - 46 ¼"			
	60** - 58"			

* Optional on the SG-LED

** SG-LED only

† Lumen data based on 4000K

Contact factory for higher Lumen/Wattage output options.

Additional power supply cables, connecting cables, hard-wire boxes sold separately.

Specifications subject to change without notice.

See spec sheet or jescolighting.com for more details.

RIGID LINEAR • FLUORESCENT SLEEK PLUS SERIES



Backlighting of Columns

FORM + FUNCTION

- The extensive Sleek Plus Fluorescent Series includes a complete collection of Single- and Twin-, Fixed- and Adjustable- formats with a choice of T4, T5, T5HO lamp options
- Adjustable Single or Twin fixtures have a patented rotating light barrel to direct light where needed
- Extruded aluminum housing provides proper heat control, extending lamp life and light output efficiency
- Silent electronic ballast rated 120V 50/60Hz provides optimal performance
- Non-glare ribbed acrylic diffuser distributes lighting with the highest efficiency and beam control quality
- Multiple units can connect together using Direct Connectors to form a continuous run, or with Connecting Cables available in various lengths

SG4

SLEEK PLUS CLASSIC - T4



Max Run: Fixtures combined up to 350W

Includes: (1) T4 lamp, (1) SG-DC, (2) Mounting Clips

Dimming: No

SG5

SLEEK PLUS CLASSIC - T5




Max Run: Fixtures combined up to 350W

Includes: (1) T5 lamp, (1) SG-DC, (2) Mounting Clips

Dimming: No

SG5HO

SLEEK PLUS CLASSIC - T5HO



Max Run: Fixtures combined up to 350W

Includes: (1) T5HO lamp, (1) SG-DC, (2) Mounting Clips

Dimming: No

ACCESSORIES Page 49

TO ORDER

MODEL	WATTS	SWITCH	CCT	FINISH
<input type="text"/>	- <input type="text"/>	<input type="text"/>	/ <input type="text"/>	- <input type="text"/>
SG4		SW - On/Off		W - White
SG5		Switch		
SG5HO		(Optional)		

Specifications subject to change without notice.
See spec sheet or jescolighting.com for more details.



WATTAGE, DIMENSIONS & LUMEN DATA

Model	Watts	Dims	Lumens*	CCT
SG4	6 6W**	9 3/8" L x 3/4" W x 1 1/4" H	480	30 3000K
	8 8W	13 1/2" L x 3/4" W x 1 1/4" H	600	41 4100K
	12 12W	17 1/2" L x 3/4" W x 1 1/4" H	800	64 6400K
	16 16W	19 1/2" L x 3/4" W x 1 1/4" H	1000	BK Black
	20 20W	21" L x 3/4" W x 1 1/4" H	1350	BU Blue
	22 22W	29" L x 3/4" W x 1 1/4" H	1850	GN Green
	24 24W	34 1/2" L x 3/4" W x 1 1/4" H	2150	RD Red
	26 26W	40 3/8" L x 3/4" W x 1 1/4" H	2550	
	28 28W	46 1/4" L x 3/4" W x 1 1/4" H	2900	
	35 35W	58" L x 3/4" W x 1 1/2" H	3650	
SG5	6 6W**	9 3/8" L x 3/4" W x 1 1/2" H	480	30 3000K
	8 8W**	12 3/8" L x 3/4" W x 1 1/2" H	600	35 3500K
	14 14W	22 3/4" L x 3/4" W x 1 1/2" H	1350	41 4100K
	21 21W	34 1/2" L x 3/4" W x 1 1/2" H	2150	50 5000K
	28 28W	46 1/4" L x 3/4" W x 1 1/2" H	2900	64 6400K
	35 35W	58" L x 3/4" W x 1 1/2" H	3650	BK Black
				BU Blue
SG5HO	24 24W	22 3/8" L x 7/8" W x 1 3/4" H	2200	GN Green
	39 39W	34 3/8" L x 7/8" W x 1 3/4" H	3500	RD Red
	54 54W	46 1/4" L x 7/8" W x 1 3/4" H	5000	

* Based on 4100K lamps.

** Not available with a Rocker Switch.

APPLICATIONS

- Retail Displays, Showcases & Exhibit Lighting
- Shelf Lighting
- Under Cabinet & Soffit Lighting
- Lighting for Toe Kicks & Coves
- Backlighting



Merchandise display lighting



Patented 360° adjustable light barrel

WATTAGE, DIMENSIONS & LUMEN DATA

Model	Watts	Dims	Lumens*	CCT
SG4A	6 6W**	9 1/2" L x 7/8" W x 1 5/8" H	480	30 3000K
	8 8W	13 3/4" L x 7/8" W x 1 5/8" H	600	41 4100K
	12 12W	17 3/4" L x 7/8" W x 1 5/8" H	800	64 6400K
	16 16W	19 1/2" L x 7/8" W x 1 5/8" H	1000	BK Black
	20 20W	21 1/4" L x 7/8" W x 1 5/8" H	1350	BU Blue
	22 22W	29 1/4" L x 7/8" W x 1 5/8" H	1850	GN Green
	24 24W	34 5/8" L x 7/8" W x 1 5/8" H	2150	RD Red
	28 28W	46 1/2" L x 7/8" W x 1 5/8" H	2900	
SG5A	6 6W**	9 1/2" L x 7/8" W x 1 5/8" H	480	30 3000K
	8 8W**	12 1/2" L x 7/8" W x 1 5/8" H	600	35 3500K
	14 14W	22 7/8" L x 7/8" W x 1 5/8" H	1350	41 4100K
	21 21W	34 5/8" L x 7/8" W x 1 5/8" H	2150	50 5000K
	28 28W	46 1/2" L x 7/8" W x 1 5/8" H	2900	64 6400K
	35 35W	58 1/4" L x 7/8" W x 1 5/8" H	3650	BK Black
				BU Blue
SG5AHO	24 24W	22 7/8" L x 7/8" W x 1 7/8" H	2200	30 3000K
	39 39W	34 5/8" L x 7/8" W x 1 7/8" H	3500	35 3500K
	54 54W	46 1/2" L x 7/8" W x 1 7/8" H	5000	41 4100K
				50 5000K
				64 6400K
				BU Blue
				GN Green
				RD Red

* Based on 4100K lamps.

** Not available with a Rocker Switch.

SG4A

SLEEK PLUS ADJUSTABLE - T4

T4	120V AC	87+ CRI	DRY	360°	UL LISTED
----	---------	---------	-----	------	-----------

Max Run: Fixtures combined up to 350W

Includes: (1) T4 lamp, (1) SG-DC, (2) Mounting Clips

Dimming: No

SG5A

SLEEK PLUS ADJUSTABLE - T5

T5	120V AC	87+ CRI	DRY	360°	UL LISTED
----	---------	---------	-----	------	-----------

Max Run: Fixtures combined up to 350W

Includes: (1) T5 lamp, (1) SG-DC, (2) Mounting Clips

Dimming: No

SG5AHO

SLEEK PLUS ADJUSTABLE - T5HO

T5HO	120V AC	87+ CRI	DRY	360°	UL LISTED
------	---------	---------	-----	------	-----------

Max Run: Fixtures combined up to 350W

Includes: (1) T5HO lamp, (1) SG-DC, (2) Mounting Clips

Dimming: No

ACCESSORIES Page 49

TO ORDER

MODEL	WATTS	SWITCH	CCT	FINISH
SG4A	-	SW - On/Off	/	S - Silver
SG5A	-	Switch	-	W - White
SG5AHO	-	(Optional)	-	

Specifications subject to change without notice.
See spec sheet or jescolighting.com for more details.

RIGID LINEAR • SLEEK PLUS TWIN ADJUSTABLE



Backlighting up and down:
SG5AT

SG5AT

SLEEK PLUS TWIN ADJUSTABLE - T5

T5	120V AC	87+ CRI	DRY	360°	UL LISTED
----	------------	------------	-----	------	--------------

Max Run: Fixtures combined up to 350W

Includes: (2) T5 lamps, (1) SG-DC, (2) Mounting Clips

Dimming: No

SG5ATHO

SLEEK PLUS TWIN ADJUSTABLE - T5HO

T5HO	120V AC	87+ CRI	DRY	360°	UL LISTED
------	------------	------------	-----	------	--------------

Max Run: Fixtures combined up to 350W

Includes: (2) T5HO lamps, (1) SG-DC, (2) Mounting Clips

Dimming: No



Patented 360°
adjustable light barrel

ACCESSORIES Page 49

TO ORDER

MODEL	WATTS	SWITCH	CCT	FINISH
<input type="text"/>	-	<input type="text"/>	/	<input type="text"/>
SG5AT		SW - On/Off		S - Silver
SG5ATHO		Switch		W - White
		(Optional)		

Specifications subject to change without notice.
See spec sheet or jescolighting.com for more details.


WATTAGE, DIMENSIONS & LUMEN DATA

Model	Watts	Dims	Lumens*	CCT
SG5AT	14 (2) 14W	22 7/8" L x 2 7/8" W x 7/8" H	1350	30 3000K
	21 (2) 21W	34 5/8" L x 2 7/8" W x 7/8" H	2150	35 3500K
	28 (2) 28W	46 1/2" L x 2 7/8" W x 7/8" H	2900	41 4100K
	35 (2) 35W	58 1/4" L x 2 7/8" W x 7/8" H	3650	50 5000K
				64 6400K
				BK Black
				BU Blue
				GN Green
				RD Red
SG5ATHO	24 (2) 24W	22 7/8" L x 2 7/8" W x 7/8" H	2200	30 3000K
	39 (2) 39W	34 5/8" L x 2 7/8" W x 7/8" H	3500	35 3500K
	41 (2) 41W	46 1/2" L x 2 7/8" W x 7/8" H	5000	41 4100K
	54 (2) 54W	58 1/4" L x 2 7/8" W x 7/8" H	5000	50 5000K
				64 6400K
				BU Blue
				GN Green
				RD Red

* Based on 4100K lamps.

SLEEK ACCESSORIES & COMPONENTS

	Description	Model	SG-LED p. 45	SGA-LED p. 45	SG4 p. 46	SG5 p. 46	SG5HO p. 46	SG4A p. 47	SG5A p. 47	SG5AHO p. 47	SG5AT p. 48	SG5ATHO p. 48
	Direct Connector	SG-DC	•	•	•	•	•	•	•	•	•	•
	3" Connecting Cable 6" Connecting Cable 12" Connecting Cable 24" Connecting Cable 36" Connecting Cable 48" Connecting Cable	SG-CC3 SG-CC6 SG-CC12 SG-CC24 SG-CC36 SG-CC48	•	•	•	•	•	•	•	•	•	•
	3" Right Angle Connecting Cable 6" Right Angle Connecting Cable 12" Right Angle Connecting Cable 24" Right Angle Connecting Cable 36" Right Angle Connecting Cable 48" Right Angle Connecting Cable	SG-CC3L SG-CC6L SG-CC12L SG-CC24L SG-CC36L SG-CC48L	•	•	•	•	•	•	•	•	•	•
	2' White Power Cord & Plug 6' White Power Cord & Plug 6' Grey Power Cord & Plug 8' White Power Cord & Plug 12' White Power Cord & Plug	SG-PC24-WH SG-PC72-W SG-PC72-G SG-PC96-W SG-PC144-W	•	•	•	•	•	•	•	•	•	•
 	6' Right Angle Power Cord & Plug (From Back) 6' Right Angle Power Cord & Plug (From Front)	SG-PCL SG-PCLL	•	•	•	•	•	•	•	•	•	•
 SG-MC-V SG-MC-45	Stainless Steel Mounting Clip for Vertical & Horizontal Mount (included with fixture) 45° Mounting Clip <i>Consult factory for 30° or 60° mounting clips.</i>	SG-MC-V SG-MC-45	•	•	•	•	•	•	•	•		
 SG-MC-VH	Stainless Steel Mounting Clip for Vertical Mount	SG-MC-VH	•	•	•	•	•	•	•	•		
 SG-MC-A	Adjustable Mounting Clip	SG-MC-A	•	•	•	•	•	•	•	•		
	Commercial Grade Metal Hard-Wire Box Enables Fixtures to be Controlled by Wall Switch Dims: 2 3/4" L x 1 3/4" W x 1 3/4" H	SG-BM	•	•	•	•	•	•	•	•	•	•
	Commercial Grade Metal Hard-Wire Box with On/Off Switch Dims: 3 1/2" L x 2" W x 1 1/2" H	SG-BM-SW	•	•	•	•	•	•	•	•	•	•
	Plastic Hard-Wire Box with On/Off Switch Dims: 3 5/8" L x 2 1/4" W x 1 5/8" H	SG-B	•	•	•	•	•	•	•	•	•	•
	Sleek Plus Power Strip with 6 Outlets Dims: 72" L x 3/8" W x 3/8" H Includes: (1) Direct Connector	SG-PS6	•	•	•	•	•	•	•	•	•	•





FORM + FUNCTION

- Designed for applications where the height of the lit shelves is constantly adjusted up and down to accommodate merchandise display changes in retail settings
- The low profile Smart Track system distributes power to multiple movable shelves with power feeds that slide along a vertically mounted track
- Compatible with S601P, S601, S602P, S902, the DL-FLEX Series, DL-FLEX-HD, the asymmetrical, magnetic-backed S650, and our bespoke CBF fixture
- The field-cuttable Smart Track mounts easily with supplied double-sided adhesive or mounting clips

APPLICATIONS

- Store Fixture Shelving & Cashwraps highlighting featured items
- Product Displays in Showrooms, Retail Stores and Office Workstations
- Museums, Galleries & Antique Store Lighting
- Bar Shelves, Wind & Liquor Displays in Restaurants and Bars
- Under Countertop Lighting for dramatic effects
- Case Lighting for Bookcases, China & Glassware Cabinets and Trophy Cases





DL-FLEX SERIES
LED Flexible Linear – Standard (DL-FLEX-UP), High-Output (DL-FLEX-UP-HO), Ultra-High Output (DL-FLEX-UP-ULTRA) and DL-FLEX-UP-NIC



DL-FLEX HD
High Density LED Strip




S601, S601P, S602P SERIES
LED Slim Strip



CBF
Commercial Bespoke Slim Led Fixture with pre-attached connecting cable



S902
LED Shelf/Under Cabinet Fixture with custom connecting cable



S650 SERIES
LED Shelf Light

SMART TRACK ACCESSORIES

	ST-PF-I-WH Input Power Feed Voltage: 24V DC Max Input: 100W Dimensions: 1" W x 1" H x 1 1/2" L Material: Plastic Color: White
	ST-PF-O-WH Output Power Feed Voltage: 24V DC Max Output per Feed: 72 W Dimensions: 1" W x 1" H x 1" L Material: Plastic Color: White
	ST-MC-CL Mounting Clip - Clear (2) Included with each Track
	ST-MMC-CL Mid Mounting Clip - Clear (3) Included with each Track
	ST-PF-O-CC2-WH 2 1/4" Interconnection Power Cable Use to link multiple lengths of track

	ST-DL-FLEX-PC15-WH ST-DL-FLEX-PC24-WH Input Power Connector Cable for DL-FLEX Length: 15", 24"
	ST-DL-FLEX-HD-PC15-WH ST-DL-FLEX-HD-PC24-WH Input Power Connector Cable for DL-FLEX-HD Length: 15", 24"
	S601-CC3 S601-CC6 S601-CC12 S601-CC15 (white only) S601-CC24 S601-CC48 Input Power Connector Cable for S601 Finish: BK - Black WH - White Length: 3", 6", 12", 15", 24", 48"
	ST-S650-PC24 24" Input Power Connector Cable for S650

Consult factory for custom colors and lengths.

ST-TR

8' SMART TRACK



Max Input: 100W

Max Output Load per Feed: 72 W

Dims: 47 1/4" L, 60", 96" L x 3/8" W x 5/16" H

Material: Plastic

Includes: (2) Mounting Clips
(3) Mid Mounting Clips
(3) End Caps and double sided adhesive

Environment: Indoor - Dry

Specifications subject to change without notice.
See spec sheet or jescolighting.com for more details.

TO ORDER

MODEL	LENGTH	FINISH
ST-TR	4 - 47 1/4" L 5 - 60" L 8* - 96" L	WH - White CL - Clear

Contact factory for more lengths.
* 8' Smart Track available in Clear finish only
Specifications subject to change without notice.
See spec sheet or jescolighting.com for more details.

RADIANZ REMOTE POWER SYSTEM

The new **RADIANZ** Remote Power System, designed for use with JESCO's broad range of LED lighting products, provides the perfect solution for powering stand-alone exhibits, kiosks and gondolas, both permanent or temporary, without the cost of bringing power to the fixtures. The designer has the freedom to plan the space effectively to maximize traffic flow without being limited by the location of the power source. These exhibits can be easily relocated as the needs of the space change, without the cost of re-wiring the space.

The **RADIANZ BATT-LI** series is a portable, lithium-ion battery pack. Available in three capacities, the **RADIANZ** powers all of JESCO's 12V, 24V or 350mA LED fixtures at the lowest cost per watt hour in the market. Plug & Play power connections, an on/off switch, a four-level charge indicator, and an audible low battery warning make the battery pack very user-friendly. A plug-in charger is provided with each battery. A 100% charge is achievable in 3-5 hours depending on the capacity.

BATT-LI

RADIANZ REMOTE POWER SYSTEM

Input Charging Voltage: 13V / 60W - use supplied charger

Output Voltage/Current: 12V / 24V / 350mA

Capacity: 100Wh / 150Wh / 266Wh

Full charge time: 3 hours / 4 hours / 5 hours

Integral USB Port: Yes (100Wh, 150Wh)




Cycle Life: >500 times, then 80% capacity

Environment: Indoor - Dry

TO ORDER

MODEL	-	OUTPUT	-	CAPACITY
BATT-LI	-		-	
		12V - 12V		100WH - 100Wh
		24V - 24V		150WH - 150Wh
		350MA - 350 mA		266WH - 266Wh

See spec sheet or jescolighting.com for more details.



ADDITIONAL FEATURES

- LED charge level indicator
- Quick re-charging
- Over-discharge protection
- Over-charge protection
- Short-circuit protection
- Audible low battery warning
- 100Wh and 150Wh capacity batteries come with a 5V USB port for charging phones and tablets - max output 2A

APPLICATIONS

- Temporary & Permanent Exhibits
- Gondolas
- Kiosks
- Islands
- Trade Show Booths
- Display Windows
- Jewelry Cases
- Museum Displays
- Pop-ups



COMPATIBLE PRODUCTS

DISPLAY LIGHTING

ARC201	page 23
SD100	page 13
SD105	page 14
SD106	page 18
SD107	page 16
SD109	page 16
SD110	page 29
SD111	page 29
SD112	page 29
SD120	page 29
SD183	page 12
SD283	page 11
SD300	page 17
SD302	page 19
SD304	page 15
SD383	page 10
SDL	page 20







PK811	page 27
PK820	page 26
PK921	page 28
PK923	page 28
RZ-SM	page 30

RIGID LINEAR









CBF	page 9, 34
DL-RS	page 41
RZ-TR	page 43
S601, S602P	page 37
S602	page 35
S650	page 38
S902	page 39

FLEXIBLE LINEAR (see FLEX catalog)

24V PP LED POWER SUPPLIES • 24V DC • PLUG & PLAY

	Description	Model	S601, S601P p. 37	S602P p. 35	S650 p. 38	S902 p. 39	DL-RS (indoor) p. 41	PK900 p. 28	CBF p. 9	S602P p. 35	SD283 p. 11	SD383 p. 10	SDLL p. 20
	Wall Plug Power Supply May be dimmed with LC-DIM5A 3 1/4" L x 1 3/4" W x 1 1/4" H Input/Output: 100 - 240V AC / 24V DC Wattage: 24W Max c-UL-us Listed. LPS.	DL-PS-WP24/24	•	•	•	•	•	•	•	•	•	•	•
	Desktop Power Supply May be dimmed with LC-DIM5A. 3 1/2" L x 1 1/2" W x 1" H Input/Output: 100 - 240V AC / 24V DC Wattage: 24W Max c-UL-us Listed. LPS.	DL-PS-24/24	•	•	•	•	•	•	•	•	•	•	•
	Desktop Power Supply May be dimmed with LC-DIM5A. 4 3/8" L x 2" W x 1 1/2" H Input/Output: 100 - 240V AC / 24V DC Wattage: 48W Max c-UL-us Listed. LPS.	DL-PS-48/24	•	•	•	•	•	•	•	•	•	•	•
	Desktop Power Supply May be dimmed with LC-DIM5A 4 1/4" L x 2" W x 1 1/2" H Input/Output: 100 - 240V AC / 24V DC Wattage: 60W Max c-UL-us Listed. LPS.	DL-PS-60/24	•	•	•	•	•	•	•	•	•	•	•
	Desktop Power Supply May be dimmed with LC-DIM5A 5 3/4" L x 2 1/2" W x 1 1/4" H Input/Output: 100 - 240V AC / 24V DC Wattage: 90W Max c-UL-us Listed. LPS.	DL-PS-100/24	•	•	•	•	•	•	•	•	•	•	•
	Desktop Power Supply 7 7/8" L x 2 3/4" W x 1 3/8" H Input/Output: 100 - 120V AC / 24V DC Wattage: 96W Max 47" 18AWG SVT output wire Class 2 c-UL-us Listed.	DL-PS-100/24-CL2	•	•	•	•	•	•	•	•	•	•	•

24V HW LED POWER SUPPLIES • 24V DC • HARD WIRE ELECTRONIC

	Description	Model	p. 37 \$601P	p. 38 \$650	p. 39 \$902	p. 41 DL-RS (outdoor)	p. 41 DL-RS (indoor)	p. 28 PK900	p. 9 CBF	p. 35 \$602P	p. 11 SD283	p. 10 SD383	p. 20 SDLL
	Hard Wire LED Power Supply Dimmable with TRIAC dimmer Auto-reset protection 4 15/16" L x 1 63/64" W x 25/32" H Input/Output: 120V AC / 24V DC Wattage: 40W (8W minimum load) Class 2 c-UR-us Recognized. IP 67.	DL-PS-40/24-HW-DIM	•	•	•	•	•		•	•	•	•	•
	Hard Wire LED Power Supply Dimmable with TRIAC dimmer Auto-reset protection 4 15/16" L x 1 63/64" W x 25/32" H Input/Output: 120V AC / 24V DC Wattage: 60W (8W minimum load) Class 2 c-UR-us Recognized. IP 67.	DL-PS-60/24-HW-DIM	•	•	•	•	•		•	•	•	•	•
	Hard Wire LED Power Supply Dimmable with TRIAC dimmer Auto-reset protection 4 15/16" L x 1 63/64" W x 25/32" H Input/Output: 120V AC / 24V DC Wattage: 96W (8W minimum load) Class 2 c-UR-us Recognized. IP 67.	DL-PS-100/24-HW-DIM	•	•	•	•	•		•	•	•		
	Hard Wire Power Supply 3" L x 1 1/2" W x 1" H Input/Output: 100-240V AC / 24V DC Wattage: 12W Max Class 2 c-UR-us Recognized.	DL-PS-12/24-HW	•	•	•		•	•	•	•	•	•	•
	Hard Wire Power Supply 4 5/8" L x 1 3/8" W x 1" H Input/Output: 100-240V AC / 24V DC Wattage: 20W Max Class 2 c-UR-us Recognized.	DL-PS-20/24-HWA	•	•	•		•	•	•	•	•	•	•
	Hard Wire Power Supply 6 1/2" L x 1 3/4" W x 1 3/8" H Input/Output: 100-240V AC / 24V DC Wattage: 60W Max Class 2 c-UR-us Recognized.	DL-PS-60/24-HWA	•	•	•		•	•	•	•	•	•	•
	Hard Wire Power Supply 8 3/4" L x 2 3/4" W x 1 1/2" H Input/Output: 100-240V AC / 24V DC Wattage: 96W Max Class 2 c-UR-us Recognized.	DL-PS-96/24-HWA	•	•	•		•	•	•	•	•	•	
	Hard Wire Power Supply with Terminal Block Connection 8" L x 2 7/8" W x 1 1/2" H Input/Output: 100-240V AC / 24V DC Wattage: 96W Max Class 2 c-UR-us Recognized.	DL-PS-100/24-TB	•	•	•		•	•	•	•	•		

See Specs for more details. Specifications are subject to change without notice.

24V LED POWER SUPPLIES • 24V DC • HARD WIRE IN JUNCTION BOX ENCLOSURE*

	Description	Model	S601P, S601	S650	S902	DL-RS (outdoor)	DL-RS (indoor)	PK900	CBF	S602P	SD283	SD383	SDLL
			p. 37	p. 38	p. 39	p. 41	p. 41	p. 28	p. 9	p. 35	p. 11	p. 10	p. 20
	LED Power Supplies with Aluminum Enclosure 8 3/8" L x 2 3/8" W x 2 1/8" H Input/Output: 100-240V AC / 24V DC ¹ Wattage: 20W Max Class 2 c-UR-us Recognized.	DL-PS-20/24-JBA	•	•	•		•	•	•	•	•	•	•
	LED Power Supplies with Aluminum Enclosure 10 1/8" L x 2 3/8" W x 2 1/8" H Input/Output: 100-240V AC / 24V DC ¹ Wattage: 60W Max Class 2 c-UR-us Recognized.	DL-PS-60/24-JBA	•	•	•		•	•	•	•	•	•	•
	LED Power Supplies with Aluminum Enclosure 11 1/8" L x 3 3/8" W x 2 1/8" H Input/Output: 90 - 305V AC / 24V DC ¹ Wattage: 96W Max Class 2 c-UR-us Recognized.	DL-PS-96/24-JBA	•	•	•		•	•	•	•	•	•	
	Outdoor Hardwire Power Supply in a Junction Box 13 1/2" L x 2 7/8" W x 1 1/2" H Input/Output: 100-240V AC / 24V DC Wattage: 80W Max Class 2 c-UR-us Listed for dry, damp, or wet location use Integrated dimmer - see spec sheet.	DL-PS-80/24-JB-OD	•	•	•	•	•	•	•	•			
	Outdoor Hardwire Power Supply in a Junction Box 11 1/2" L x 2 1/2" W x 1 5/8" H Input/Output: 100 - 277V AC / 24V DC Wattage: 96W Max Class 2 c-UR-us Listed for dry, damp, or wet location use.	DL-PS-96/24-JB-OD	•	•	•	•	•	•	•	•			
	LED Power Supply with Junction Box Enclosure Dimmable with TRIAC dimmer 6 11/16" L x 2 43/64" W x 1 1/4" H Input/Output: 120V AC / 24V DC Wattage: 40W (8W minimum load) Class 2 c-UR-us Listed. IP 67.	DL-PS-40/24-JB-DIM	•	•	•	•	•		•	•	•	•	•
	LED Power Supply with Junction Box Enclosure Dimmable with TRIAC dimmer 10 1/8" L x 2 3/8" W x 2 1/8" H Input/Output: 120V AC / 24V DC Wattage: 60W (8W minimum load) Class 2 c-UR-us Listed. IP 67.	DL-PS-60/24-JB-DIM	•	•	•	•	•		•	•	•	•	•
	LED Power Supply with Junction Box Enclosure Dimmable with TRIAC dimmer 11 1/8" L x 3 3/8" W x 2 1/2" H Input/Output: 120V AC / 24V DC Wattage: 96W (8W minimum load) Class 2 c-UR-us Listed. IP 67.	DL-PS-100/24-JB-DIM	•	•	•	•	•		•	•	•	•	

* Power Supplies can be purchased without junction box enclosure - see www.jescolighting.com





¹ May be dimmed with LC-DIM5A-HW.

² For 277V AC input, consult factory for details.





See Specs for more details. Specifications are subject to change without notice.

POWER SUPPLIES • 12V LED POWER SUPPLIES

12V PP LED POWER SUPPLIES • 12V DC • PLUG & PLAY

	Description	Model	p. 12 SD183	p. 13 SD100	p. 14 SD105	p. 23 ARC201	p. 26 PK820	p. 27 PK811	p. 16 SD109
	Plug & Play Wall Plug Power Supply May be dimmed with LC-DIM5A 2 7/8" L x 1 3/8" W x 2 1/8" H Input/Output: 100-240V AC / 12V DC Wattage: 24W Max c-UL-us Listed. LPS.	DL-PS-WP24/12	•	•	•	•	•	•	•
	Plug & Play Desktop Power Supply May be dimmed with LC-DIM5A 3 1/2" L x 1 1/2" W x 1" H Input/Output: 100-240V AC / 12V DC Wattage: 24W Max c-UL-us Listed. LPS.	DL-PS-24/12	•	•	•	•	•	•	•
	Plug & Play Desktop Power Supply May be dimmed with LC-DIM5A 3 1/2" L x 1 1/2" W x 1" H Input/Output: 100-240V AC / 12V DC Wattage: 30W Max c-UL-us Listed. LPS.	DL-PS-30/12	•	•	•	•	•	•	•
	Plug & Play Desktop Power Supply May be dimmed with LC-DIM5A 3 5/8" L x 1 3/4" W x 1 1/4" H Input/Output: 100-240V AC / 12V DC Wattage: 60W Max c-UL-us Listed. LPS.	DL-PS-60/12	•	•	•	•	•	•	

12V HW LED POWER SUPPLIES • 12V DC • HARD WIRE

	LED Power Supply 4 5/8" L x 1 3/8" W x 1" H Input/Output: 100-240V AC / 12V DC Wattage: 20W	DL-PS-20/12-HWA	•	•	•	•	•	•	•
	LED Power Supply 6 1/2" L x 1 3/4" W x 1 3/8" H Input/Output: 100-240V AC / 12V DC Wattage: 60W	DL-PS-60/12-HWA	•	•	•	•	•	•	•
	LED Power Supply Dimmable with MLV & TRIAC dimmer 4 15/16" L x 1 63/64" W x 25/32" H Input/Output: 120V AC / 12V DC Wattage: 40W (8W minimum load) SAM rated. Class 2 c-UR-us Recognized. Nema 3R - Outdoor Use	DL-PS-40/12-HW-DIM	•	•	•	•	•	•	•
	LED Power Supply Dimmable with MLV & TRIAC dimmer 4 15/16" L x 1 63/64" W x 25/32" H Input/Output: 120V AC / 12V DC Wattage: 60W (8W minimum load) SAM rated. Class 2 c-UR-us Recognized. Nema 3R - Outdoor Use	DL-PS-60/12-HW-DIM	•	•	•	•	•	•	•

12V JB LED POWER SUPPLIES • 12V DC • HARD WIRE IN JUNCTION BOX ENCLOSURE *















	LED Power Supply with Aluminum Enclosure 10 1/8" L x 2 3/8" W x 2 1/8" H Input/Output: 90 - 264V AC / 12V DC ¹ Wattage: 60W Max Class 2 c-UR-us Recognized	DL-PS-60/12-JBA	•	•	•	•	•	•	•
---	--	------------------------	---	---	---	---	---	---	---

* Power Supplies can be purchased without junction box enclosure - see www.jescolighting.com

¹ May be dimmed with LC-DIM5A-HW.

See Specs for more details. Specifications are subject to change without notice.





LED LED POWER SUPPLIES • 24V/12V DC • PLUG & PLAY ACCESSORIES

	Description	Model	p. 12	p. 13	p. 14	p. 23	p. 26	p. 27	p. 16	p. 37	p. 38	p. 39	p. 41	p. 28	p. 9	p. 35	p. 11	p. 10	p. 20
			SD183	SD100	SD105	ARC201	PK820	PK811	SD109	S601	S650	S902	DL-RS (indoor)	PK900	CBF	S602P	SD283	SD383	SDLL
	2-Way Split Power Feed Connects multiple home runs to a single power supply. May be used with other splitters Feed: 7 1/2" L Connector Runs: 10 3/4" L	DL-PS-2Y	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
	3-Way Split Power Feed Connects multiple home runs to a single power supply. May be used with other splitters Feed: 11 1/4" L Connector Runs: 12 1/4" L	DL-PS-3Y	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
	4" Male 2-Wire Input Power Connector For connecting plug-and-play supplies to hard-wire equipment or lighting controllers	DL-PS-PT-M	•	•	•	•	•	•	•	•			•	•	•	•	•	•	•
	12" Female 2-Wire Output Power Connector For connecting plug-and-play supplies to hard-wire equipment or lighting controllers	DL-PS-PT-F	•	•	•	•	•	•	•	•			•	•	•	•	•	•	•
	48" LED Driver Extension Cable Black 48" LED Driver Extension Cable White	DL-PS-EXT48 DL-PS-EXT48-WH	•	•	•	•	•	•	•	•		•	•	•	•	•	•	•	•
	96" LED Driver Extension Cable Black 96" LED Driver Extension Cable White	DL-PS-EXT96 DL-PS-EXT96-WH	•	•	•	•	•	•	•			•	•	•	•		•	•	•
	1-Port Distribution Block Connects (1) fixture	DB-CV-DC/AMP1												•					
	1-Port Hard Wire Distribution Block Connects (1) fixture	DB-CV-HW/AMP1												•					
	3-Port Distribution Block Connects up to (3) fixtures 6-Port Distribution Block Connects up to (6) fixtures	DB-CV-DC/AMP3 DB-CV-DC/AMP6												•					
	3-Port Hard Wire Distribution Block Connects up to (3) fixtures 6-Port Hard Wire Distribution Block Connects up to (6) fixtures	DB-CV-HW/AMP3 DB-CV-HW/AMP6												•					
	12VDC 36" Extension Cable with PD connector	DB-CV-EXT-PD/PD-36	•	•	•	•	•	•	•								•	•	•
	12VDC 3" Adapter Cable HW to female PD connector	PS-CV-HW/PDF-3	•	•	•	•	•	•	•								•	•	•
	12VDC 6-port Constant Voltage Distribution Box with PD in/out connector	DB-CV-PD/PD-6	•	•	•	•	•	•	•								•	•	•
	12VDC 3" Adapter Cable DC to female PD connector	PS-CV-DC/PDF-3	•	•	•	•	•	•	•								•	•	•





See Specs for more details. Specifications are subject to change without notice.

TRANSFORMERS & ACCESSORIES

TR PP TRANSFORMERS • 12V AC ELECTRONIC • PLUG & PLAY



	Description	Model	LOW VOLTAGE MINI RECESSED p. 31
	Class 2 Plug & Play Transformer Output: 12V / 60W Finish: Black, White	XF60P3-BK XF60P3-WH	•
	Plug & Play Transformer Output: 12V / 80W Dimmable with ELV dimmers	XF-80C	•
	Plug & Play Transformer Output: 12V / 105W Dimmable with ELV dimmers	XF-105C	•
	Plug & Play Transformer Output: 12V / 150W Dimmable with ELV dimmers	XF-150C	•

TR HW TRANSFORMERS • 12V AC ELECTRONIC • HARD WIRE






	Hard Wire Transformer 4 1/8" L x 2 3/8" W x 1 7/8" H Input/Output: 120V - 12V, 50/60Hz Max/Min Watt: 60W/10W c-UL-us Class 2	XF-60	•
	Hard Wire Transformer 2 5/8" L x 1 3/8" W x 1 1/8" H Input/Output: 120V - 12V, 60Hz Max/Min Watt: 80W/20W	XF-80	•
	Hard Wire Transformer Dimmable with ELV Dimmers. No Twist, Push Wire Conductor Terminals Included 2 1/4" L x 1 1/4" W x 7/8" H Input/Output: 120V - 12V, 60Hz Max/Min Watt: 80W/20W	XF-80S	•
	Hard Wire Transformer Dimmable with Incandescent or ELV Dimmers. No Twist, Push Wire Conductor Terminals Included 4 3/8" L x 2 7/8" W x 1 1/4" H Input/Output: 120V - 12V, 60Hz Max/Min Watt: 105W/35W	XF105D	•

See Specs for more details. Specifications are subject to change without notice.






CC PP LED POWER SUPPLIES • CONSTANT CURRENT • PLUG & PLAY

	Description	Model	SD110 p. 29	SD111 p. 29	SD112 p. 29	SD120 p. 29	SD107 p. 16	SD300 p. 17	SD304 p. 15	SD106 p. 18	SD302 p. 19
	350mA Constant Current 8W Wall Plug Power Supply Output: 3 - 36V DC 72" 20 AWG wire length. Class 2 c-UL-us for dry locations only.	PS-CC-350/8-WP	•	•	•	•	•	•	•	•	
	350mA Constant Current 12W Wall Plug Power Supply Output: 3 - 36V DC Min Load: 3W 30" 20 AWG wire length. Class 2 c-UL-us for dry locations only.	PS-CC-350/12-WP	•	•	•	•	•	•	•	•	

CC HW LED POWER SUPPLIES • CONSTANT CURRENT • HARD WIRE

	350mA Constant Current 36W Hard Wire Power Supply 6 7/8" L x 1 7/8" W x 1 1/16" H Input: 110-277V AC (15W minimum load) c-UL-us Recognized.	PS-CC-350/36-HW	•	•	•	•	•	•	•	•	
	700mA Constant Current 12W Hard Wire Power Supply 4 7/8" L x 1 7/8" W x 3/4" H Input: 100 - 240V AC Class 2 c-UL-us Recognized.	PS-CC-700/12-HW									•
	700mA Constant Current 30W Hard Wire Power Supply 6 3/8" L x 2" W x 7/8" H Input: 100 - 240V AC Class 2 c-UL-us Recognized.	PS-CC-700/30-HW									•
	350mA Constant Current 12W Hard Wire Power Supply 3" L x 1 1/16" W x 1 1/8" H Input: 90 - 264 V AC Class 2 c-UL-us, LPS, Dry location only.	PS-CC-350/12-HW-M	•	•	•	•	•	•	•	•	
	350mA Constant Current 16W Hard Wire Power Supply 3" L x 1 1/16" W x 1 1/8" H Input: 90 - 264 V AC Class 2 c-UL-us, LPS, Dry location only.	PS-CC-350/16-HW-M	•	•	•	•	•	•	•	•	

CC LED POWER SUPPLIES • CONSTANT CURRENT • ACCESSORIES

	6-Port Distribution Block with PB input and output connector Includes 5 jumpers	DB-CC-R-PB/PB-6	•	•	•	•	•	•	•	•	•
	3" Adaptor Cable DC to PB connector	PS-CC-R-DC/PBF-3	•	•	•	•	•	•	•	•	•
	36" Extension Cable with PB Connectors Extends run between fixture and distribution block	PS-CC-R-EXT-PB-36 PS-CC-R-EXT-PBF-36	•	•	•	•	•	•	•	•	•
	Jumper for Plug Type B Must be plugged into unused slots of distribution block to complete the circuit	DB-CC-PB-JP	•	•	•	•	•	•	•	•	•
	2 Conductor Lever Nut 28 to 12 AWG (stranded or solid) 600V / 20A Max Strip length : 3/8" c-UL-us listed	DL-PS-222-412	•	•	•	•	•	•	•	•	•

See Specs for more details. Specifications are subject to change without notice.

DIM LED DIMMING CONTROLLER SOLUTIONS

Control Type		Model	Description
Basic <ul style="list-style-type: none"> Plug and Play In-line dimmer control 		LC-DIM5A	12V/24V Plug & Play Dimmer 4 1/4" L x 1 7/8" W x 1 1/8" H Max Output: 60W @ 12V DC 120W @ 24V DC Built in 0-10V Dimming Control. Smooth dimming. 0-10V dimming control with rotary knob for precise dimming. Compatible with DL-PS plug and play power supplies.
Basic <ul style="list-style-type: none"> Hard wire 0-10V with compatible driver 		LC-DIM-01-HW	5V-24V Hard Wire Dimmer Interface 4 1/4" L x 1 3/4" W x 1 1/8" H Max Output: 196W Output Current: 8A 100%-15% dimming. Performance vary based on LED product and installation Requires additional 0-10V dimmer switch
Architectural <ul style="list-style-type: none"> Hard wire 0-10V dimming interface for simple wall plate dimmers or architectural dimming systems Tested and approved by Lutron and Crestron with select dimmers Compatible with DS-DV-TV-WH wall dimmer switch 		LC-DIM5A-HW	6 1/4" L x 3" W x 1 1/2" H Max Output: 60W @ 12V DC 120W @ 24V DC Requires separate 0-10V Dimmer Switch (DS-DV-TV-WH). Smooth dimming. 0-10V dimming interface, requires additional 0-10V dimmer switch or consult dimming control manufacturer for more information.
Wall Plate 0-10V Dimmer Switch <ul style="list-style-type: none"> Hard wire White Finish Replaces old model DL-PS-DS-TV 		DS-DV-TV-WH	2 5/8" L x 1 3/4" W Use with LC-DIM5A-HW or LC-DIM-01-HW Smooth dimming. Wall plate dimmer switches to dim our magnetic power supplies are provided by others. See the product specification sheets for a listing of approved models.
Basic <ul style="list-style-type: none"> Hard wire or Plug and Play† Greater flexibility of control and installation Remote control dimmer Max 1 dimmer per location Max remote distance: 50 feet 		LC-DIM200-RF-HW	4 1/4" L x 2 1/8" W x 1 3/8" H Max Output: 60W @ 12V DC 96W @ 24V DC Key chain remote control switch with on/off function and local control. Use only one LC-DIM200-RF-HW per location. LC-DIM200-RF-HW cannot be synchronized with one another. Can be converted to plug and play by adding DL-PS-PT-M and DL-PS-PT-F connectors.
Advanced Radio Frequency Dimmer Controller <ul style="list-style-type: none"> Touch wheel Includes wall mount remote holder 4 controllable zones Unlimited number of receivers per zone 3 savable scenes/colors per zone Brightness control Required LC-RF-400-RCV 		LC-RF-400H-DIM	Remote Dims: 4 3/4" L x 2 3/16" W x 1 1/8" H Operating Voltage: 3.6V DC (3 x AAA batteries) Working Frequency: 434 MHz Remote Distance: 100ft. Max
Wall Mounted Radio Frequency Dimmer Controller <ul style="list-style-type: none"> Fits standard single gang switch boxes Utilizes a battery for wireless installation Required LC-RF-400-RCV 		LC-RF-400W-DIM	Receiver Dims: 4 3/4" L x 2 15/16" W Operating Voltage: 3V DC (CR2025 battery) Working Frequency: 434 MHz Remote Distance: 100ft. Max
Wall Mounted Dual Radio Frequency Dimmer Controller <ul style="list-style-type: none"> Allows for 2 zone dimming Fits standard double gang switch boxes Required LC-RF-400-RCV 		LC-RF-402W-DIM	Receiver Dims: 4 3/4" L x 2 15/16" W Operating Voltage: 12-24V DC Working Frequency: 434 MHz Remote Distance: 100ft. Max
Radio Frequency Receiver <ul style="list-style-type: none"> Works with LC-RF-400H-DIM LC-RF-400W-DIM LC-RF-402W-DIM 		LC-RF-400-RCV	Receiver Dims: 7 1/8" L x 1 13/16" W x 3/4" H Input: 12-24V DC Channels: 4 Output: 384 Watts Max (96W Max per channel) 5A Max per channel






For Low Voltage Magnetic Dimming applications refer to DL-PS-xx/24-JBM Power Supplies (dimmers supplied by others).

Interference, noise control/reduction, and voltage drop must be taken into consideration when installing dimming controls. Installing low voltage cable near line voltage wiring may cause interference and result in flickering.







It is highly recommended the dimmer and power supply be installed as close as possible to the LED fixture(s) to maintain signal integrity. Long wiring runs can produce a significant drop in the signal level resulting in different light levels by the same control device. Installation wiring longer than 30 feet, or where excessive electrical noise exists, should be tested for signal integrity prior to installation. Shielded cable or conduit should be considered during the installation to reduce interference and electrical noise.

Always install according to NEC and local codes.

RGB LED RGB CONTROLLER SOLUTIONS

Control Type		Model	Description
Basic Radio Frequency <ul style="list-style-type: none"> Controlled with remote up to 30 feet away Controller can be hidden Max 1 controller per location 		LC-RF-300	<p>3 1/4" L x 2 1/2" W x 1" H Max Output: 432 Watts Max (6A per channel) Accepts P&P and HW power supplies Remote Distance: 30' Max Remote control with touch sensitive color wheel</p> <p>Allows user to control RGB lights from remote location without line of sight. Recommended only one controller per location due to potential interference with other RF type controllers. Color wheel allows user to easily select specific colors Includes 15 pre-set color changing models, on/off function, brightness and speed control</p>
Infrared <ul style="list-style-type: none"> Controlled with remote up to 30 feet away Receiver must be visible for remote, requires line of sight to function Multiple controllers possible per location 		LC-IR-300	<p>2 1/2" L x 1 3/8" W x 7/8" H Max Output: 144 Watts Max (2A per channel) Includes 44 key remote control 6 user-defined savable colors Remote Distance: 30' Max Includes terminal block</p> <p>Infrared controller requires user to point in the general direction of the receiver to function properly. Allows use of multiple controllers per location. Remote has 6 buttons that allow the user to save custom colors Line of sight control allows multiple controllers per location Accepts P&P power supplies</p>
Advanced Radio Frequency RGB Controller <ul style="list-style-type: none"> Touch wheel. Includes wall mount remote holder. 4 controllable zones Unlimited number of receivers per zone 3 savable scenes/colors per zone Brightness control 10 built-in color changing modes Required LC-RF-400-RCV 		LC-RF-400H-RGB	<p>Remote Dims: 4 3/4" L x 2 3/16" W x 1 1/16" H Operating Voltage: 3.6V DC (3 x AAA batteries) Working Frequency: 434 MHz Remote Distance: 100ft. Max</p>
Advanced Wall Mount Radio Frequency RGB Controller <ul style="list-style-type: none"> Touch wheel control Allows for single zone color control with 3 savable colors Required LC-RF-400-RCV 		LC-RF-410W-RGB	<p>Receiver Dims: 4 3/4" L x 2 15/16" W Operating Voltage: 12-24V DC Working Frequency: 434 MHz Remote Distance: 100ft. Max</p>
Radio Frequency Receiver <ul style="list-style-type: none"> Works with LC-RF-400H-RGB LC-RF-410W-RGB 		LC-RF-400-RCV	<p>Receiver Dims: 7 1/16" L x 1 13/16" W x 3/4" H Input: 12-24V DC Channels: 4 Output: 384 Watts Max (96W Max per channel) 5A Max per channel</p>


















DMX LED DMX CONTROLLER SOLUTIONS

Control Type		Model	Description
DMX <ul style="list-style-type: none"> Architectural lighting control programmed via software installed in a computer 16 million colors to program User can create their own scenes, color changes, fades Can control multiple lighting systems independently or simultaneously Custom programming available - consult factory 		LC-PC-100	Simple DMX Controller 2 3/4" L x 3 3/8" W x 1 1/2" H Must be programmed with included software Simple desktop DMX controller pre-programmed for basic functionality. Simple 2 button interface for scene selection. Best for single RGB lighting systems
		LC-PC-400	Simple Wall Mount DMX Controller 3 3/8" L x 3 3/8" W x 7/16" H Must be programmed with included software Features Touch-Screen Wall Plate Simple wall mount DMX controller with touch sensitive glass faceplate. Touchscreen features 3 modes: color selection, scene selection, and dimmer mode. Best for single RGB lighting systems
		LC-PC-500	Advanced Wall Mount DMX Controller 6 5/8" L x 5" W x 1/2" H Must be programmed with included software Features Touch-Screen Wall Plate Advanced wall mount DMX controller with touch sensitive glass faceplate. Allows 5 different lighting systems to be controlled simultaneously. Features Ethernet network ability to allow control with Apple IOS or Google Android devices
REPEATER <ul style="list-style-type: none"> For extending runs in dimming and color changing applications 		LC-200-RPT	12V/24V Power Repeater 6 1/2" L x 1 1/2" W x 1" H Requires additional DL-PS power supply Size power supply to connected load Input to LC-200-RPT can be at the end or start of fixture run
INTERFACE <ul style="list-style-type: none"> Assigns a DMX address to RGB or CTA LED light sources 		LC-200-INT	DMX Interface 7" L x 1 1/2" W x 1 1/8" H Requires a DMX controller RJ45 connector for DMX input 170 unique DMX addresses, 512 channels Works with CTA and RGB flexible light strips 12V and 24V DC compatible
		LC-300-INT	Advanced DMX Interface 6 1/2" L x 2 25/64" W x 1 9/32" H Channels: 3 or 4 Max Load: 96W-288W per channel Max Current: 8A per channel Requires a DMX controller Assigns DMX address to LED fixtures Works with CTA, RGB, and RGBW flexible light strips 12V and 24V DC compatible

Interference, noise control/reduction, and voltage drop must be taken into consideration when installing dimming controls. Installing low voltage cable near line voltage wiring may cause interference and result in flickering.

It is highly recommended the dimmer and power supply be installed as close as possible to the LED fixture(s) to maintain signal integrity. Long wiring runs can produce a significant drop in the signal level resulting in different light levels by the same control device. Installation wiring longer than 30 feet, or where excessive electrical noise exists, should be tested for signal integrity prior to installation. Shielded cable or conduit should be considered during the installation to reduce interference and electrical noise.

Always install according to NEC and local codes.

LIGHTING SOLUTIONS 	INFINA® AC LED Flexible Light Strip 	FLEX Linear LED Line & Low Voltage Series 	Recessed Modulinear 	Recessed Downlights 
TRACK LIGHTING 	ENVISAGE V Ceiling & ADA Wall Sconces 	ENVISAGE VI Decorative Mini Pendants 	ENVISAGE VII LED Pendants & Wall Sconces 	RADIANZ Portable Power System 
Edge-Lit LED Flat Panels 	WW2 LED Wall Washers & Flood Lights 	Architectural Pendants & Wall Sconces 	SMART TRACK Adjustable Low Voltage Power System 	MLX MULTI-LINK Modular Linkable LED Linear Fixture 
RADIANZ Display Lighting 	RELYENCE LED Lighting Distributor Program 			



Project: Tropicana Casino, Atlantic City NJ
North Tower Casino
Photographer: John DiMaio
Architect: SOSH Architects
Millwork: Trade Images



LOOK TO OUR NEW LINEAR FLEXIBLE LED CATALOG



120V LED STRIP – INFINA® & INFINA® ACX™

- Patented
- Up to 150' runs in precise 4" increments
- Smooth ELV dimming
- No in-line drivers required
- Indoor/Outdoor, Plug-in/Hard Wired



24V LED OUTDOOR STRIP – FLEX

- Multiple levels of output and wattages
- Up to 50' runs
- Made to order or field-cuttable



24V LED INDOOR STRIP – FLEX

- Multiple levels of output and wattages
- Multiple levels of LEDs per foot
- On-board Constant Current IC-chips for uniform intensity & output
- Simple snap-together connections



12V LED MODULES

- Indoor/Outdoor
- Multiple levels of output & wattages
- Perfect for signage or curved surfaces
- Individually addressable LED modules



24V LED RGB, RGBW & COLOR TUNING WHITE

- Works with Simple RGB or complex DMX controls
- Up to 16 million colors can be achieved
- Tunable White from 2400K to 7000K
- JESCO offers assistance with setting up your schemes



MOUNTING CHANNELS

- Surface or Recessed mounting
- Multiple levels of depth
- Lensed or open
- Indoor/Outdoor

A			
ACC-MT-MAG-01-SET	41	DL-PS-100/24-CL2	53
ACC-MT-MAG-02	35, 37	DL-PS-100/24-HW-DIM	54
ARC201CV-4W	23	DL-PS-100/24-JB-DIM	55
ARC201CV-8W	23	DL-PS-100/24-TB	54
		DL-PS-222-412	59
B		DL-PS-EXT48	57
BATT-LI	52	DL-PS-EXT48-WH	57
		DL-PS-EXT96	57
C		DL-PS-EXT96-WH	57
CBF	9, 34	DL-PS-OD-2Y	41
CH-SM-31-CLIP	9, 34	DL-PS-OD-3Y	41
CH-SM-31-CLIP-A	9, 34	DL-PS-OD-EC	41
		DL-PS-OD-EXT18	41
D		DL-PS-OD-EXT48	41
DB-CC-PB-JP	59	DL-PS-OD-EXT96	41
DB-CC-R-PB/PB-6	59	DL-PS-OD-PT-F	41
DB-CV-DC/AMP1	57	DL-PS-OD-PT-M	41
DB-CV-DC/AMP3	57	DL-PS-OD-RGB-2Y	41
DB-CV-DC/AMP6	57	DL-PS-OD-RGB-3Y	41
DB-CV-EXT-PD/PD-36	57	DL-PS-OD-RGB-EC	41
DB-CV-HW/AMP1	57	DL-PS-OD-RGB-EXT18	41
DB-CV-HW/AMP3	57	DL-PS-OD-RGB-EXT48	41
DB-CV-HW/AMP6	57	DL-PS-OD-RGB-EXT96	41
DB-CV-PD/PD-6	57	DL-PS-OD-RGB-PT-F	41
DL-PS-2Y	57	DL-PS-OD-RGB-PT-M	41
DL-PS-3Y	57	DL-PS-PT-F	57
DL-PS-12/24-HW	54	DL-PS-PT-M	57
DL-PS-20/12-HWA	56	DL-PS-WP24/12	56
DL-PS-20/24-HWA	54	DL-PS-WP24/24	53
DL-PS-20/24-JBA	55	DL-RS	41
DL-PS-24/12	56	DL-RS-C-12	41
DL-PS-24/24	53	DL-RS-C-24	41
DL-PS-30/12	56	DL-RS-C-36	41
DL-PS-40/12-JB-DIM	56	DL-RS-C-48	41
DL-PS-40/24-HW-DIM	54	DL-RS-C-72	41
DL-PS-40/24-JB-DIM	55	DL-RS-MC-1	39, 41
DL-PS-48/24	53	DL-RS-RGB	41
DL-PS-60/12	56	DS-DV-TV-WH	60
DL-PS-60/12-HWA	56		
DL-PS-60/12-JBA	56	K	
DL-PS-60/12-JB-DIM	56	KIT-RZ-EXT SM RD3	30
DL-PS-60/24	53	KIT-RZ-EXT SM SQ3	30
DL-PS-60/24-HWA	54	KIT-RZ-SM RD3	30
DL-PS-60/24-HW-DIM	54	KIT-RZ-SM SQ3	30
DL-PS-60/24-JBA	55		
DL-PS-60/24-JB-DIM	55	L	
DL-PS-80/24-JB-OD	55	LC-200-INT	62
DL-PS-96/24-HWA	54	LC-200-RPT	62
DL-PS-96/24-JBA	55	LC-300-INT	62
DL-PS-96/24-JB-OD	55	LC-DIM-01-HW	60
DL-PS-100/24	53	LC-DIM5A	60
		LC-DIM5A-HW	60
		LC-DIM200-RF-HW	60
		LC-IR-300	61
		LC-PC-100	62
		LC-PC-400	62
		LC-PC-500	62
		LC-RF-300	61
		LC-RF-400-DIM	60
		LC-RF-400-RCV	60, 61
		LC-RF-400-RGB	61
		LC-RF-400W-DIM	60
		LC-RF-402W-DIM	60
		LL-MR16-6W-38-2780	31
		LL-MR16-6W-38-3080	31
		LL-MR16-6W-38-4080	31
		LL-MR16-7HW-40-2780	31
		LL-MR16-7HW-40-3080	31
		LL-MR16-7HW-40-4080	31
		P	
		PK811CV-4W	27
		PK811CV-8W	27
		PK820CV-4W	26
		PK820CV-8W	26
		PK921	28
		PK923	28
		PKH900A	28
		PS-CC-350/8-WP	59
		PS-CC-350/12-HW-M	59
		PS-CC-350/12-WP	59
		PS-CC-350/16-HW-M	59
		PS-CC-350/36-HW	59
		PS-CC-R-DC/PBF-3	59
		PS-CC-R-EXT-PB-36	59
		PS-CC-R-EXT-PBF-36	59
		PS-CV-DC/PDF-3	57
		PS-CV-HW/PDF-3	57
		R	
		RH25	31
		RH27	31
		RH29	31
		RH30	31
		RH42	31
		RH46	31
		RH49	31
		RZ-SM-DB4	30
		RZ-SM-PS-24/24SW	30
		RZ-SM-RD	30
		RZ-SM-SQ	30
		RZ-T12	43
		RZ-T18	43
		RZ-T24	43

RZ-TR-CC06	43	SD109CV	16	SG-PC144-W	49
RZ-TR-CC12	43	SD110CC	29	SG-PCL	49
RZ-TR-CONN	43	SD111CC	29	SG-PCLL	49
RZ-TR-DMEC	43	SD112CC	29	SG-PS6	49
RZ-TR-PFEC	43	SD120CC	29	ST-DL-FLEX-HD-PC15-WH	51
RZ-TR-PS-24/24	43	SD183CV-6W	12	ST-DL-FLEX-HD-PC24-WH	51
RZ-TR-RD	43	SD183CV-8W	12	ST-DL-FLEX-PC15-WH	51
RZ-TR-SM-CC60	43	SD283CV-4W	11	ST-DL-FLEX-PC24-WH	51
RZ-TR-SQ	43	SD283CV-6W	11	ST-MC-CL	51
S		SD300CC	17	ST-MMC-CL	51
S601	37	SD302CC	19	ST-PF-I-WH	51
S601-CC03	35, 37, 51	SD304CC	15	ST-PF-O-CC2-WH	51
S601-CC6	35, 37, 51	SD383CV	10	ST-PF-O-WH	51
S601-CC12	35, 37, 51	SDCL	20	ST-S650-PC24	38, 51
S601-CC15	35, 37, 51	SDL	20	ST-TR	51
S601-CC24	35, 37, 51	SDL-CC2	21		
S601-CC48	35, 37, 51	SDLL CV	20	X	
S601-CH6	37	SDL-PC	21	XF-60	58
S601-CH6T	37	SG4	46	XF60P3-BK	58
S601-EC	37	SG4A	47	XF60P3-WH	58
S601-FLX-CONN	35, 37	SG5	46	XF-80	58
S601-MC	37	SG5A	47	XF-80C	58
S601P	37	SG5AHO	47	XF-80S	58
S601-PC	35, 37	SG5AT	48	XF-105C	58
S601-PC-HW	35, 37	SG5ATHO	48	XF105D	58
S601-SW	35, 37	SG5HO	46	XF-150C	58
S602-EC	35	SGA-LED	45		
S602-MC	35	SG-B	49		
S602P	35	SG-BM	49		
S650	38	SG-BM-SW	49		
S650-MC	38	SG-CC3	49		
S650-PC	38	SG-CC3L	49		
S650-PC-CC6	38	SG-CC6	49		
S650-PC-CC12	38	SG-CC6L	49		
S650-PC-CC24	38	SG-CC12	49		
S650-PC-HW	38	SG-CC12L	49		
S902	39	SG-CC24	49		
S902-CC3	39	SG-CC24L	49		
S902-CC6	39	SG-CC36	49		
S902-CC12	39	SG-CC36L	49		
S902-CC24	39	SG-CC48	49		
S902-CC48	39	SG-CC48L	49		
S902-PC	39	SG-DC	49		
S902-PC-HW	39	SG-LED	45		
SD100CC-R-MB1	13	SG-MC-45	49		
SD100CC-R-MC	13	SG-MC-A	49		
SD100CV	13	SG-MC-V	49		
SD105CV-6W	14	SG-MC-VH	49		
SD105CV-8W	14	SG-PC24-WH	49		
SD106CC	18	SG-PC72-G	49		
SD107CC	16	SG-PC72-W	49		
		SG-PC96-W	49		



For more details and product
specifications please visit
JESCOLIGHTING.COM



NEW YORK
CORPORATE OFFICES
15 Harbor Park Drive
Port Washington NY 11050
TEL 800 527 7796
FAX 855 265 5768

LOS ANGELES
219 South 6th Avenue
City Of Industry CA 91746
TEL 626 333 3661
TEL 855 654 0110
FAX 626 333 2955

DALLAS SHOWROOM
Dallas Trade Mart
Showroom TM 4313
2100 N. Stemmons Freeway
Dallas TX 75207

JESCOLIGHTING.COM
info@jescolighting.com

© 2017 JESCO Lighting

LCAT-SLS4



Project: The Frye Company
Roosevelt Field Mall
Garden City, NY
Millwork: JPMA, Montreal