

FIG. A





FIG. B



SOCKET TYPE MAY VARY:


- 1) Turn off power.
- 2) Slip knobs on top of socket/ballast into keyholes in base (attached to fixture).
- 3) Turn socket/ballast clockwise to secure in place.
- 4) Lock socket/ballast by pushing tabs up into slots in base. (Ref. FIG. A)

OR:

- 1) Turn off power.
- 2) Slip knobs on top of socket/ballast into keyholes in base (attached to fixture).
- 3) Turn socket/ballast clockwise to secure in place. (Ref. FIG. B)

- 1) Turn off power.
- 2) Slip knobs on top of socket into keyholes in ballast (attached to fixture.) REF. FIG. A.
- 3) Turn socket clockwise to secure in place.
- 4) Find the appropriate threaded holes on mounting strap. Assemble mounting screws into threaded holes.
- 5) Attach mounting strap to outlet box. (Screws not provided). Mounting strap can be adjusted to suit position of fixture.
- 6) Grounding instructions: (See Illus. A or B).
- A) On fixtures where mounting strap is provided with a hole and two raised dimples. Wrap ground wire from outlet box around green ground screw, and thread into hole.
- B) On fixtures where a cupped washer is provided. Attach ground wire from outlet box under cupped washer and green ground screw, and thread into mounting strap.


If fixture is provided with ground wire. Connect fixture ground wire to outlet box ground wire with wire connector. (Not provided.) After following the above steps. Never connect ground wire to black or white power supply wires.



- 7) Make wire connections (connectors not provided.) Reference chart below for correct connections and wire accordingly.

Connect Black or Red Supply Wire to:	Connect White Supply Wire to:
Black	White
*Parallel cord (round & smooth)	*Parallel cord (square & ridged)
Clear, Brown, Gold or Black without tracer	Clear, Brown, Gold or Black with tracer
Insulated wire (other than green) with copper conductor	Insulated wire (other than green) with silver conductor

*Note: When parallel wires (SPT I & SPT II) are used. The neutral wire is square shaped or ridged and the other wire will be round in shape or smooth (see illus.)



- 8) Push fixture to wall, carefully passing mounting screws through holes.
- 9) Secure fixture to wall using threaded balls.

