

PROJECT:
TYPE:
ORDERING # :
COMMENTS:

LED Side Mount








FEATURES

- LED technology is combined with a side mount design for more directional lighting, without glare. Coordinates with matching LED deck light 15765.
- Cast Aluminum Housing.
- High-Low Setting – Low: 2.5 W / 4 VA Light Output, High: 4 W / 5.8 VA Light Output
- Integrated LEDs and Driver, 2950K (-150/+175), High CRI.
- 9V - 15V AC/DC
- 53" of usable #18-2, SPT-1-W leads. Cable connector supplied.
- 8" In-ground stake



ORDERING INFORMATION

EXAMPLE: 15815AZT (Product # & Finish)

PRODUCT	FINISH	WATTAGE	LIGHT SOURCE	WIRING	MOUNTING ACCESSORIES (INCLUDED)	OPTIONS & ACCESSORIES																																			
15815 Dimensions: 6" W x 20" L	Cast Aluminum AZT - Textured Architectural Bronze™ 	Low Setting: 2.5 W / 4 VA High Setting: 4 W / 5.8 VA Note: Not for use with electronic transformers.	Integrated LEDs and Driver 2950K (-150 / +175) High CRI	53" of usable #18-2, SPT-1-W leads. Cable connector supplied.	8" In-ground stake	15601AZT - Cast Aluminum Surface Mounting Flange w/ Bronze Finish, Neoprene Gasket For Watertight Seal																																			
	BE - Beach 					15601BKT - Cast Aluminum Surface Mounting Flange w/ Black Finish, Neoprene Gasket For Watertight Seal																																			
	BKT - Textured Black 					15601BBR - Cast Brass Surface Mounting Flange, Neoprene Gasket For Watertight Seal 																																			
	Fixture Photometric (fc)– High Setting <table border="1"> <tr> <td>Distance from Light</td> <td>0'</td><td>1'</td><td>2'</td><td>3'</td><td>4'</td><td>5'</td><td>6'</td><td>7'</td><td>8'</td> </tr> <tr> <td>Footcandles</td> <td>31.5</td><td>17.2</td><td>6.7</td><td>2.5</td><td>1.2</td><td>0.5</td><td>-</td><td>-</td><td>-</td> </tr> </table> Fixture Photometric (fc) – Low Setting <table border="1"> <tr> <td>Distance from Light</td> <td>0'</td><td>1'</td><td>2'</td><td>3'</td><td>4'</td><td>5'</td><td>6'</td><td>7'</td><td>8'</td> </tr> <tr> <td>Footcandles</td> <td>21.3</td><td>12</td><td>4.1</td><td>1.7</td><td>0.7</td><td>0.2</td><td>-</td><td>-</td><td>-</td> </tr> </table>					Distance from Light	0'	1'	2'	3'	4'	5'	6'	7'	8'	Footcandles	31.5	17.2	6.7	2.5	1.2	0.5	-	-	-	Distance from Light	0'	1'	2'	3'	4'	5'	6'	7'	8'	Footcandles	21.3	12	4.1	1.7	0.7
Distance from Light	0'	1'	2'	3'	4'	5'	6'	7'	8'																																
Footcandles	31.5	17.2	6.7	2.5	1.2	0.5	-	-	-																																
Distance from Light	0'	1'	2'	3'	4'	5'	6'	7'	8'																																
Footcandles	21.3	12	4.1	1.7	0.7	0.2	-	-	-																																
						Polycarbonate Lens 15677CLR - Accessory lens of clear polycarbonate plastic. Provides additional internal protection from lawn sprinklers, etc. 																																			

NOTES

For Warranty Information, please visit www.landscapelighting.com

We reserve the right to revise the design or components of any product due to parts availability or change in UL standards, without assuming any obligation or liability to modify any products previously manufactured, and without notice.

