

ASSEMBLING & INSTALLATION INSTRUCTIONS PRODUCT# 8520-64

WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER .

ASSEMBLING THE FIXTURE (Fig.1)

1. Put the glass shade (B) over the socket cup (A).
2. Put the check ring (C) into the glass shade (B) and cover the socket.
3. Thread the socket ring (D) on to the socket and secure the glass shade.

HANGING THE FIXTURE (Fig.3)

1. Disconnect power at main electrical panel before installation.
2. Thread the two mounting screws about 1/4" into the pre-drilled holes in the mounting plate, spaced about the same distance apart as the holes in the fixture back plate. Attach the mounting plate to the junction box using two junction box screws. The side of the mounting plate marked "GND" must face out.
3. Guide fixture wires through hole in center of mounting plate then cover the junction box with canopy, aligning the screw of mounting plate with the hole of canopy and lock it with brass ball.
4. Using proper chain pliers to open one end link of the chain provided and connect to the fixture loop (A). Close the link.
5. By measuring, determine correct number of links needed for proper hanging height. Using proper chain pliers disconnect and discard remaining chain.
6. Open the other end link of the chain and hang the fixture on the loop at the ceiling. close the link.

CONNECTING THE WIRES(Fig.2)

1. Take the black wire from the ceiling junction box and the smooth wire leg from the fixture and twist bare ends together. Twist wire connector onto end of wire until snug.
 2. Repeat same process with white junction box wire and ribbed wire leg of fixture wire. NOTE: Twist wires together in the same direction you twist the wire connector onto wires.
 3. If your junction box has a grounding wire (green or bare copper), attach this wire and the bare copper wire from the fixture together as step 1. If junction box has no ground wire, attach the bare copper fixture wire to the green ground screw on the crossbar.
 4. Tuck these wire connections neatly into the ceiling outlet box and then raise the canopy all the way to the ceiling.
 5. Install the light bulbs in accordance with the fixture specifications
- NOTE: DO NOT EXCEED THE SPECIFIED WATTAGE.**

Your installation is now complete Return power to the junction box and test the fixture.

Fig.2




Fig.3




Fig.1

