# ASSEMBLING & INSTALLATION INSTRUCTIONS PRODUCT# 8811-65 For Wall Mount Fixtures

## WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER.

#### MOUNTING THE FIXTURE

#### **Installation** (see fig.1)

- 1. Disconnect power at main electrical panel before installation.
- 2. Thread the two mounting screws about 1/4" into the pre-drilled holes in the mounting plate, spaced about the same distance apart as the holes in the fixture back plate. Attach the mounting plate to the junction box using two junction box screws. The side of the mounting plate marked "GND" must face out.
- 3.Guide fixture wires through hole in center of mounting plate
- 4. Follow wiring instructions carefully (see fig. 2)
- 5.Place the fixture body(G)over the mounting plate so that the mounting plate studs protrude through the cover plate holes and screw cap nuts (H)onto the mounting screws.
- 6.Place the socket sleeve (E)and the harp(C) over the socket of the fixture body(G),then lock it securely with the check ring (D) .Install the light bulb and put the glass shade(B)on to the harp(C),then screw the finial(A)onto the glass shade(B).
- 7.Attach the crystal(F)to the small ring and the leaf of the fixture body(G).
- 8.Install the light bulbs in accordance with the fixture's specifications. DO NOT EXCEED THE MAXIMUM WATTAGE RATING!

### Wiring (see fig.2)

- 1. Connect the electrical wires as follows. Connect the Black wire from the fixture to the black house (hot) Wire. Connect the white wire from the fixture to the white (neutral) house wire. Make sure all wire nuts are secured. You may wrap the connections with electrical tape. If your outlet box has a ground wire (green or bare copper) connect fixture's ground wire to it. Otherwise attach the bare copper fixture wire to the green ground screw on the mounting plate.
- 2. Tuck the wire connections neatly into the wall junction box.





