

## Lighting Your Life Since 1970

Product Specifications - 87005WT				
Job Name:	Job Type:			
Quantity:	Comments			



Low Profile Plus EE 1-Light Flush Mount

Finish		Glass/Shade		Product Category	
White		White		Flush Mount	
Lamping		Measurements	40.00	Shipping	
Number of Bulbs	1	Width	12.0"	Carton Weight	2.1 lbs
Light Type	Fluorescent	Height	2.5"	Carton Width	4"
Bulb Type	G10q T5 Circline	Length	N/A	Carton Height	14"
Max Bulb Wattage	22	Extension	N/A	Carton Length	14"
Max Fixture Wattage	22	Back Plate Width	N/A	Carton Cubic Feet	0.41
Rated Life	±12,000 Hours	Back Plate Height	N/A	Master Pack	6
Rated Lumens	±1,800	НСО	N/A	Master Pack Weight	17.6 lbs
Color Temp	±3,000 K	Min Overall Height	N/A	Master Pack Width	14.0"
Bulb(s)	Included	Max Overall Height	N/A	Master Pack Height	14.6"
Light Up/Down	N/A	Hanging Weight	2.1 lbs	Master Pack Length	24.1"
Beam Spread	N/A	Height Adjustable	N/A	Master Cubic Feet	2.85
CRI	N/A	Slope	N/A	UPS Shippable	Yes
Photo Cell Included	N/A	Chain Length	N/A		
Ballast/Driver/Transformer	Yes	Wire Length	N/A		
Dimmable	No	Canopy Width	N/A		
		Canopy Height	N/A		
		Canopy Length	N/A		
		., •			
Certification		Other		Equivalents	
Safety Rating	Damp	UPC Code	783209015548	Incandescent Watts	164
Energy Star	No	Shades Included	N/A	Fluorescent Watts	N/A
CA Title 24	Yes	Crystals Included	N/A		
CA Title 20	No	Diffuser Included	N/A		
ADA	No	Conversion Kit	N/A		
Dark Sky	N/A	Material	Steel		
Daik Sky	IN/A	iviatei iai	Steel		

Maxim Lighting International and all designs, logos and images © 2013 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes. Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do

the installation. Always install to a mechanically sound structure.