

## Lighting Your Life Since 1970

Product Specifications - 22296BKSN					
Job Name:	Job Type:				
Quantity:	Comments				



## 22296BKSN

**Rapture 7-Light Pendant** 

**Finish** Satin Nickel

Lamping	
Number of Bulbs	7
Light Type	Xenon
Bulb Type	G9
Max Bulb Wattage	50
Max Fixture Wattage	350
Rated Life	±2,000 Hours
Rated Lumens	±5,250
Color Temp	±2,900 K
Bulb(s)	Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	Standard

Glass/Shac											
	7	7	•	2	П.	•	/:	S	9	a	

**Canopy Length** 

Measurements	
Width	8.3"
Height	14.0"
Length	37.8"
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
HCO	N/A
Min Overall Height	N/A
Max Overall Height	57.0"
Hanging Weight	16.3 lbs
Height Adjustable	Yes
Slope	120°
Chain Length	N/A
Wire Length	94"
Canopy Width	4.5"
Canopy Height	0.8"

## **Product Category**

Island Pendant

Snipping	
Carton Weight	16.3 lbs
Carton Width	11'
Carton Height	13'
Carton Length	42'
Carton Cubic Feet	3.53
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes

ertifica	tıon		

Certification		Other	
Safety Rating	Dry	UPC Code	783209089051
Energy Star	No	Shades Included	N/A
CA Title 24	No	Crystals Included	N/A
CA Title 20	No	Diffuser Included	N/A
ADA	No	Conversion Kit	N/A
Dark Sky	N/A	Material	Stainless Steel

## **Equivalents**

13.5"

Incandescent Watts	N/A
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2013 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.