

Lighting Your Life Since 1970

Product Specifications - 23094BCPC		
Job Name:	Job Type:	
Quantity:	Comments	



23094BCPC **Cirque 6-Light Pendant**

Finish Polished Chrome

Lamping

=amping	
Number of Bulbs	6
Light Type	Xenon
Bulb Type	G9
Max Bulb Wattage	40
Max Fixture Wattage	240
Rated Life	
Rated Lumens	±0
Color Temp	
Bulb(s)	Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	N/A

Glass/Shade
Beveled Crysta

Measurements	
Width	15.0"
Height	29.5"
Length	N/A
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
НСО	N/A
Min Overall Height	N/A
Max Overall Height	56.0"
Hanging Weight	15.4 lbs
Height Adjustable	Yes
Slope	120°
Chain Length	N/A
Wire Length	N/A
Canopy Width	N/A
Canopy Height	N/A

Product Category Single Pendant

Shipping	
Carton Weight	15.4 lbs
Carton Width	20"
Carton Height	16"
Carton Length	20"
Carton Cubic Feet	3.62
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes

~	-4:5:		i	•
C.e.	rtifi	CAT	เดเ	7

o or arroad or		0
Safety Rating		UPC
Energy Star	No	Shad
CA Title 24	No	Crys
CA Title 20	No	Diffu
ADA	No	Con
Dark Sky	N/A	Mate

- (O	t	h	ρ	r
	_	٠.	•	_	

Canopy Length

Other	
UPC Code	783209004092
Shades Included	N/A
Crystals Included	N/A
Diffuser Included	N/A
Conversion Kit	N/A
Material	Metal

Equivalents

N/A

Incandescent Watts	N/A
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2013 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.