

## Lighting Your Life Since 1970

Product Specifications - 85538WTSN				
Job Name:	Job Type:			
Quantity:	Comments			



## 85538WTSN

**Linear EE 3-Light Flush Mount** 

Finish Satin Nickel		Glass/Shade White		Product Category Flush Mount	
Lamping		Measurements	44 511	Shipping	40.5.11
Number of Bulbs	3	Width	11.5"	Carton Weight	13.5 lbs
Light Type	Fluorescent	Height	0.0"	Carton Width	13"
Bulb Type	Med Bi Pin T8	Length	48.0"	Carton Height	5"
Max Bulb Wattage	32	Extension	5"	Carton Length	50"
Max Fixture Wattage	96	Back Plate Width	N/A	Carton Cubic Feet	2.00
Rated Life	±10,000 Hours	Back Plate Height	N/A	Master Pack	2
Rated Lumens	±8,400	HCO	N/A	Master Pack Weight	32.3 lbs
Color Temp	±2,700 K	Min Overall Height	N/A	Master Pack Width	13.8"
Bulb(s)	Not Included	Max Overall Height	N/A	Master Pack Height	11.3"
Light Up/Down	N/A	Hanging Weight	13.5 lbs	Master Pack Length	50.3"
Beam Spread	N/A	Height Adjustable	N/A	Master Cubic Feet	4.50
CRI	N/A	Slope	N/A	UPS Shippable	Yes
Photo Cell Included	N/A	Chain Length	N/A		
Ballast/Driver/Transformer	Yes	Wire Length	N/A		
Dimmable	N	Canopy Width	N/A		
		Canopy Height	N/A		
		Canopy Length	N/A		
		Canopy Length	14/73		
Certification		Other		Equivalents	
Safety Rating	Dry	UPC Code	783209093904	Incandescent Watts	764
Energy Star	No	Shades Included	N/A	Fluorescent Watts	N/A
-				Fluorescent watts	IN/A
CA Title 24	Yes	Crystals Included	N/A		
CA Title 20	No	Diffuser Included	N/A		
ADA	No	Conversion Kit	N/A		
Dark Sky	N/A	Material	Metal		

Maxim Lighting International and all designs, logos and images © 2013 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.