



1. If you are placing an existing fixture, disconnect and remove the old fixture. Expose the supply wiring from the outlet box.
2. Screw top threaded pipe 3 complete turns into the flat side of mounting strap and lock in place with hex nut.
3. Fasten the mounting strap to the outlet box using the two screws supplied with the outlet box.
4. Spread the electrical wires so that the black wires are on one side of the outlet box and the white wires are on the other side.

**5. Electrical connections:**

Connect the white wire(s) from the fixture to the white wire of the outlet box. Connect the black wire(s) from the fixture to the black wire of the outlet box.

- ☐ **NOTE:** Black outlet box wire may be red, round & smooth and/or have copper conductor. White outlet box wire may be square & ridged and/or have a silver conductor.

**Note: Never connect ground wire to black or white power supply wires.**

**6. Grounding Connection:**

Connect fixture ground wire to ground wire from outlet box with wire connector (not provided).

7. Place crown thru top threaded pipe so that it sits flush against ceiling. Be sure all wires are inside pan. Secure crown to ceiling by fastening lock washer and coupler onto top threaded pipe.

Note: Coupler must turn at least 3 times, if it does not you must remove coupler and lengthen threaded pipe accordingly.

8. Install bottom threaded pipe into coupler.
9. Install bulbs (not included). See relamping label located at socket area for type and maximum allowed wattage.

**10. Flush Mounts With Cap + Finial:**

Place shade thru center pipe so that top rim of glass checks properly into bottom of crown. Secure glass shade with hex nut, if provided. Do not over tighten. Then slide cap up and secure with finial.

**Flush Mounts With Only Finial-Recessed At Top:**

Place shade thru center pipe so that top rim of glass checks properly into bottom of crown. Secure glass shade with hex nut. Do not over tighten. Then secure with finial.

**Flush Mounts With Only Finial-Flat Top:**

- ☐ Place shade thru center pipe so that top rim of glass checks properly into bottom of crown. Secure glass shade with finial.