



IMPORTANT TURN OFF THE POWER AT THE MAIN FUSE OR CIRCUIT BREAKER BOX BEFORE STARTING INSTALLATION

**Carefully unpack and identify all parts.
Bulbs not included.**

1. Slip the upper glass shade and then harp through the socket. Lock harp onto socket by fastening with two thumb screws. Then secure all together by fastening counter ring onto socket.
2. Install crown:
 - A. Install the short threaded stud by screwing into hole which is located at front of arm.
 - B. Slip the break through the threaded stud.
 - C. Then install crown onto the threaded stud by fastening with a flat washer, lock washer, and hex nut.
3. Install a hex nut onto one end of threaded pipe. Leave about 3/8" (10 mm) of thread exposed. Insert same end of the threaded pipe through hole located at bottom section of harp. Lock them together by fastening another hex nut from above.
4. Install bulb (not included). See relamping label located near socket area for type and maximum allowed wattage.
5. Gently sit the lower glass shade inside of main frame. Then carefully slide them through the already installed threaded pipe until top rim of the main frame checks securely inside of crown. Lock them into position by fastening with a flat washer and hex nut. Do not over tighten. NOTE: Make certain the crown is sitting properly in between the upper glass shade and main frame. Then slip the font and secure by fastening with finial.
6. Follow enclosed "**Outdoor Fixture Installation Instructions**" for electrical and fixture installation onto house outlet box.