


IMPORTANT
TURN OFF POWER AT MAIN FUSE OR
CIRCUIT BREAKER BOX BEFORE
STARTING INSTALLATION

Carefully unpack and identify all parts before beginning assembly. Bulb not included.

1. Gently sit the lower glass shade inside of main frame.
2. Install harp onto socket by fastening with a counter ring.
3. Install bulb (not included). See relamping label located near socket area for type and maximum allowed wattage.
4. Install a hex nut onto one end of center pipe leaving about 3/8" (10 mm) of thread exposed. Install same end of threaded pipe by screwing into harp. Then tighten hex nut.
5. Sit crown securely on top of main frame. Then slip the upper glass shade through the center pipe until it checks properly on top of crown. Then slip font and rubber washer. Secure all together by fastening with finial. Do not over tighten.
6. Electrical installation onto post: If you are replacing and existing fixture, disconnect and remove the old fixture.
 - A) Slip post cup over post. Mark position of holes in post cup on post.
 - B) Remove post cup and expose the supply wiring from above post. Drill 1/8" (3mm) diameter pilot holes in post at places where marked.
 - C) Make wire connections. (wire connectors not provided). Refer to chart below for correct connections. Wire supply wires to fixture wires accordingly.

Connect Black Fixture Wire to:	Connect White Fixture Wire to:
Black Supply Wire or *Parallel cord (round & smooth)	White Supply Wire or *Parallel cord (square & ridged)
Clear, Brown, Gold or Black without tracer	Clear, Brown, Gold or Black with tracer
Insulated wire (other than green) with copper conductor	Insulated wire (other than green) with silver conductor

*Note: When parallel wire (SPT 1 & SPT2) is used. One wire is square shaped or ridged and the other wire will be round in shape or smooth. (See Illustration)



- D) Connect ground wire from supply source to fixture ground wire with connector. Never connect ground wire to black or white power supply wires. Carefully place wires inside post.
- E) Slip post cup onto post. Align holes in post cup with holes in post. Attach post cup to post with sheet metal screws.