

# LED RECESSED

Ceiling mounted • Wet location listed



## Specifications:

### P8061-28-30K

#### Description:

5" LED Round Retrofit, 600 lumens

#### Construction:

Satin White (-28)  
 Steel construction  
 Glass: White polycarbonate lens  
 Flicker-free dimming to 10% brightness with most ELV type dimmers  
 (See Dimming Notes)  
 Title 24 compliant  
 covers a standard 4" hexagonal recessed outlet box  
 Mounting strap for outlet box included  
 6" of wire supplied  
 Satin White finish  
 Flicker free dimming down to 10%  
 Flicker rate less than 30%  
 Frosted polycarbonate lens

#### Performance:

Number of Modules	1
Input Power	10.5W
Input Voltage	
Input Frequency	
Lumens/LPW	700/66 (LM-79) per module
CCT	3000K
CRI	
Life	(L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Min. Start Temp	-30° C
Max. Operating Temp	30° C
Warranty	5 year warranty
Labels	cULus Wet location listed ENERGY STAR® qualified

#### Images:



#### Dimensions:

Diameter: 6.34"

Height: 3.82"

#### Catalog number:

Base

**P8061**

Finish

**28 - Satin White**

Color Temp

**30K - 3000K**

CRI

**Blank- 90 CRI**