

LED RECESSED

Ceiling mounted • Wet location listed



Specifications:

P8080-28-30K

Description:

4" LED Round Retrofit, 600 lumens

Construction:

Satin White (-28)
 Steel construction
 Glass: White polycarbonate lens
 Flicker-free dimming to 10% brightness with most ELV type dimmers
 (See Dimming Notes)
 Title 24 compliant
 covers a standard 4" hexagonal recessed outlet box
 Mounting strap for outlet box included
 6" of wire supplied
 Satin White finish
 Flicker free dimming down to 10%
 Flicker rate less than 30%
 Frosted polycarbonate lens

Performance:

Number of Modules	1
Input Power	9.5W
Input Voltage	
Input Frequency	
Lumens/LPW	630/66 (LM-79) per module
CCT	3000K
CRI	
Life	(L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Min. Start Temp	-30° C
Max. Operating Temp	30° C
Warranty	5 year warranty
Labels	cULus Wet location listed ENERGY STAR® qualified

Images:



Dimensions:

Diameter: 5.35"

Height: 3"

Catalog number:

Base
P8080

Finish
28 - Satin White

Color Temp
30K - 3000K

CRI
Blank- 90 CRI