

ASSEMBLY INSTRUCTIONS FOR YOUR WILLIAMSBURG TUCKER CHANDELIER

IMPORTANT SAFETY INSTRUCTIONS:

*These instructions are provided for your safety. It is very important that they are read completely before beginning the installation of your fixture.

***WE STRONGLY RECOMMEND INSTALLATION BY A LICENSED ELECTRICIAN.**

*Turn off power at switch before replacing bulbs

*If any special control devices are used with this fixture, follow the instructions carefully to assure full compliance with N.E.C. requirements. If there are any questions, contact a qualified electrical contractor.

ASSEMBLY INSTRUCTIONS:

1. SHUT OFF THE MAIN ELECTRICAL SUPPLY AT THE FUSE BOX/ CIRCUIT BREAKER.
2. Remove all parts carefully from the carton. Do not throw away any parts.
3. Place the fixture on a level surface. Begin assembly by attaching the fixture to the lower canopy.
4. Attach the bottom of the extension arm to the fixture frame by placing hook (O) into loop (P) as shown in Illustration A. Thread screw (N) completely into hook (O) to secure the extension arm to the fixture frame. Attach the top of the extension arm to the lower canopy by placing loop (M) over hook (L). Repeat steps for remaining support arms.
5. Disconnect hang straight (E) from chain (G) by removing quick link (F). Keep cross bar (B), threaded tube (C), canopy (H), and collar (I) together.
6. Measure desired drop for fixture to hang and add/remove chain links with chain break tool (not included). Reattach quick link (F) to the top link of chain (G).
7. Connect the bottom of chain (G) to loop (K) using quick link (J). Thread the wires exiting loop (K) through the links in chain (G).
8. Unthread collar (I) from hang straight (E). Slide the collar down over the electrical wires and chain (G) so it sits on loop (K).
9. Slide canopy (H) down over the electrical wires and chain (G) so it sits on top of collar (I).
10. Thread wires exiting the top of chain (G) through the center of hang straight (E) and threaded tube (C). Attach hang straight (E) to the top of chain (G) using quick link (F).
11. Cut the cord to the desired length to make electrical connections. At least 8" of wire will be needed to make proper electrical connections. Lift the fixture to the ceiling and attach cross bar (B) to the outlet box using mounting screws (D).
12. Make proper electrical connections described in steps 13 - 15. A LICENSED ELECTRICIAN IS RECOMMENDED.
13. Attach ground wire from the fixture (green or copper in color) to the ground wire in outlet box. Fasten wires together with wire nut (A) and tightly wrap connection with electrical tape.
14. Attach hot wire from fixture (black in color, or smooth side of wire) to hot wire from ceiling outlet box. Fasten wires together with wire nut (A) and tightly wrap connection with electrical tape.
15. Attach neutral wire from fixture (white in color or ribbed side of wire) to neutral wire from ceiling outlet box. Fasten wires together with wire nut (A) and tightly wrap connection with electrical tape.
16. Carefully push wire connections back into ceiling outlet box. Slide canopy (H) up chain (G) and hold firmly against ceiling. Slide collar (I) up chain (G) and thread onto hang straight (E) to secure the canopy in place.
17. Insert six 60W max, type B, candelabra base bulbs into the sockets.
18. Reconnect main electrical supply at fuse box/ circuit breaker and test the fixture.

* To clean fixture, wipe with soft cloth. Do not use any chemical or abrasive cleaners. *

ASSEMBLY INSTRUCTIONS FOR YOUR WILLIAMSBURG TUCKER CHANDELIER

