

LOW-VOLTAGE PENDANTS

Coronado Pendant



DESCRIPTION

Rectangular onyx shade with metal frame. Includes low-voltage, 35 watt halogen bi-pin lamp or 8 watt replaceable 500 lumen 80 CRI 3000K LED SORAA® module and six feet of field-cutttable suspension cable.

INSTALLATION


Socket terminates with FreeJack male connector, which may be installed into a system connector. Elements ordered with a system prefix include a connector for that system. ForFor Kable Lite due to weight.

ACCESSORIES & OPTICAL CONTROLS

Swag Hook

WEIGHT

3.06lb / 1.39kg ±



onyx



white glass

ORDERING INFORMATION

700	SYSTEM	COR	COLOR	FINISH	LAMP
FJ	FREEJACK		H ONYX	Z ANTIQUE BRONZE	12 VOLT HALOGEN
MP	MONOPOINT		W WHITE GLASS	S SATIN NICKEL	-LEDS830 12 VOLT LED 80 CRI 3000K
MO	MONORAIL				-24 24 VOLT HALOGEN
MO2	TWO-CIRCUIT MONORAIL				

Note: MP includes 4" Round Flush Canopy. Note: MP includes 4 Round Flush Canopy.

When installing LED option on MO2 only magnetic transformers may be used.



TECH LIGHTING®

7400 Linder Avenue
Skokie, Illinois 60077

T 847.410.4400
F 847.410.4500

Tech Lighting, L.L.C.

700 ____ COR ____

FIXTURE TYPE: _____

JOB NAME: _____

NOTES: _____



©2015 Tech Lighting, L.L.C. All Rights Reserved. The "Tech Lighting" graphic is a registered trademark of Tech Lighting, L.L.C. Tech Lighting reserves the right to change specifications for product improvements without notification.