

POP - IN 4" LED Recessed R4DRDR/R4DRDN

WAC LIGHTING Responsible Lighting®



Fixture Type:

Catalog Number:

Project: _____

Location: _____

PRODUCT DESCRIPTION

Minimum profile downlight with driver and electrical connection box attached to fixture for easy remodel or new construction installation.

FEATURES

- Electrical wiring box directly on the back of the fixture
- Available as a remodel or new construction
- Installs into ceilings between ½" and 1½" thick
- 50,000 hour rated life
- 5 year warranty
- 90 CRI

ORDERING NUMBER

SPECIFICATIONS

Construction: Die-cast aluminum with frosted TIR lens

Input: 120V

Dimming: 100% - 10% ELV, 100% - 5% TRIAC

Harmonic Distortion (THD): <20%

Operating Temperature: -20°C (-4°F) to 40°C (104°F)

Standards: Title 24 JA8-2016 Compliant; Energy Star® rated; Wet location listed; ETL listed

	Model	Power	Beam	Max Lumens	Max CBCP	Color Temp	Finish
	R4DRDR <i>Round Remodel IC - Rated, Airtight Wet Location Listed</i>	12W	F 45°	1035	1390	930 3000K	WT White
	R4DRDN <i>Round New Construction IC - Rated, Airtight Wet Location Listed</i>	12W	F 45°	1035	1390	930 3000K	WT White

Frame-In Kit (Optional Accessory)

	Model	Notes
	R4DRDN - FRAME <i>IC - Rated, Airtight</i>	<i>Ceiling thickness: ½" - 1½"</i>

R4DRD - F930-WT

Example: **R4DRDR-F930-WT**

wacighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760